## Heavyweight noise cancellation meets lightweight comfort

- Industry-leading noise cancellation. Blocks out 96% of background noise.\*
- Up to 24 hours of talk time. Keep talking all day.
- Customizable Parrott Button<sup>TM.</sup> Get fast access to your favorite features.
- Tough, IP54-rated design. IP54-rated protection against dust and moisture.
- Comfortable headband. For all-day wear.
- $\bullet$  Voice  $control^{\ensuremath{\mathsf{TM}}}.$  Answer or reject calls with just your voice.
- Large buttons. Large, easy to locate and press buttons.
- Walk and talk. Wireless range of up to 300 feet/100 meters from paired Bluetooth  $^{\rm @}$  devices.

Engineered for superior communication in high-noise environments

## TECHNICAL SPECIFICATIONS



blueparrott GN

## BlueParrott B350-XT BPB-35020

	SFECIFICATIONS	DIUEFAITUIT DSJV-AT DFD-3302
Audio	Speaker	36mm
	Speaker sensitivity	123dB SPL at 1 mW/1 kHz
	Speaker impedance	32 Ω
	Speaker max input power	50mW
	Speaker frequency range	150-6800 Hz
	Microphone type	bi-directional electret
	Microphone frequency range	150-6800 Hz
	Microphone sensitivity	-47dBV/Pa
Ease of use	Paired devices	Up to 8, connected to two at the same time (multi-use)
	Wearing style	Over-the-head
	App. support	BlueParrott App & BlueParrott Updater
	Features	Answer/end/reject call, LED for power / pairing indicator, Advanced Audio Distribution (A2DP) for music, podcast and GPS streaming**, voice dialing (activate Siri®/Google Assistant <sup>™</sup> )**, voice guidance, VoiceControl (answer/reject calls using your voice), NFC, HD voice, volume up / down, Customizable Parrott Button <sup>™</sup> , IP54 water and dust resistant
Battery	Talk time	Up to 24 Hours
	Standby time	500+ hours
	Power Nap for extended standby time	N/A
	Charging time	Approx. 3 hours
	Charging cable	Standard USB-A to Micro USB connector (1m)
	Battery capacity	300mA (headset)
	USB Charging Cable	included
Connectivity	Bluetooth® wireless technology	Bluetooth wireless technology is a radio technology developed to deliver short-range wireless mobility. Bluetooth technology eliminates wires between devices, such as mobile phones and headsets, and enables communication between devices that are in close proximity to one another. Bluetooth facilitates fast, secure transmissions of both voice ar data. More information is available at www.bluetooth.com or www. bluetooth.org
	Bluetooth <sup>®</sup> compliance	Bluetooth version 5.0
	Supported Bluetooth® profiles	Advanced Audio Distribution (A2DP) v1.3.1, hands-free profile v1.7, headset profile v1.2
	Supported modes	EDR (2 and 3 Mb), SCO, eSCO, sniff mode
	Security	128 bit encryption
		128 bit encryption Up to 300 feet/100 meters**
	Operating range	128 bit encryption Up to 300 feet/100 meters** 0000
General	Operating range Pairing passkey or PIN	Up to 300 feet/100 meters** 0000
General	Operating range	Up to 300 feet/100 meters** 0000 Headset: 3.5 oz (98 grams)
General	Operating range Pairing passkey or PIN Headset and/or charging case weight Headset dimensions	Up to 300 feet/100 meters** 0000 Headset: 3.5 oz (98 grams) Headset H 165 x W 140 x D 50 mm (6.6 x 5.2 x 1.9 in)
General	Operating range Pairing passkey or PIN Headset and/or charging case weight Headset dimensions Operating temperature	Up to 300 feet/100 meters** 0000 Headset: 3.5 oz (98 grams) Headset H 165 x W 140 x D 50 mm (6.6 x 5.2 x 1.9 in) -10° C to 60° C (14 F to 140 F)
General	Operating range Pairing passkey or PIN Headset and/or charging case weight Headset dimensions	Up to 300 feet/100 meters** 0000 Headset: 3.5 oz (98 grams) Headset H 165 x W 140 x D 50 mm (6.6 x 5.2 x 1.9 in)
General	Operating range Pairing passkey or PIN Headset and/or charging case weight Headset dimensions Operating temperature Storage temperature	Up to 300 feet/100 meters** 0000 Headset: 3.5 oz (98 grams) Headset H 165 x W 140 x D 50 mm (6.6 x 5.2 x 1.9 in) -10° C to 60° C (14 F to 140 F) -10° C to 45° C (14 F to 113 F) Headset: PC/ABS, PC, silicon rubber, nylon, POM, stainless steel, foam, leatherette and TPU.
General	Operating range Pairing passkey or PIN Headset and/or charging case weight Headset dimensions Operating temperature Storage temperature Materials	Up to 300 feet/100 meters** 0000 Headset: 3.5 oz (98 grams) Headset H 165 x W 140 x D 50 mm (6.6 x 5.2 x 1.9 in) -10° C to 60° C (14 F to 140 F) -10° C to 45° C (14 F to 113 F) Headset: PC/ABS, PC, silicon rubber, nylon, POM, stainless steel, foam, leatherette and TPU. 1 BlueParrott B350-XT headset, 1 USB charging cable, vehicle charger, foam ear cushic
General	Operating range         Pairing passkey or PIN         Headset and/or charging case weight         Headset dimensions         Operating temperature         Storage temperature         Materials	Up to 300 feet/100 meters** 0000 Headset: 3.5 oz (98 grams) Headset H 165 x W 140 x D 50 mm (6.6 x 5.2 x 1.9 in) -10° C to 60° C (14 F to 140 F) -10° C to 45° C (14 F to 113 F) Headset: PC/ABS, PC, silicon rubber, nylon, POM, stainless steel, foam, leatherette and TPU. 1 BlueParrott B350-XT headset, 1 USB charging cable, vehicle charger, foam ear cushic spare microphone windscreen , quick start guide, warranty and warning leaflet
General	Operating range         Pairing passkey or PIN         Headset and/or charging case weight         Headset dimensions         Operating temperature         Storage temperature         Materials         What's in the box         Certification	Up to 300 feet/100 meters** 0000 Headset: 3.5 oz (98 grams) Headset H 165 x W 140 x D 50 mm (6.6 x 5.2 x 1.9 in) -10° C to 60° C (14 F to 140 F) -10° C to 45° C (14 F to 113 F) Headset: PC/ABS, PC, silicon rubber, nylon, POM, stainless steel, foam, leatherette and TPU. 1 BlueParrott B350-XT headset, 1 USB charging cable, vehicle charger, foam ear cushic spare microphone windscreen , quick start guide, warranty and warning leaflet Bluetooth 5.0, CE, FCC, IC, CEC, WEEE, REACH, TELEC, RSC

\*Independently verified by CJS Labs, San Francisco, CA.

\*\* Device and network dependent.

## blueparrott.com/b350-xt

BlueParrottB350-XT/techspec/05/2020

GN Making Life Sound Better FOR 150 YEARS