



PROFINET-Switch

4-port, managed

- PROFINET Conformance Class B
- Integration into the automation network with GSDML file
- Quick, simple configuration and diagnosis via PROFINET and web interface
- LLDP, DCP, SNMP, diagnosis alarms
- Media redundancy: MRP client
- Port mirroring
- Network statistics (frames and errors)
- Managed switch with 4 x 100 Mbps RJ45 ports

One of the most important functions of a PROFINET-Switch is the prioritizing of the PROFINET frame traffic in the machine network. The managed switch can differentiate whether the frame is a web query, an FTP file transmission, a media stream, or a PROFINET frame. In the case of a high transmission load, the important frames can thus be prioritized in order to prevent frame losses. With a GSDML file you can integrate the switch into your automation environment in the usual way. The supported PROFINET protocols, such as LLDP, DCP, or even diagnosis alarms, can be easily configured and administered.

Technical advantages when using a PROFINET-Switch

Prioritizing of PROFINET frames

Assignment of a configuration via the device name

Neighborhood detection

Device exchange without programming device

Ring redundancy

Each port can be activated or deactivated

Diagnostic messages for network problems

Identification and maintenance data

With this variant of the managed PROFINET-Switch, you can connect up to 4 network participants while saving time and money. If you would like to connect more participants, we recommend our 8-port managed PROFINET-Switch.

Technical specifications

General information	
Order number	700-850-4PS01
Article name	PROFINET Switch 4-port, managed
Scope of delivery	PROFINET Switch 4-port, Quick Start Guide, CD with GSDML-File
Dimensions (DxWxH)	32,5 x 58,5 x 76,5 mm
Weight	Approx. 130 g
PROFINET interface	
Number	4
Protocol	PROFINET IO Device as defined in IEC 61158-6-10
Physical layer	Ethernet

Transmission rate	max. 100 Mbps
Connection	RJ45 socket
Features	Media Redundancy Protocol (MRP), automatic addressing / topology detection (LLDP, DCP), conformance class B
Status indicator	4 LEDs, function status 8 LEDs, Ethernet status
Voltage supply	24 V DC (18...30 V DC)
Current draw	Max. 250 mA with 24 V DC
Power dissipation	Max. 2.4 W
Ambient conditions	
Ambient temperature	-40 °C ... +75 °C
Transport and storage temperature	-40 °C ... +85 °C
Relative air humidity	95 % r H without condensation
Pollution degree	2
Protection rating	IP20
Certifications	CE, UL
CE	
RoHS	Yes
REACH	Yes
UL	
UL	UL 61010-1/ UL 61010-2-201
Voltage supply	DC 24 V (18 ... 30 V DC, SELV and limited energy circuit)
Pollution degree	2
Altitude	Up to 2,000 m
Temperature cable rating	87 °C