



TENTE Industrial

Stainless Steel Castors

Series 8470



TENTE

BETTER MOBILITY. BETTER LIFE.

Stainless Steel Castors



Series 8470

TENTE Castors & Wheels
Unit B4, 3 - 29 Birnie Avenue
Lidcombe NSW 2141
Phone: 1300836831

Email: sales.au@tente.com
Web: tente.com.au

Thanks to outstanding technology and perfect craftsmanship, TENTE Stainless Steel castors are immune to exceptional operating conditions.

They show no damage, even in the long term, when exposed to water, ice, fluctuating temperatures, salt, grease or cleaning agents.

Stainless Steel castors can be specially equipped for use in particular fields of application, e.g. for use in bakeries, with heat-resistant wheels which can withstand temperatures of +280 °C.

Series 8470

Housing made of Stainless Steel, double ball bearing swivel head, wheel axle with nut

Available as:

- 8470 Swivel castor
- 8478 Fixed castor
- 8477 Swivel castor with total lock

Fittings:



Plate



Bolt hole 13 mm



Wheels:

- UFX Wheel centre: Polyamide
Tread: Elastic-tyre, grey non-marking, with small threadguards, precision ball bearing, sealed
- UFD Wheel centre: Polyamide
Tread: Elastic-tyre, grey non-marking, roller bearing, stainless
- UAD Wheel centre: Polyamide, white
Tread: Polyurethane, purple, roller bearing, stainless
- UOO Wheel: Polyamide, white, plain bearing

Wheel sizes: 80 mm to 200 mm Ø

Load capacity:

up to 500 kg per castor

Stainless Steel castors with heat resisting wheels:

Available as:

- 8470 Swivel castor
- 8478 Fixed castor

Wheels:

- IDG Wheel centre: Aluminium
Tread: heat resisting rubber, damping, with threadguards, self-lubricating bushing, temperature range from -30 °C to +250 °C

Our heat resistant wheels can be used for up to 5 minutes at an ambient temperature of 310 °C. However, the temperature of the tread must not be allowed to exceed 250 °C.

Wheel size: 100 mm Ø

Load capacity: 80 kg per castor

- BOG Wheel made of duroplastic, self-lubricating bushing, temperature range from -40 °C to +280 °C

Higher temperatures are possible in the short term. We shall be happy to advise you.

Wheel sizes – Load capacities:

- 080 mm Ø – 100 kg per castor
- 100 mm Ø – 125 kg per castor