



Factory site: 666 Xiangfu Road, Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755 Fax: +86-571-88926789 88132890

sales@hcforklift.com www.hcforklift.com



Facebook









HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.



A series pallet truck mini range I

with capacities of 1,500kg



A series pallet truck mini range II



High Performance

- / Rated capacity 1500kg, meet the needs of the majority of customers.
- / Powered by traction motor not only has good acceleration and perfect performance, but also low heat.
- / Latest CURTIS control system, precise and smooth.
- / Regenerative braking for battery recovery during travel speed reduction, anti-slope on gradient.
- / All key parts such as tiller, switches, connectors, battery indicator and hour meter all adopt the famous brand.

Comfort

- / Simple and beautiful tiller made by REMA designed to make the operator feel comfortable, all the operation can be completed by one hand.
- / Optimized designing structure to offer a good visibility and easy entrance of the pallet.
- / Built-in charger and maintenance free gel battery adopted to provide convenient usage.
- / The compact body and semicircular design provide an ideal operation in limited space, and the ability of walking upright greatly increases the convenience in
- / Standard fork height 80mm, equipped the guide device easy to get in pallets (including sealing pallets).
- / Side battery change is standard feature.

Reliability

- / 5-pivot design provide longer working life.
- / Imported waterproof connectors, all wires and cables are protected, greatly improve the reliability of the electric system.
- / Top quality hydraulic power unit applied to provide low noise, low vibration, smooth lifting and landing reliable
- / Punch formed forks to provide more strength and tip guide to provide higher efficient operation.
- / Using non-contact proximity switch, improves safety and reliability.

Standard specification

- / Permanent magnet drive motor
- / CURTIS permanent magnet controller
- / Emergency switch
- / Multi-function battery indicator
- / PU wheel
- / 1150mm fork length
- / 560mm outside fork width
- / Electronic lifting limitation
- / Non-contact proximity switch
- / Till made by REMA
- / Horn
- / Maintenance free battery
- / Internal charger
- / Walking upright / Guide device
- / Additional wheel
- / Tandem load wheel

Maintenance

nostic instrument.

is easy for service.

don't need to worry about them.

/ Built-in charger and maintenance free gel battery, you

/ Integrated battery indicator, hour meter and self-diag-

/ Full opened hood, easy accessibility of all components,

/ All shafts installed lubricated shaft sleeve and oil cup,

provide convenient maintenance and long service life.

Options

- / Different length of fork
- / Different width of outside fork
- / Single load wheel









Safety

- / Three braking system of regenerative braking, reverse current braking, parking brake, insures the safe opera-
- avoid the harm to the driver.
- / The standard equipped electronic lifting limitation protect the pump motor from damaging dramatically

- / Anti-slope on gradient can keep the safety.
- / The emergency button on the tiller head can effectively
- and more energy saving.