

PRODUCT SPECIFICATIONS FOR RM500B



WEIGHTS

Maximum Operating Weight	28400 kg
--------------------------	----------

OPERATING SPECIFICATIONS

Cutting/Mixing Width	2438 mm
----------------------	---------

Operating Speed	3.2 km/h
-----------------	----------

Maximum Cutting/Mixing Depth	508 mm
------------------------------	--------

Rotor Speed - First (at 2100 Engine rpm)	110 r/min
--	-----------

Maximum Travel Speed	10 km/h
----------------------	---------

Rotor Speed - Third (at 2100 Engine rpm)	205 r/min
--	-----------

Rotor Options	Universal, Combination, Soil
---------------	------------------------------

Rotor Speed - Second (at 2100 Engine rpm)	152 r/min
---	-----------

ENGINE

Gross Power	403 kW
-------------	--------

Engine Model	C15
--------------	-----

DIMENSIONS

Ground Clearance	506 mm
------------------	--------

Wheel Base	6.55 m
------------	--------

Length	10.32 m
--------	---------

Maximum Height	3.59 m
----------------	--------

Width

2.98 m

SERVICE REFILL CAPACITIES

Fuel Tank Capacity

1056 l

RM500B OPTIONAL EQUIPMENT

PUSH BAR

TORQUE LIMITER

PRODUCT LINK

MIRROR PACKAGE

ROLL OVER PROTECTIVE STRUCTURE

UNIVERSAL ROTOR

COMBINATION ROTOR

SOIL ROTOR

FALLING OBJECT PROTECTIVE STRUCTURE

WATER SPRAY SYSTEM

ULTRA LOW-FLOW WATER SPRAY SYSTEM

EMULSION SPRAY SYSTEM

ROADING LIGHT PACKAGE

COUNTERWEIGHT KIT

WARNING BEACON LIGHT

REMOTE CAMERA - REAR MIXING CHAMBER DOOR