



T1581

Ride-on floor scrubber

Productivity boost

Enhance your cleaning performance and keep your floors looking their best with a versatile and user-friendly mid-sized rideon scrubber. T1581 effectively cleans large hard-floor surfaces with light-to-medium dirt and stains in areas such as logistics, retail and manufacturing.



Large tank capacity

Extend runtime with large 237 L recovery tank capacity and up to 4 hours of operation with fully-charged battery.



Simple operation

User-friendly operator controls featuring one-button cleaning start-up and three pre-set scrubbing programs simplify operation and training.



Versatile cleaning performance

Maintain consistent cleaning results across uneven surfaces with self-leveling brush system that automatically adjusts to the floor surface.

Inside the T1581

- Simple operation with three pre-set programs, allowing operator to select the program that best fits their cleaning need.
- 2. Maintain cleaning performance across uneven surfaces with self-leveling system that automatically adjusts the scrub deck height to a floor's surface.
- 3. Quick, mess-free tank draining with large, pinch-style recovery tank drain hose.

- Large-capacity solution tank to clean effectively with fewer dump/fill cycles.
- 5. Consistent water pick-up with durable v-shaped squeegee design and standard Linatex® squeegee blades.
- 6. Reduce maintenance time by easily accessing daily maintenance and service areas with service-friendly design.



T1581 specifications

FEATURE DISK **CYLINDRICAL** Cleaning path 1,050 mm 1,000 mm Productivity theoretical max* 6,458 m²/h 7,085 m²/h Scrubbing speed 7.2 kmh Brush speed 200 rpm 1,000 rpm Brush pressure 116 kg 37 kg Solution tank capacity 218 L Recovery tank capacity 237 L Battery run time** up to 4 hours Battery voltage (240Ah Gel Battery) 6x 6V Dimensions (LxWxH) 2,006 x 1,376 x 1,508 mm Squeegee width 1,380 mm Weight (with heaviest battery) 840 kg 865 kg External radius (wall to wall) 2,440 mm 2.570 mm Maximum ramp climb 16% Sound level (operator's ear)*** 76 dBA 79 dBA

Specifications subject to change without notice.

For a demonstration or additional information, call **1800 226 843** or email **contactus@tennantco.com**

T1581-brochure-en-au 7/24

©2024 The Tennant Company logo and other trademarks designated with the symbol "®" are trademarks of Tennant Company registered in the United States and/or other countries. Tennant Company's products are sold and serviced through subsidiaries of Tennant Company and distributors. All rights reserved.

Tennant Australia

SPECIFICATION

Unit 2, 10 Johnston Crescent Horsley Park NSW 2175 T: 1800 226 843 (FREE CALL) T: +61 2 9839 9700 www.tennantco.com.au

contactus@tennantco.com

Tennant New Zealand

18 Onslow Ave, Papatoetoe,
Auckland, 2104
T: +64 9 253 9013
F: +64 9 253 9015
www.tennantco.co.nz
contactus@tennantco.com

^{*}Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook

^{**} Run times are based on Continuous Scrubbing Run Times

^{***} Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA