

Lithobox Technical Specifications

Manufacturer	İnceler Medikal Sağlık Hizmetleri San. Tic. Ltd. Şti.
Model	Lithobox®
User Mode	Single, Continuous, Auto
Output Energy	1-10 bar
Frequencyofuse	1 - 15 HZ
Memory	3 programmable frequency memories
Usage Power	110-240 V, 10% the AC, 50-60 Hz
Dimensions(W-L-H)	ControlUnit:320mmx350mmx120mm Weight: 5 kg
Standard Probe Sizes	0.8 mm (2.4Fr), 1.0 mm (3.0Fr), 1.2 mm (3.6Fr), 1.5 mm (4.5 Fr), 2.0 mm (6.0 Fr)
Sterilization Methods	Probe: Autoclave, Chemical or Gas Sterilization Handpiece: Chemical or Gas Sterilization
Operating environment	0°C < temperature < 40°C
Relative Humidity	0% < humidity < 60% and hygienic environment
Atmospheric Pressure	%30-75
Quality and Classification	700 - 1060 hPa EN ISO 13485:2012 According to EN 60601-1 Class I Type B According to EN 93/42 MDD Class IIb

Lithobox Set

Lithobox Main Unit	1 Unit
Hand Piece(including 3m hose)	1 Unit
Probes	5 Units
Ø 0.8 mm, length 640 mm	
Ø 1.0 mm, length 640 mm	
Ø 1.2 mm, length 640 mm	
Ø 1.5 mm, length 640 mm	
Ø 2.0 mm, length 450 mm	
Probes Cover Pipes	5 Units
Foot Pedal	1 Unit
Portable Carrying Bag	1 Unit
Medical Compressor	Optionally
Trolley	Optionally