

FIXED ANGLE NOTCHING MACHINE

FA 200/6 COD. 1460001002



In the international market, the success of IMAC notching machines is due to their versatility, exactness, solidity and to the easiness of use in the wide range of products.

The IMAC Notchers are the best due to their cutting exactitude in the different type of materials and for the clean notching issued on the metal sheet, avoiding the bothersome trimmings.

Free from oiling, they don't need any maintenance assistance.



The fixed angle notching machines are equipped with:

- Hydraulic functioning through two cylinders to grant a constant and smooth notching,
- A wide and rigid worktable with aluminium rods with directional triple functions, for the measuring the different type of notches,
- Angle squares guides equipped with nr. 3 reference holes without scales.
- Head configuration which allows the cuts longer than the blade length.
- Economic square rods,
- Cutting zone protection sheet made in Polycarbonate which allows a wide sight of the working area and maximum safety,
- Swarf collecting box.



FIXED ANGLE NOTCHING MACHINE	U.M.	FA 200/6
Blade length	mm	205
Maximum thickness of the sheet	mm	6
Maximum thickness on stainless steel	mm	4
Holddown	-	2
Blade gap automatic regulation	-	Optional
Engine	Kw	2.2
Strokes per minute	N	45
Table dimension	mm	625x954
Height of working table	mm	930
Hydraulic oil	Viscosità	46
Oil tank capacity (Oil not included)	Lt	25
Cutting angle		90
Stroke electronic control	-	Optional
Overall dimensions)	mm	920x970x1000
Approximate weight	Kg	390

ELECTRICAL SYSTEM:	
Tension Feeding	400Volt three phase 50HZ
Tension auxiliary services	24 volt with galvanic division
Operative temperature	5-40°C
Humidity	80% without condensation

<u>ACCESSORIES</u>				
DESCRIPTION	PICTURE	CODE	PRICE LIST	PRODUCT CHOSEN
Electronic stroke adjuster and potentiometer		30600165	€ 940,00	<input type="checkbox"/>
Right overturning stop		10000501	€ 75,00	<input type="checkbox"/>
Left overturning stop		10000502	€ 75,00	<input type="checkbox"/>
Disappearing stop		10000503	€ 75,00	<input type="checkbox"/>
Right table extention 500 mm long		10000506	€ 450,00	<input type="checkbox"/>
Left table extention 500 mm long		10000507	€ 450,00	<input type="checkbox"/>
Right table extention 1000 mm long		10000508	€ 685,00	<input type="checkbox"/>
Left table extention 1000 mm long		10000509	€ 685,00	<input type="checkbox"/>

Electronic stroke adjuster and potentiometer		10000619	€ 3.635,00	<input type="checkbox"/>
Kit with internal stroke bar to turn the notching machine into a small shearing machine in order to jet straps wuith a maximum lenght of 200 mm		1000628	€ 140,00	<input type="checkbox"/>
Special Voltage	/	40602005	€ 290,00	<input type="checkbox"/>
Tropicalization	/	40602007	€ 265,00	<input type="checkbox"/>
Special Painting	/	40602006	€ 295,00	<input type="checkbox"/>
First filling oil	/	40400192	€ 125,00	<input type="checkbox"/>
Packing into a fumigated wooden crate	/	40400075	€ 310,00	<input type="checkbox"/>
Packing into a fumigated wooden box	/	3105010010	€ 480,00	<input type="checkbox"/>
ATTENTION: THE COST OF ALL ACCESSORIES IS EXCLUDED FROM THE INITIAL PRICE OF SALE.				