



AT A GLANCE

- ✓ For welding, grinding, cutting, and gouging fumes
- ✓ Spacious 1500 x 700mm downdraft work bench
- ✓ Hinged side panels allow placement of longer objects on the table
- ✓ Auto-cleaning filter
- ✓ Made in Europe
- ✓ Robust 5mm HD worktop

**7 YEAR
WARRANTY
OFFER***

FEATURES

- ✓ Cleanable / reusable filter greatly extends filter life & reduces operating costs
- ✓ Consistent suction and prevention of filter clogging and air flow drop, due to cleanable filter
- ✓ Auto filter cleaning saves operator down-time (start cleaning cycle at end of shift and walk away)
- ✓ Spark deflector plate shields filter from coarse particles & sparks, virtually eliminating fire risk & extending filter life
- ✓ Large 14m² filter surface area & nanofiber structure provide high filtration efficiency and long life
- ✓ Working hour counter, filter fullness indicator, malfunction warning
- ✓ Powerful 2.2kw motor provides max airflow of 2,500m³
- ✓ Acoustic sponge sound insulation for reduced noise level

| Part No. | Description |
|----------|---|
| WC-TA400 | TA400 Table |
| 91990116 | Main cartridge filter standard F9 |
| 91990118 | Optional HEPA (high efficiency) H13 main cartridge filter |

| Specifications | |
|------------------------|-------------------------|
| Motor Power | 2.2kW |
| Power Supply | Three phase 415V 5 Pin |
| Maximum Air Flow | 2,500m ³ /hr |
| Surface Area of Filter | 14m ² |
| Filter Cleaning | Automatic |
| Table Load Capacity | 500kg |
| Body | Galvanised Steel |
| Fan | Aluminium |
| Noise | 74 dBA |
| Sound Insulation | Acoustic Sponge |
| Dimensions | W1580 x D780 x H1450mm |
| Weight | Approx. 300kg |



User guide, specs, videos