

EZ Touch I/O°

EZSeries TouchPLC 6" TFT Color

6" Color EZ Series TouchPLC - (5.7" TFT) Overview

EZ Series TouchPLC has a White LED display, 75K hrs, 5.7" diagonal touch screen with 320x240 pixel resolution and is available with 32 I/O (max) PLC base. I/O modules are not included with EZ Series TouchPLC and can be purchased separately. Please refer to EZI/O section which lists all the available modules along with part number and pricing. All these panels have a very low slim profile along with a smaller footprint on enclosures, perfect for tight spaces.



Specifications:

HMI:

- 5.7" color TFT Touchpanel, 65K colors
- 75,000 hour bulb half-life (White LED)
- NEMA 4, FDA compliant material
- 320x240 pixel resolution
- Application Memory: 2MB
- USB Type A Data log, backup & more
- USB Type B Programming
- Micro SD Card for Data logging
- Built-in Ethernet for Remote Access (PC, iOS, Android)
- 4.4" (111.8mm) installed depth



PLC:

- I/O Options: Digital (including shaft encoder inputs and PWM outputs), analog, temperature, highspeed, program storage
- · Auto-tune PID, 8 independent loops
- · Advanced mathmatical function blocks
- Total Program/Data Memory 64KB (ladder)
- 3ms Scantime for 1K Instruction
- RS232 & RS422/485 Ports
- Ethernet Expand with remote I/O up to 2048 I/O points
- · ASCII In/Out

Remote Monitoring and Control


EZRMC Mobile HMI Application for your Android and Apple Devices













EZAutomation



EZTouch I/O Flex®

EZTouch I/O Flex 7" TFT Color Panels

7" Color EzTouch I/O Flex - (7" Wide TFT) Overview

EZTouch I/O Flex has a White LED display, 75K hrs, 7" diagonal touchscreen with 800 x 480 pixel resolution and is available with 32 I/O (max) PLC base. I/O modules are not included and can be purchased separately. Please refer to EZI/O section which lists all the available modules along with part number and pricing. All these panels have a very low profile slim bezel design that provides a small footprint on enclosures, perfect for tight spaces.

Features:

HMI:

- 7" TFT (Wide) Color Touchscreens
- Built-in Image Library (4000+ Symbols)
- · Advanced Alarm Messages & Screens
- · Email & Text Message Alerts
- · Trending Graphs
- Data logging
- Up to 999 User designed screens
- Patented Online Edit of HMI (No Machine Downtime, Edit on the Fly)
 Ethernet Port for Remote Access and connectivity to PLCs, AC Drives, or 3rd party devices

 Dual Driver Support to simultaneously interface with Major Brand PLCs or AC Drives (Allen Bradley, ABB, Omron, Siemens, Mitsubishi, Automation Direct etc.)



EZ3-T7C-E-PLC-E

PLC:

- Flexible I/O (Digital, Analog, High speed counters, Temperature, PWM)
- · Auto-tune PID, up to 8 independent loops
- Advanced Math Function Blocks
- · Recipe Editing
- · Date, Time and Event Based Control
- RS232/422/485 Expansion port (up to 2048 I/O)

 Ethernet Port (Modbus Master for AC Drive or 3rd Party Device)



Remote Monitoring and Control EZRMC Mobile HMI Application for your Android and Apple Devices







7" TFT Color







Dimensions 188.34 7.42 8.03 .32





EZAutomation



EZ Touch I/O°

EZSeries TouchPLC 8" TFT Color Slim Bezel Panels

8" Color EZSeries TouchPLC - Slim Bezel (8" TFT)

These panels have a 8" diagonal touch screen, with a 640x480 pixel resolution and feature a TFT LCD (liquid crystal display) and is available with 64 I/O (max) PLC base. I/O modules are not included with EZSeries TouchPLC and can be purchased separately. Please refer to EZI/O section which lists all the available modules along with part number and pricing. All models feature a low-profile slim bezel design that provides a small footprint on your enclosure.



Remote Monitoring and Control EZRMC Mobile HMI Application for your Android and Apple Devices





Specifications:

HMI:

- 8" color TFT Touchpanel, 65K colors
- 75,000 hour bulb half-life (White LED)
- NEMA 4, FDA compliant material
- 640x480 pixel resolution
- Application Memory: 2MB
- USB Type A Data log, backup & more
- USB Type B Programming
- Micro SD Card Data logging Ethernet
- · Remote Access (PC, iOS, Android)
- 4.4" (111.7mm) installed depth


PLC:


- I/O Options: Digital (including shaft encoder inputs and PWM outputs), analog, temperature, highspeed, program storage
- Auto-tune PID, 8 independent loops
- Advanced mathmatical function blocks
- Total Program/Data Memory 64KB (ladder)
- 3ms Scantime for 1K Instruction
- RS232 & RS422/485 Ports
- Ethernet Expand with remote I/O up to 2048 I/O points
- ASCII In/Out












8" TFT Color Dimensions









EZ Touch I/O°

EZSeries TouchPLC 10" TFT Color Slim Bezel Panels

10" Color EZSeries TouchPLC - Slim Bezel (10.4" TFT)

These panels have a 10.4" diagonal touch screen, with a 800x600 pixel resolution and feature a TFT LCD (liquid crystal display) and is available with 64 I/O (max) PLC base. I/O modules are not included with EZSeries TouchPLC and can be purchased separately. Please refer to EZI/O section which lists all the available modules along with part number and pricing. All models feature a low-profile slim bezel design that provides a small footprint on your enclosure.



Remote Monitoring and Control EZRMC Mobile HMI Application for your Android and Apple Devices





Specifications:

HMI:

- 10.4" color TFT Touchpanel, 65K colors
- 75,000 hour bulb half-life (White LED)
- NEMA 4, FDA compliant material
- 800x600 pixel resolution
- · Application Memory: 2MB
- USB Type A Data log, backup & more
- USB Type B Programming
- Micro SD Card Data logging Ethernet
- · Remote Access (PC, iOS, Android)
- 4.5" (114.3mm) installed depth

PLC:

- I/O Options: Digital (including shaft encoder inputs and PWM outputs), analog, temperature, highspeed, program storage
- Auto-tune PID, 8 independent loops
- · Advanced mathmatical function blocks
- Total Program/Data Memory 64KB (ladder)
- 3ms Scantime for 1K Instruction
- RS232 & RS422/485 Ports
- Ethernet Expand with remote I/O up to 2048 I/O points
- ASCII In/Out







