



MC9300 Handheld Mobile Computer

The ultimate Android[™] ultra-rugged combination keypad/touch mobile computer

Every day, over three million workers use an MC9000 Series mobile computer to streamline processes in warehouses and manufacturing plants all over the world. But now you need to handle and ship more orders every day, faster than ever. Introducing the mobile computer that can get it done, the MC9300 — the next evolution of the world's best-selling and most trusted enterprise mobile computer. Your workers get the ultimate in simplicity with Android, an operating system your workers already know well, a larger advanced touch display and more. Handle all of your applications with the ultimate in processing power and memory. New data capture capabilities include optional front and back cameras, extraordinary scan ranges and superior direct part mark (DPM) capture. The new battery runs twice as long as the MC9200 on a single charge. It's the most rugged MC9000 Series ever created, ready to outlast virtually every device in its class in any environment — including the freezer. New Mobility DNA solutions make device, OS security and battery management easy, while delivering better-than-ever robust wireless connections. And since you can run your existing TE apps right out of the box, migrating to Android couldn't be easier.



The Ultimate Android Platform

Maximum Processor Power and Memory

The ultra-powerful 8-core processor combines with up to eight times the RAM and 16 times the Flash memory of the MC9200 to deliver superior performance on all your voice and data apps.

Power a Full Shift and Beyond with Maximum Battery Power

The PowerPrecision+ battery delivers the most battery power in its class — nearly twice the battery run time of the MC9200, plus fast

charging and a wealth of battery statistics to better manage your battery pool. And with PowerPrecision Console, a free PC-based Mobility DNA tool, it's easy to identify and discard aging batteries, before they impact workforce productivity and your operations.

Dependably Superior WiFi Connections

With 2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO) technology and WorryFree WiFi, a free Mobility DNA tool, you get increased WiFi range and speed, near instant application response times, unmatched roaming, exceptional voice quality and network diagnostics that help keep your WiFi network up and running at peak performance.

A Lifetime Security Guard for Android

With LifeGuard[™] for Android[™], you get the security updates you need to keep your Zebra Android devices secure every day they are in service — along with easy end-to-end control of the OS update process, plus support for future versions of Android.

The Ultimate in Application Support

Run Your Terminal Emulation (TE) Apps, Right Out of the Box

Integrated support for your TE apps makes it easy to migrate from Windows to Android — no backend modification or user training required. And when you're ready to turn your 'green screen' TE apps into elegant touch-centric intuitive screens to boost productivity, Mobility DNA's All-touch TE makes it easy.







Larger Touchscreen with Advanced Technology

The large multi-touch 4.3 in. WVGA display allows your workers to view more business data, while providing best-in-class indoor/ outdoor readability and data input flexibility. Use a finger — even with a thick glove — or a stylus. And users can interact with the screen even if the display is wet.

Bluetooth Low Energy (BLE) 5.0 for Twice the Speed and Four Times the Range

Bluetooth peripheral performance is improved, while power requirements are reduced, extending battery cycle times.

Ultra High-Resolution Photos and Videos Improve Productivity The optional 13 MP color rear-facing camera captures highly

detailed photos and videos to document proof of condition, proof of compliance and more.

Rich Locationing Support

Easily implement locationing to boost operational efficiency with support for many technologies, including Visible Light Communication (VLC) via the optional front facing 5MP camera, plus WiFi, Bluetooth 5.0 BLE and Zebra's locationing solutions.

Advanced Industrial Scanning and an Extraordinary Scan Range

With our advanced scan engines, your workers can capture virtually any barcode in any condition, the first time every time. The SE4850 Extended Range Imager captures barcodes in hand and on your uppermost warehouse racks — from 3 inches to as far as 70 feet away. Our SE4770 and SE4750 imagers are ideal for standard range scanning. The SE4750 DPM enables dependable lightning-fast capture of virtually every direct part mark. And our 'tried and true' 1D SE965 engine offers Adaptive Scanning technology with the widest working range in its class.

Vibrate Feedback Mode

The optional vibrate mode is ideal in noisy warehouse environments, where the beep tone that signifies a successful scan can be virtually impossible to hear.

The Best of Both Worlds — Touchscreen and Keypad Input

Two data entry modes support TE apps today and Android intuitive, interactive apps tomorrow. Maximize key-based data entry simplicity with your choice of keypads and enable touch input for TE or Android apps now or in the future. And since you can easily swap keypads right in your facility, you can re-purpose devices or replace broken keypads instantly — no trip to the service depot and no device downtime.

Capture Multiple Barcodes and Entire Forms with a Single Scan

SimulScan makes it easy to capture labels on boxes and pallets that contain many barcodes, plus text fields.

Doubles as Walkie-Talkie

With Voice-over-IP (VoIP) support and pre-loaded PTT Express, your workers get push-to-talk capability. (License Required)

All Day Comfort in the Most Scan Intensive Apps

When you give your workers the MC9300, you give them a mobile computer designed for comfort, with the most proven ergonomics — a perfectly weighted device with a pistol-style grip.

NFC for Simple Pairing

With a quick tap, workers can pair the MC9300 with a ring scanner, mobile printer, headset and more with optional NFC.

The Ultimate Ultra-Rugged Design for Every Environment

The Most Rugged Device in its Class

When it comes to handling the harshest environments, the MC9300 is at the top of its class. The MC9300 is virtually waterproof, dropproof, dust-proof and tumble-proof, offering superior reliability. And Corning Gorilla Glass brings maximum scratch-and-impact resistance to two of the most vulnerable device features — the display and exit window.

A Model for the Most Challenging Environments

Regardless of whether your environment includes freezers, coolers or the presence of hazardous materials, there is an MC9300 model to meet your needs. The freezer model includes a heated scanner exit window and a freezer-rated battery. And the Class 1 Div 2 nonincendive model¹ enables mobile computing in areas with flammable gases and materials.

The Ultimate Accessory Ecosystem

New Accessories Minimize Charging Time, Maximize Backroom Space and More

All new charging cradles take advantage of the new fast charging feature, enabling a 90% charge in four hours or less. New cradle configurations allow you to increase density and device flexibility to make the most of your backroom area. And the universal ShareCradle base is rack mountable and can accommodate the MC9300 and other Zebra mobile computers with the addition of the right adapter cup.

Cost-Effectively Upgrade with Backwards Accessory Compatibility

Use your existing MC9200 device charging solutions by simply adding an adapter cup, as well as the soft holster and handstrap.

Specifications

or optically bonded (freezer model).BacklightLED backlit displayPowerRechargeable Li-Ion: 3.6V, 7000mAh, (Freezer Capacity battery — 5000mAh) Both batteries offer: PowerPrecision+ with improved battery technology for longer cycle times and real-time visibility into battery metrics for better battery management, fast charging (up to 2.4A); hot swap battery backup with temporary session persistenceExpansion SlotUser accessible MicroSD with 32GB SDHC and up to 256GB SDXCNetwork ConnectionsUSB 2.0 High Speed (Host and Client), WLAN and WPAN (Bluetooth)NotificationAudible tone; Multi-color LED bar (between keyboard and display), haptic feedbackKeypadBacklit, Field replaceable keypads; 58 Key Alpha- Numeric, 53 Key Alpha-Numeric STD, 53 Key Terminal Emulation (5250 and VT), 43 Key, 34 Key Numeric/Function, 29 Key Numeric/CalculationVoice and AudioSpeaker, Microphone, PTT Voice (Internal Speaker and Bluetooth Wireless Headset Support).Performance Char= CPUQualcomm Snapdragon** 660 octa-core, 2.2 GHzOperating SystemAndroid 11; upgradeable to Android 14Memory4 GB RAM/32 GB Flash pSLCUser EnvironmentStandard: -4°F to 122°F/-20°C to +50°C, Freezer: -22°F to 122°F/-30°C to +50°C, Freezer: -22°F to 122°F/-30°C to +50°C, Freezer: 5% to 95%, non-condensing; Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heate across temperature per MIL-STD-810G, 8t (.24m) drops to concrete across temperature per MIL-STD-810G.		
Display4.3 in. WVGA (800 x 480), color displayImager WindowCorning Gorilla GlassTouchpanelDual mode capacitive touch with finger, gloved finger or stylus input (conductive stylus sold separately); screen protector (sold separately); Corning Gorilla Glass with air gap (standard model or optically bonded (freezer model).BacklightLED backlit displayPowerRechargeable LI-Ion: 3.6V, 7000mAh, (Freezer Capacity battery - 5000mAh) Both batterise offer: PowerPrecision+ with improved battery technology for longer cycle times and real-time visibility into battery metrics for better battery management, fast charging (up to 2.4A); hot swap battery backup with temporary session persistenceExpansion SlotUser accessible MicroSD with 32GB SDHC and up to 256GB SDXCNetwork ConnectionsUSB 2.0 High Speed (Host and Client), WLAN and WPAN (Bluetooth)NotificationAudible tone; Multi-color LED bar (between keyboard and display), haptic feedbackKeypadBacklir, Field replaceable keypads; 58 Key Alpha- Numeric, 53 Key Alpha-Numeric STD, 53 Key Terminal Emulation (5250 and VT), 43 Key, 34 Key Numeric/Function, 29 Key Numeric/CalculationVoice and AudioSpeaker, Microphone, PTT Voice (Internal Speaker and Bluetooth Wireless Headset Support).Performance CharacteristicsCPU Qualcomm Snapdragon" 660 octa-core, 2.2 GHz Operating SystemAndroid 11: upgradeable to Android 14 Memory4 GB RAM/32 GB Flash pSLCUser EnvironmentStandard: -4*F to 122*F/-20*C to +50*C, Freezer: -22*F to 122*F/-30*C to +50*CStorage Temp40°F to 158*F/-40°C to 70*CHumidityStandard: 10 ft, (3.1m) dr	Dimensions	
Imager WindowCorning Gorilla GlassTouchpanelDual mode capacitive touch with finger, gloved finger or stylus input (conductive stylus sold separately); screen protector (sold separately); Corning Gorilla Glass with air gap (standard model or optically bonded (freezer model).BacklightLED backlit displayPowerRechargeable Li-Ion: 3.6V, 7000mAh, (Freezer Capacity battery - 5000mAh) Both batterise offer: PowerPrecision+ with improved battery technology for longer cycle times and real-time visibility into battery metrics for better battery management, fast charging (up to 2.4A); hot swap battery backup with temporary session persistenceExpansion SlotUser accessible MicroSD with 32GB SDHC and up to 256GB SDXCNetwork ConnectionsUSB 2.0 High Speed (Host and Client), WLAN and WPAN (Bluetooth)NotificationAudible tone; Multi-color LED bar (between keyboard and display), haptic feedbackKeypadBacklit, Field replaceable keypads; 58 Key Alpha- Numeric, 53 Key Alpha-Numeric STD, 53 Key Terminal Emulation (5250 and VT), 43 Key, 34 Key Numeric/Function, 29 Key Numeric/CalculationVoice and AudioSpeaker, Microphone, PTT Voice (Internal Speaker and Bluetooth Wireless Headset Support).Performance CharacteristicsCPUOperating Temp.Standard: -4°F to 122°F/-20°C to +50°C, Freezer: -22°F to 122°F/-30°C to +50°CStorage Temp40°F to 158°F/-40°C to 70°CHumidityStandard: 10°F, 31°G, 81°C, 21°G, 2	Weight	26.9 oz./765g with battery
Touchpanel Dual mode capacitive touch with finger, gloved finger or stylus input (conductive stylus sold separately); screen protector (sold separately); Corning Gorilla Glass with air gap (standard model or optically bonded (freezer model). Backlight LED backlit display Power Rechargeable LI-Ion: 3.6V, 7000mAh, (Freezer Capacity battery – 5000mAh) Both batteries offer: PowerPrecision+ with improved battery technology for longer cycle times and real-time visibility into battery metrics for better battery management, fast charging (up to 2.4A); hot swap battery backup with temporary session persistence Expansion Slot User accessible MicroSD with 32GB SDHC and up to 2.56GB SDXC Network Connections USB 2.0 High Speed (Host and Client), WLAN and WPAN (Bluetooth) Notification Audible tone; Multi-color LED bar (between keyboard and display), haptic feedback Keypad Backlit, Field replaceable keypads; 58 Key Alpha- Numeric, 53 Key Alpha-Numeric STD, 53 Key Terminal Emulation (5250 and VT), 43 Key, 34 Key Numeric/Function, 29 Key Numeric/Calculation Voice and Audio Speaker, Microphone, PTT Voice (Internal Speaker and Bluetooth Wireless Headset Support). Performance Characteristics CPU Operating Temp. Standard: -4"F to 122"F/-20"C to +50"C, Freezer: -22"F to 122"F/-30"C to +50"C Standard: -4"F to 158"F/-40"C to 70"C Humidity Standard: -4"F to 152"F/-30"C to +50"C Freezer: 5% to 95%, condensi	Display	4.3 in. WVGA (800 x 480), color display
finger or stylus input (conductive stylus sold separately); screen protector (sold separately); Corning Gorilla Glass with air gap (standard model or optically bonded (freezer model).BacklightLED backlit displayPowerRechargeable Li-Ion: 3.6V, 7000mAh, (Freezer Capacity battery — 5000mAh) Both batteries offer: PowerPrecision+ with improved battery technology for longer cycle times and real-time visibility into battery metrics for better battery management, fast charging (up to 2.4A); hot swap battery backup with temporary session persistenceExpansion SlotUser accessible MicroSD with 32GB SDHC and up to 256GB SDXCNetwork ConnectionsUSB 2.0 High Speed (Host and Client), WLAN and WPAN (Bluetooth)NotificationAudible tone; Multi-color LED bar (between keyboard and display), haptic feedbackKeypadBacklit, Field replaceable keypads; 58 Key Alpha- Numeric, 53 Key Alpha-Numeric STD, 53 Key Terminal Emulation (5250 and VT), 43 Key, 34 Key Numeric/Function, 29 Key Numeric/CalculationVoice and AudioSpeaker, Microphone, PTT Voice (Internal Speaker and Bluetooth Wireless Headset Support).Performance Chara-cteristicsCPUQualcomm Snapdragon** 660 octa-core, 2.2 GHzOperating Temp.Standard: -4*F to 122*F/-20*C to +50*C, Freezer: -22*F to 152*F/-20*C to +50*C	Imager Window	Corning Gorilla Glass
PowerRechargeable Li-Ion: 3.6V, 7000mAh, (Freezer Capacity battery — 5000mAh) Both batteries offer: PowerPrecision+ with improved battery technology for longer cycle times and real-time visibility into battery metrics for better battery management, fast charging (up to 2.4A); hot swap battery backup with temporary session persistenceExpansion SlotUser accessible MicroSD with 32GB SDHC and up to 256GB SDXCNetwork ConnectionsUSB 2.0 High Speed (Host and Client), WLAN and WPAN (Bluetooth)NotificationAudible tone; Multi-color LED bar (between keyboard and display), haptic feedbackKeypadBacklit, Field replaceable keypads; 58 Key Alpha- Numeric, 53 Key Alpha-Numeric STD, 53 Key Terminal Emulation (5250 and VT), 43 Key, 34 Key Numeric/Function, 29 Key Numeric/CalculationVoice and AudioSpeaker, Microphone, PTT Voice (Internal Speaker and Bluetooth Wireless Headset Support).Performance CharacteristicsCPU Qualcomm Snapdragon** 660 octa-core, 2.2 GHzOperating SystemAndroid 11; upgradeable to Android 14Memory4 GB RAM/32 GB Flash pSLCUser EnvironmentStandard: -4°F to 122°F/-20°C to +50°C, Freezer: -22°F to 122°F/-30°C to +50°CStandard: 5% to 95%, non-condensing; Freezer: 5% to 95%, non-condensing; Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heateDrop SpecificationStandard: 10 ft. (3.1m) drops at room temperature per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G.Tumble Specification6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification.SealingIP67 and IP65 per applicable IEC sealing </td <td>Touchpanel</td> <td>finger or stylus input (conductive stylus sold separately); screen protector (sold separately); Corning Gorilla Glass with air gap (standard model)</td>	Touchpanel	finger or stylus input (conductive stylus sold separately); screen protector (sold separately); Corning Gorilla Glass with air gap (standard model)
(Freezer Capacity battery — 5000mAh) Both batteries offer: PowerPrecision+ with improved battery technology for longer cycle times and real-time visibility into battery metrics for better battery management, fast charging (up to 2.4A); hot swap battery backup with temporary session persistenceExpansion SlotUser accessible MicroSD with 32GB SDHC and up 	Backlight	LED backlit display
to 256GB SDXCNetwork ConnectionsUSB 2.0 High Speed (Host and Client), WLAN and WPAN (Bluetooth)NotificationAudible tone; Multi-color LED bar (between keyboard and display), haptic feedbackKeypadBacklit, Field replaceable keypads; 58 Key Alpha- Numeric, 53 Key Alpha-Numeric STD, 53 Key Terminal Emulation (5250 and VT), 43 Key, 34 Key Numeric/Function, 29 Key Numeric/CalculationVoice and AudioSpeaker, Microphone, PTT Voice (Internal Speaker and Bluetooth Wireless Headset Support).Performance CharacteristicsCPUOperating SystemAndroid 11; upgradeable to Android 14Memory4 GB RAM/32 GB Flash pSLCUser Environment-40°F to 152°F/-20°C to +50°C, Freezer: -22°F to 122°F/-30°C to +50°CStorage Temp40°F to 158°F/-40°C to 70°CHumidityStandard: 5% to 95%, non-condensing; Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heateDrop SpecificationStandard: 10 ft. (3.1m) drops at room temperature per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G.Tumble Specification6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification.SealingIP67 and IP65 per applicable IEC sealing	Power	(Freezer Capacity battery — 5000mAh) Both batteries offer: PowerPrecision+ with improved battery technology for longer cycle times and real-time visibility into battery metrics for better battery management, fast charging (up to 2.4A); hot swap battery backup with temporary
WPAN (Bluetooth)NotificationAudible tone; Multi-color LED bar (between keyboard and display), haptic feedbackKeypadBacklit, Field replaceable keypads; 58 Key Alpha- Numeric, 53 Key Alpha-Numeric STD, 53 Key Terminal Emulation (5250 and VT), 43 Key, 34 Key Numeric/Function, 29 Key Numeric/CalculationVoice and AudioSpeaker, Microphone, PTT Voice (Internal Speaker and Bluetooth Wireless Headset Support).Performance CharacteristicsCPUOperating SystemAndroid 11; upgradeable to Android 14Memory4 GB RAM/32 GB Flash pSLCUser EnvironmentStandard: -4°F to 122°F/-20°C to +50°C, Freezer: -22°F to 122°F/-30°C to +50°CStorage Temp40°F to 158°F/-40°C to 70°CHumidityStandard: 5% to 95%, non-condensing; Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heateDrop SpecificationStandard: 10 ft. (3.1m) drops at room temperature per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G.Tumble Specification6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification.SealingIP67 and IP65 per applicable IEC sealing	Expansion Slot	
keyboard and display), haptic feedbackKeypadBacklit, Field replaceable keypads; 58 Key Alpha- Numeric, 53 Key Alpha-Numeric STD, 53 Key Terminal Emulation (5250 and VT), 43 Key, 34 Key Numeric/Function, 29 Key Numeric/CalculationVoice and AudioSpeaker, Microphone, PTT Voice (Internal Speaker and Bluetooth Wireless Headset Support).Performance CharacteristicsCPUQualcomm Snapdragon** 660 octa-core, 2.2 GHzOperating SystemAndroid 11; upgradeable to Android 14Memory4 GB RAM/32 GB Flash pSLCUser EnvironmentOperating Temp.Standard: -4°F to 122°F/-20°C to +50°C, Freezer: -22°F to 122°F/-30°C to +50°CStorage Temp40°F to 158°F/-40°C to 70°CHumidityStandard: 5% to 95%, non-condensing; Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heateDrop SpecificationStandard: 10 ft. (3.1m) drops at room temperature per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G.Tumble Specification6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification.SealingIP67 and IP65 per applicable IEC sealing	Network Connections	
Numeric, 53 Key Alpha-Numeric STD, 53 Key Terminal Emulation (5250 and VT), 43 Key, 34 Key Numeric/Function, 29 Key Numeric/CalculationVoice and AudioSpeaker, Microphone, PTT Voice (Internal Speaker and Bluetooth Wireless Headset Support).Performance CharacteristicsCPUQualcomm Snapdragon** 660 octa-core, 2.2 GHzOperating SystemAndroid 11; upgradeable to Android 14Memory4 GB RAM/32 GB Flash pSLCUser EnvironmentStandard: -4°F to 122°F/-20°C to +50°C, Freezer: -22°F to 122°F/-30°C to +50°CStorage Temp40°F to 158°F/-40°C to 70°CHumidityStandard: 5% to 95%, non-condensing; Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heateDrop SpecificationStandard: 10 ft. (3.1m) drops at room temperature per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G.Tumble Specification6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification.SealingIP67 and IP65 per applicable IEC sealing	Notification	
and Bluetooth Wireless Headset Support). Performance Characteristics CPU Qualcomm Snapdragon" 660 octa-core, 2.2 GHz Operating System Android 11; upgradeable to Android 14 Memory 4 GB RAM/32 GB Flash pSLC User Environment Standard: -4°F to 122°F/-20°C to +50°C, Freezer: -22°F to 122°F/-30°C to +50°C Storage Temp. -40°F to 158°F/-40°C to 70°C Humidity Standard: 5% to 95%, non-condensing; Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heate Drop Specification Standard: 10 ft. (3.1m) drops at room temperature per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G. Tumble Specification 6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification. Sealing IP67 and IP65 per applicable IEC sealing	Keypad	Numeric, 53 Key Alpha-Numeric STD, 53 Key Terminal Emulation (5250 and VT), 43 Key, 34 Key
CPU Qualcomm Snapdragon" 660 octa-core, 2.2 GHz Operating System Android 11; upgradeable to Android 14 Memory 4 GB RAM/32 GB Flash pSLC User Environment Standard: -4°F to 122°F/-20°C to +50°C, Freezer: -22°F to 122°F/-30°C to +50°C Storage Temp. -40°F to 158°F/-40°C to 70°C Humidity Standard: 5% to 95%, non-condensing; Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heate Drop Specification Standard: 10 ft. (3.1m) drops at room temperature per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G. Tumble Specification 6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification. Sealing IP67 and IP65 per applicable IEC sealing	Voice and Audio	Speaker, Microphone, PTT Voice (Internal Speaker and Bluetooth Wireless Headset Support).
Operating System Android 11; upgradeable to Android 14 Memory 4 GB RAM/32 GB Flash pSLC User Environment Standard: -4°F to 122°F/-20°C to +50°C, Freezer: -22°F to 122°F/-30°C to +50°C Storage Temp. -40°F to 158°F/-40°C to 70°C Humidity Standard: 5% to 95%, non-condensing; Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heate Drop Specification Standard: 10 ft. (3.1m) drops at room temperature per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G Tumble Specification 6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification. Sealing IP67 and IP65 per applicable IEC sealing	Performance Chara	cteristics
Memory 4 GB RAM/32 GB Flash pSLC User Environment User Environment Operating Temp. Standard: -4°F to 122°F/-20°C to +50°C, Freezer: -22°F to 122°F/-30°C to +50°C Storage Temp. -40°F to 158°F/-40°C to 70°C Humidity Standard: 5% to 95%, non-condensing; Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heate Drop Specification Standard: 10 ft. (3.1m) drops at room temperature per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G. Tumble Specification 6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification. Sealing IP67 and IP65 per applicable IEC sealing	CPU	Qualcomm Snapdragon™ 660 octa-core, 2.2 GHz
User Environment Operating Temp. Standard: -4°F to 122°F/-20°C to +50°C, Freezer: -22°F to 122°F/-30°C to +50°C Storage Temp. -40°F to 158°F/-40°C to 70°C Humidity Standard: 5% to 95%, non-condensing; Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heate Drop Specification Standard: 10 ft. (3.1m) drops at room temperature per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G Tumble Specification 6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification. Sealing IP67 and IP65 per applicable IEC sealing	Operating System	Android 11; upgradeable to Android 14
Operating Temp. Standard: -4°F to 122°F/-20°C to +50°C, Freezer: -22°F to 122°F/-30°C to +50°C Storage Temp. -40°F to 158°F/-40°C to 70°C Humidity Standard: 5% to 95%, non-condensing; Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heate Drop Specification Standard: 10 ft. (3.1m) drops at room temperature per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G Freezer: 7 ft. (2.1m) drops to concrete across temperature per MIL-STD-810G. Tumble Specification 6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification. Sealing IP67 and IP65 per applicable IEC sealing	Memory	4 GB RAM/32 GB Flash pSLC
Freezer: -22°F to 122°F/-30°C to +50°C Storage Temp. -40°F to 158°F/-40°C to 70°C Humidity Standard: 5% to 95%, non-condensing; Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heate Drop Specification Standard: 10 ft. (3.1m) drops at room temperature per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G Freezer: 7 ft. (2.1m) drops to concrete across temperature per MIL-STD-810G. Tumble Specification 6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification. Sealing IP67 and IP65 per applicable IEC sealing	User Environment	1
Humidity Standard: 5% to 95%, non-condensing; Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heate Drop Specification Standard: 10 ft. (3.1m) drops at room temperature per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G. Tumble Specification 6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification. Sealing IP67 and IP65 per applicable IEC sealing	Operating Temp.	
Freezer: 5% to 95%, condensing (Condensation resistant model with integrated exit window heate Drop Specification Standard: 10 ft. (3.1m) drops at room temperature per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G Freezer: 7 ft. (2.1m) drops to concrete across temperature per MIL-STD-810G. Tumble Specification 6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification. Sealing IP67 and IP65 per applicable IEC sealing	Storage Temp.	-40°F to 158°F/-40°C to 70°C
per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G Freezer: 7 ft. (2.1m) drops to concrete across temperature per MIL-STD-810G. Tumble Specification 6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification. Sealing IP67 and IP65 per applicable IEC sealing	Humidity	
tumble specification. Sealing IP67 and IP65 per applicable IEC sealing	Drop Specification	per MIL-STD-810G, 8 ft. (2.4m) drops to concrete across temperature per MIL-STD-810G Freezer: 7 ft. (2.1m) drops to concrete across
	Tumble Specification	6,000 3.3 ft. (1m) tumbles; meets and exceeds IEC tumble specification.
	Sealing	

Vibration	4 g's PK Sine (5 Hz to 2 kHz); 0.04 g 2/Hz Random (20 Hz to 2 kHz); 60 minute duration per axis, 3 axis	
Thermal Shock	-40°F to 158°F (-40° C to 70°C) rapid transition	
Electrostatic Discharge (ESD)	±15kVdc air discharge; ±8kVdc direct discharge; ±8kVdc indirect discharge	
Interactive Sensor Technology (IST)		
Ambient Light Sensor	Automatically adjusts display and keypad backlight brightness	
Motion Sensor	3-axis Accelerometer with MEMS Gyro	
Data Capture		
Scanning	SE965: 1D standard range laser scanner SE4750: 1D/2D standard range omnidirectional imager SE4770: 1D/2D standard range omnidirectional imager SE4750 DPM: Direct Part Mark (DPM) imager SE4850: 1D/2D extended range imager	
Camera	Front: 5MP fixed focus, 2.0 aperture Rear: 13MP autofocus, 2.2 aperture, flash LED generates balanced white light, support torch mode, supports rear camera barcode scanning	
NFC	Tap to Pair, ISO 14443 Type A and B, Felica and ISO 15693 cards, P2P mode and Card Emulation via Host (HCE) support	
Wireless LAN		
Radio	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/w; Wi-Fi certified; IPv4, IPv6, 2x2 MU-MIMO	
Data Rates	5GHz: 802.11a/n/ac — up to 866.7 Mbps 2.4GHz: 802.11b/g/n — up to 300 Mbps	
Operating Channels	Channel 1-13 (2412-2472 MHz); Chan 36-165 (5180- 5825 MHz) Channel Bandwidth: 20, 40, 80 MHz Actual operating channels/ frequencies and bandwidths depend on regulatory rules and certification agency	
Security and Encryption	WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP and AES); WPA/WPA2 Enterprise (TKIP and AES) - EAP-TTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC and LEAP, EAP-PWD FIPS 140-2 Level 1: Data in Motion and Data at Rest	
Multimedia	Wi-Fi Multimedia (WMM and WMM-PS; Including TSPEC)	
Certifications	WFA (802.11n, WMM-PS, 802.11ac, PMF, WMM-AC, Voice Enterprise, WiFi Direct and WPS 2.0)	
Fast Roam	PMKID caching; Cisco CCKM; 802.11r; OKC	
Wireless PAN		
Bluetooth	Class 2, Bluetooth V5.0 with BR/EDR and Bluetooth Low Energy (BLE) Support	

Markets and Applications

Logistics

- Receiving/put-awayInventory
- managementReturns processing
- Cross dock operations
- EDI transactions/ picking

Manufacturing

- Inventory management
 - Supply-line
 - replenishment

 Safety testing
 - Quality control audits
- Parts tracking/track and trace

Retail

- Retail/inventory
 management
- Price audits/changes
- Back of store order fulfillment
- Store receiving

Cold Chain

- Receiving/putawayEDI transactions/
 - picking
 - Inventory management
 - Supply-line replenishment
 - Safety testing
 - Quality control audits

Government

- Receiving/put-away
- Inventory management
- Returns processing
- Cross dock operations
- EDI transactions/ picking

Device Approvals and Compliance		
TAA (Optional on select configurations)	Trade Agreement Act optional on select configurations Compliant, FIPS 140-2 (DIM and DAR) support; FIPS 140-2 Level 1: Data in Motion and Data at Rest	
Non-Incendive (NI) ¹ (Optional on select configurations)	Suitable for use in Class I, II, III Div 2 Safety: cULus Listing — ISA/ANSA 12.12.01 Gases: Class I — Groups A, B, C, D Dusts: Class II — Groups F, G Fibers and Flyings: Class III $-20^{\circ}C \le Ta \ge +50^{\circ}C T6$	

Communication and Messaging

Workforce Connect PTT Express (included) provides instant push-to-talk small group communications across Wi-Fi networks. Workforce Connect PTT Pro (supported) provides a scalable network agnostic push-to-talk solution which also includes messaging, location services and two-way radio integration. Workforce Connect Voice client (supported) enables the MC9300 to function as a full featured mobile telephone with multi-line capability across Wi-Fi networks.

Environmental Compliance

Environment

• RoHS Directive 2011/65/EU; Amendment 2015/863

• REACH SVHC 1907/2006

A complete list of product and materials compliance, please visit: www.zebra.com/environment

Warranty

Subject to the terms of Zebra's hardware warranty statement, the MC9300 is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement, please visit: http://www.zebra.com/warranty

Recommended Services

Zebra OneCare® Essential and Select support services Zebra Visibility Services – VisibilityIQ[™] Foresight or Asset Visibility Service

Platforming

Mobility DNA, Enterprise MDK, Standard Android SDK and SOTI for Android, Analytics Agent

Footnotes

1. Available in North America.

For details related to Common Criteria support, please visit: www.zebra.com/commoncriteria

Mobility DNA

Mobility DNA solutions help you get more value out of our mobile computers by adding functionality as well as simplifying deployment and management of our mobile devices. For more information on these Zebra-only features, please visit www.zebra.com/mobilitydna

Mobility DNA is available on Android only. Features may vary by model and a Support Contract may be required. To learn what solutions are supported, please visit: https://developer.zebra.com/mobilitydna





03 9582 7000

sales@umd.com.au https://www.umd.com.au Unit 1,200 Wellington Road, Clayton, Victoria, 3168, Australia



ZEBRA and the stylized Zebra head are trademarks of Zebra Technologies Corp., registered in many jurisdictions worldwide. Android is a trademark of Google LLC. All other trademarks are the property of their respective owners. ©2022 Zebra Technologies Corp. and/or its affiliates. 02/23/2022