

# The Smoothest Ride in Travel Mobility



**GO GO**®  
**LX** WITH CTS SUSPENSION




Comfort-Trac Suspension

The Go-Go® LX with Comfort-Trac Suspension (CTS) offers a whole new level of comfort and performance. This industry-first CTS technology incorporates advanced suspension for improved absorption over various terrains. The Go-Go LX with CTS offers a 136 kg (300 lb.) weight capacity, a per charge range up to 16.9 km (10.5 miles) and a maximum speed of 6.4 km/h (4 mph). Standard features include feather-touch disassembly, a wraparound delta tiller (with charger port), non-scuffing tyres, LED headlight and front basket.

# Go-Go LX (CTS Suspension)

## Specifications

Weight Capacity	136 kgs (300 lbs.)
Maximum Speed <sup>1</sup>	Up to 6.4 km/h (4 mph)
Ground Clearance <sup>2</sup>	3.8 cm (1.5") at motor
Turning Radius <sup>2</sup>	116.2 cm (44.75")
Overall Length <sup>2</sup>	104.1 cm (41")
Overall Width <sup>2</sup>	52.1 cm (20.5")
Front Tyres	5 x 17.8 cm (2" x 7") solid
Rear Tyres	6.35 x 20.3 cm (2.5" x 9") solid
Range Per Charge <sup>1,4</sup>	Up to 16.9 km (10.5 miles)
Total Weight Without Batteries <sup>5</sup>	39.6 kg (87.4 lbs.)
Heaviest Piece When Disassembled	16.6 kg (36.6 lbs.) (front section)
Standard Seating	<b>Type:</b> Foldable, vinyl covered, molded plastic <b>Weight:</b> 10 kg (23 lbs.) <b>Material:</b> Black vinyl <b>Dimensions:</b> Width: 43.1 cm (17") Depth: 43.1 cm (17")
Motor Output	24-volt DC motor, sealed mini-transaxle
Brakes	Regenerative and electromechanical
Battery Requirements <sup>3,5</sup>	(2) 12V deep-cycle Size: (2) 17 AH <b>Weight:</b> 13.8 kg (30.4 lbs.) per battery pack
Battery Charger	Off-board, 2 amp
Delta Tiller	Yes
Colour Options	



Quality  
Endorsed  
Company  
SAI Global

**PRIDE® MOBILITY SCOOTERS**  
LIVE YOUR BEST®

20-24 Apollo Drive Hallam, Victoria 3803  
ACN 088 609 661 ABN 66 088 609 661

(Tel) 03 8770 9600 • [www.pridemobility.com.au](http://www.pridemobility.com.au)

## Features

- Charger port built into the tiller
- Convenient dual voltage charger that can charge battery pack on-board or off-board
- Comfort-Trac front and rear suspension
- Feather-touch disassembly
- Front frame-mounted seat post offers maximum stability
- Long-lasting, high-intensity, front LED headlight
- Microprocessor-based controller
- Pride's exclusive black, non-scuffing tyres

## Accessories

- Pride rear bag/walking stick holder
- Walker holder\*
- Oxygen tank holder\*
- Mobile phone holder
- Cup holder
- Rear view mirror
- Saddle bag
- Flag

*\*Must have Pride rear bag to attach*

<sup>1</sup> Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).

<sup>2</sup> Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

<sup>3</sup> AGM or gel cell type required.

<sup>4</sup> Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

<sup>5</sup> Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

**PRIDE®**  
MOBILITY  
LIVE YOUR BEST®