

EcoLift™ SERIES

NON-POWERED VERTICAL LIFTS

JLG
reachingout®

Performance

	EcoLift 50	EcoLift 70
Working Height	3.50 m	4.20 m
Platform Height	1.50 m	2.20 m
Stowed Height	1.55 m	1.94 m
Stowed Width	0.7 m	0.7 m
Stowed Length	0.985 m	1.28 m
Platform Size	72 x 60 cm	85 x 64.4 cm
Rated Capacity	150 kg	150 kg
Weight	180 kg	305 kg

Standard Features

- Unlimited Lift Cycles
- Rust-Free Aluminium Platform w/Diamond Tread
- Full-Height Self-Closing, Self-Latching Saloon Gate
- Tool Tray
- Frame-Mounted Bubble Level
- Protective Wall Bumpers
- Integrated Fork Pockets
- Auto-Braked When Entering Platform
- "Auto-lok" Brake on Elevation
- Mechanically Detented Handle

Applications

- Commercial and Residential Painting
- Facility Maintenance
- Displays and Decorating
- HVAC Maintenance
- Renovations and Remodeling
- Plant Maintenance
- Equipment Maintenance Installers — Cable, Security, Professional



EcoLifts are an ecofriendly alternative to your powered access needs. They are hydraulic oil and battery free. And with no need to charge, EcoLifts have no energy consumption.

The JLG "1 & 5" Warranty

JLG Industries, Inc., backs its products with its exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds AS/NZS 1418.10 2011 as originally manufactured for intended applications.

JLG

JLG Industries (Australia)

358 Park Road
Regents Park, NSW 2143
Telephone 02 8718 6300
Fax 02 8718 6377
www.jlg.com.au

An Oshkosh Corporation Company