



Urban Solar Street Light



EarthLight 

Industrial & Commercial Lighting
earthlight.com.au

Urban

Solar Street Light

The Earthtrack Urban Solar Solar Street Light, designed for industrial-grade use, combines functionality and aesthetic appeal. It offers reliable, cost-effective reliable, and eco-friendly lighting. Key features include easy installation, low maintenance, and consistent illumination. The Urban is a great choice for reliable and emission-free solar Solar Street Lighting for pathways and streets.

- ✓ Black Start Functionality
- ✓ Adjustable Solar Panel Tilt Angle (15°-40°)
- ✓ 1 Hour Solar Charge = 3 Hours Light Run Time
- ✓ 4 Days Battery Autonomy
- ✓ Fully Programmable Control System
- ✓ Small Footprint Compact Column Design
- ✓ Vandal Resistant Battery Enclosure With Cooling Vents

**Optional Event
Banner Mount**



earthlight.com.au
1300 410 485
sales@earthlight.com.au

Urban

Specifications

CODE	ETG-01UB036	ETG-01UB037	ETG-01UB038
MANUFACTURER SPEC			
Total Height	6.1m		
Enclosure Mounting	50W x 1	100W x 1	50W x 2
Outreach Arm	Single - 1.8m outreach	Single - 1.8m outreach	Twin - 1.8m outreach
Pole Finish	Hot dip galvanised (powder coat optional)		
Electrical Enclosure	Vandal-resistant, water/dust resistant enclosure with cooling fan		
Base Plate Mounting	4 × M24 at 350mm PCD		
Dimensions			
Total Weight (Kg)	321		336
Luminaire Height	6.1m		
LUMINAIRE			
Lumen Output	7,000	16,000	14,000
Luminaire Wattage	50W x1	100W x1	50W x2
ELECTRICAL			
Solar Panel (W)	400		
Solar Panel Tilt	15-40°		
MPPT Controller	20A MPPT controller		
Battery Capacity	3.53kWh	7.06kWh	
Battery Type	ELION LiFePO4 - Lithium Iron Phosphate		
Normal Voltage	25.6V		
Charge Current	50A		
Battery Autonomy	4 Days		



earthlight.com.au
1300 410 485
sales@earthlight.com.au

Urban

Dimensions



