

QUATTRO® Sentinel mattress replacement system specification



...reducing avoidable harms



SPECIFICALLY DESIGNED
FOR THE CARE OF BARIATRIC
PATIENTS

- **CHOICE OF THERAPY MODE:**
ACTIVE MODE to provide 1-in-4 cell cycle active therapy
or
CONTINUOUS LOW PRESSURE THERAPY MODE provides reactive therapy
- **EXTRA DURABLE** air cells constructed from reinforced PU coated nylon for extra strength and durability
- **ODS™** (ortho-differential support) cell design provides optimal comfort and support for varying body shapes and sizes
- **AUTOsupport™** automatically adjusts pressure within each of the cells throughout the cycle so that support, posture and therapy are constantly maintained at optimum levels
- **MAXIMUM INFLATION** inflates the mattress to maximum static pressure for 15 minutes before returning to previous therapy mode
- **COMFORT CONTROL** adjustable in either therapy mode to help patient compliance
- **REMOVABLE SIDE BOLSTERS** ideal for use with width-retractable beds to allow easy movement of complete bed system with patient in-situ
- **AUDIBLE AND VISUAL ALERTS** indicate current operation status / fault conditions
- **AUTOLOCK** feature prevents inadvertant button operation
- **PHASE FLOW™** pressure control pump operates on demand only, reducing power consumption, noise and extending service life
- **CPR FUNCTION** for simple and effective rapid deflation to enable CPR procedures
- **TRANSPORT FACILITY** allows unpowered support of the patient for up to 12 hours
- **MULTI-STRETCH COVER** is waterproof and moisture-vapour permeable with welded seams and can be removed for laundering
- **LOW AIR-LOSS** feature, where air is released and circulated beneath the mattress cover, helps to reduce humidity and manage the skin 'microclimate' between the patient and the support surface
- **ERGONOMIC DESIGN SOLUTIONS** including anti-kink umbilical, non-tear mattress anchoring straps and cable management, together with integrated power unit carry handle and adjustable hanging brackets
- **MODULAR CONSTRUCTION** enables simple repair/ service on site for minimum downtime
- **370 KG (58 STONE)** patient weight limit

QUATTRO[®] Sentinel

technical data

Power Unit	
Length	335 mm
Height	233 mm
Depth	165 mm
Weight	3.4 kg
Mode of Operation	1-in-4 cell cycle (Active therapy) or Continuous Low Pressure (Reactive therapy)
Alternating Cycle Time	16 mins
Ingress Protection Rating	IP21
Mains Cable	5 metres
Electricity Supply	230V~50Hz
Rated Input	9.4 VA
Fuse Rating	T500mA 250V HRC (ceramic) 5 x 20 mm
Noise Level	33.5 dBa

Mattress	
Length*	2000 mm
Width*	1200 mm (860 mm without bolsters)
Depth	180 mm
Weight	23.4 kg
Inner Construction Materials	Base tray: Woven nylon 940 DTEX PU coated both sides Base layer and side bolsters: CMHR foam Cells: Reinforced PU coated nylon
Cover Material	PU coated stretch nylon
Number of Cells	17
Max. User Weight	370 kg / 58 stone
Min. User Weight	None
Fire Retardancy	BS 7177 BS 7175 Crib 5 test method BS 6807

Please refer to user manual for recommended cleaning products and procedures.

Covers are anti-bacterial/microbial treated (active ingredient: zinc pyrithione)

*UK standard size – approx. max top surface, inflated +/- 15mm

Talley manufacture products to comply with National and International safety standards and are certified to ISO9001, ISO13485 and Directive 93/42/EEC. Every care has been taken to ensure that the information contained in this brochure was correct at the time of going to press. However, Talley reserve the right to modify the specification of any product without prior notice in line with a policy of continual product development. Our standard terms and conditions apply. © Talley Group Limited 2016. All rights reserved.



Talley Group Limited
Premier Way, Abbey Park Industrial Estate
Romsey, Hampshire, SO51 9DQ England
TEL: +44(0)1794 503500
FAX: +44(0)1794 503555
EMAIL: sales@talleygroup.com



www.talleygroup.com



02/2018