

Tenso® LST 450

Battery Powered Strapping
Tool 19mm - 25mm

#61811



High Productivity

Saving you time with auto and manual modes

All In One

Eliminates the requirement for numerous tools and accessories

Environmentally Friendly

Welding process eliminates the need for buckles, reducing landfill

High Quality

Manufactured to the highest quality in Italy with the latest technology

The innovative Tenso LST 450 Battery Powered Strapping Tool is faster and easier to use, providing the operator with higher efficiency and productivity.

Introduced into the market in 2016, the Tenso LST Battery Powered Strapping Tools have quickly become the market leader with the highest quality production and manufacturing technique, ensuring tool longevity, and less down time with minimal repairs and servicing for every user.

The tools feature an automatic welding system offering automatic, semi-automatic, manual and soft options through the enhanced tension system.

The perfectly balanced Tenso LST 450 is comfortable and simple to operate in both horizontal and vertical applications, primarily due to the ergonomic and light weight design.

All tensioning and sealing operations are controlled by electronic push buttons. Also featuring a brushless, wear-free, motor system powered by the highest quality Tenso Li-ion battery, providing up to 600 cycles per battery charge.

Features

- Automatic Welding System: Auto, semi-auto, manual, and soft options
- Ergonomic and Lightweight Design
- Bosch Li-Ion Battery (600 cycles)
- Digital Readout Display
- Fast 30-Minute Recharge
- Hard Protectant Carry Case
- Swift and User-Friendly Operation
- Perfectly Balanced Design: Comfortable in horizontal and vertical use
- Electronic Controls: Tensioning and sealing managed by push buttons
- Brushless 'Wear-Free' Motor: Powered by a lithium-ion battery (Up to 600 cycles)



Specifications

| | |
|----------------------------|-----------------------------------|
| Dimensions (LxWxH) | 340mm x 110mm x 160mm |
| Package Type | Flat Surface (min. length 120mm) |
| Strap Type | PP/PET |
| Strap Width | 19mm - 25mm |
| Strap Thickness | 0.80mm - 1.3mm |
| Max. Tension | 4500n/460kgf |
| Join Type | Friction Weld Seal |
| Weight | 4.0kg (inc. Battery) |
| Battery | Bosch 18v - 4.0Ah Li-Ion |
| Battery Charge Time | 30 minutes |
| Battery Usage Cycle | Up to 600 uses on a single charge |

