

INSTRUMENTATION & CONTROL

Differential Pressure Switch

G75-DP | Baccara Differential Pressure Gauge Switch







Optional Mounting Bracket



- Reads and reacts to pressure differential between two reading points
- Suitable to work with both media air and liquid
- Main applications : filters backwash, pumps control, pressure control


Technical Data

| chanical | Operating temperature : -10°C to 60°C (no freezing) Outdoor UV protection Front panel cover protection "H" proof pressure : 14 bar (203 PSI) "H" pressure must be ≥ "L" pressure. |
|----------------------------|--|
| ctrical | Power supply : 6-24V DC or 12-24V AC RED + BLK power supply GRN / WHT N.0 contact Low power detect Dry contact (N.0) 0.5A at 24V AC Internal memory to retain "set-up data" at power down. |
| unting | 2" (52mm) diameter 2ft (60cm) 4 wires cable Pressure ports 1/8" BSP/NPT (male) High pressure port is marked by the letter "H" on the housing Connect high pressure before low pressure Disconnect low pressure before high pressure |
| tware | See 'Programming key features' table |
| play | The LCD display : DIF : measured differential pressure SET : pressure differential trigger setting ON : displayed when the switch contacts are closed Display resolution : 1 PSI in the range 0 - 99 psi 0.1 bar in the range 0.0 - 7 bar. |
| ndard protection class | • Dust and watertight • IP66 |
| ctrical unting tware | Front panel cover protection "H" proof pressure :14 bar (203 PSI) "H" pressure must be ≥ "L" pressure. Power supply : 6-24V DC or 12-24V AC RED + BLK power supply GRN / WHT N.0 contact Low power detect Dry contact (N.0) 0.5A at 24V AC Internal memory to retain "set-up data" at power down. 2" (52mm) diameter 2" (52mm) diameter 2" (60cm) 4 wires cable Pressure ports 1/8" BSP/NPT (male) High pressure port is marked by the letter "H" on the housing Connect high pressure before low pressure Disconnect low pressure before high pressure See 'Programming key features' table The LCD display : OIF : measured differential pressure SET : pressure differential trigger setting ON : displayed when the switch contacts are closed Display resolution : 1 PSI in the range 0 - 99 psi O.1 bar in the range 0.0 - 7 bar. |

Programming key features

| Manual operation |
|---|
| PSI or bar display |
| Time interval between pressure measurements |
| Contact closed time |
| Time interval between contact closure |
| Zero calibration |
| |

How to Order



Example : G75-DP-1BD

Baccara Differential Pressure Gauge Switch, stand alone, with mounting bracket and latch solenoid driver.



* To order controllers manufactured according to your specific requirements, please contact our technical sales department.