

HIGH LIFT PALLET TRUCK / JACK

1.5TON 540 OR 680MM WIDE

The Scissor lift pallet jack is perfect for conveyor processing which saves the operator/loader from bending over to put products on the pallet, great for OH&S issues, suitable for open pallets (pallets without bottom boards) unless placing the pallet on top of the scissor lift.

Features

- Entry and exit roller prevent physical exertion of the operator and protect load roller and pallet.
- Totally sealed hydraulic pump with a slow lowering hand control valve.
- Full adjustable push rod under forks.
- 3-Position control handle, Grease fittings at key points.
- Skid lifter suitable as a lift table or work bench.
- Stabilizers ensure maximum stability.
- Reduces unnecessary bending.
- Cannot be moved in a raised position for safety.
- Powder coated yellow for high visibility and extra protection from wear and tear.
- Polyurethane wheels: are mainly used for floors that are delicate like marble, floorboards or tiles as the softer wheel distributes the weight more over evenly the floor.



Visit www.mitaco.com.au for more photos and details

Specifications

Model		MPTSL15	MPTS15680
Capacity	(kg)	1500	1500
Min Fork Height	(mm)	85	85
Max Fork Height	(mm)	800	800
Fork Width	(mm)	160	160
Fork Overall Width	(mm)	540	680
Fork Length	(mm)	1150	1150
Overall Size LxWxH	(mm)	1480x540x1210	1480x680x1210
Load Roller (dia x width)	(mm)	75X50	75X50
Steering Wheel (dia x width)	(mm)	180X50	180X50
Net Weight	(kg)	126	126

Mitaco has national sales and distribution capabilities, our sales office and warehouse is located in Brisbane. Large inventory holdings enable fast-track dispatch of stock orders. This combined with an easy to use online ordering system makes the delivery of stocked products simple, fast and reliable.