

SM1P-ISDP: Dual Protection Headset for Communication in Extreme Noise

Dual protection is often a requirement in many critical working areas where exposures may exceed 100 dB(A), Sensear has integrated our SENS® communication capabilities into an Intrinsically Safe Dual Protection headset (ISDP) so users can effectively communicate without removing their hearing protection in these extremely high-noise hazardous conditions. Based on the existing SM1P-IS headset, and incorporating our unique dual protection feature, the SM1P-ISDP fulfills the marketplace need for a high-performance hazardous location headset for extreme noise environments.

See more details at sensear.com/products/headsets/sm1p-isdp



KEY FEATURES

SENS® Technology	Enhances speech while suppressing background noise to a safe level
360° Situational Awareness	Remain aware of surrounding noises and hazards
Double Hearing Protection	Up to 36dB NRR / 38dB SNR / 33dB, Class 5 SLC80
Volume Limiter	Limit 'in-ear' exposure to 82 dB(A)
Radio Communication	Two-Way Radio via Bluetooth® Wireless Technology or PTT Cable
Bluetooth® Communication	Bluetooth® 3.0, 15 m
Short-Range Communication	Up to 8 Programmable FM Channels, up to 45 m
FM Radio	Listen to commercial FM Radio stations
Voice Transmission	Noise-canceling Boom Mic, VOX-capable
Power	Upgraded 24-hour battery life for use in multiple shifts
Headsets Styles	Headband, Behind-the-Neck, Helmet Mount
IP Ratings	IP54 (headset), IP68 (boom mic)
Intrinsic Safety	TIA-4950-A, CSA C22.2 No. 157.92, & UL 913 5th Ed

 360° SITUATIONAL AWARENESS	 ELECTRONIC VOLUME LIMITER	 DOUBLE HEARING PROTECTION	 ENHANCE SPEECH SUPPRESS NOISE
 FACE-TO-FACE COMMUNICATION	 BLUETOOTH® COMMUNICATION	 TWO-WAY RADIO COMMUNICATION	 SHORT-RANGE COMMUNICATION
 INTRINSIC SAFETY	 Sensear <small>SAFETY THAT SPEAKS VOLUMES</small>  SENS <small>TECHNOLOGY by Sensear</small>		








Sensear in Action



Headset Styles

 <p>SM1PBISDP02 HEADBAND 36dB NRR / 37dB SNR / 32dB, Class 5 SLC80</p>	 <p>SM1PEISDP02 BEHIND-THE-NECK 36dB NRR / 38dB SNR / 33dB, Class 5 SLC80</p>	 <p>SM1PHISDP02 HELMET MOUNT 36dB NRR / 38dB SNR / 30dB, Class 5 SLC80</p>
--	---	--

Technical Specifications

GENERAL	MOUNTING TYPE	PART NUMBER	WEIGHT	IP RATING	OPERATING TEMPERATURE		
	Headband (HB)	SM1PBISDP02	495 g (17.46 oz.)	IP54	-20°C to +60°C (-4°F to 140°F)		
	Behind-the-Neck (BTN)	SM1PEISDP02	428 g (15.09 oz.)	IP54	-20°C to +60°C (-4°F to 140°F)		
	Helmet Mount (HM)	SM1PHISDP02	480 g (16.93 oz.)	IP54	-20°C to +60°C (-4°F to 140°F)		

HEARING PROTECTION	REGION	STANDARD	RESULT	HB	BTN	HM
Volume Limiter - 82 dB(A) [programmable] Only applicable when headset is powered on	Australia / NZ	AS/NZS 1270	SLC80	32dB, Class 5	33dB, Class 5	30dB, Class 5
	USA / Canada	ANSI S3.19	NRR	36dB	36dB	36dB
	Europe	EN352-1/EN352-3	SNR	38dB	38dB	38dB

POWER	BATTERY TYPE	BATTERY CAPACITY	OPERATING TIME	CHARGE TIME	CHARGING TEMPERATURE
	Rechargeable Lithium-ion	2250 mAh	24 hours (wired) / 18 hours (Bluetooth®/SR)	4 hours	0°C to +40°C (32°F to 104°F)

COMMUNICATION	FACE-TO-FACE SENS® MODE	VOICE TRANSMISSION	TWO-WAY RADIO	BLUETOOTH®
	SENS® voice pickup limit of 95 dB(A)	Noise-canceling boom microphone. VOX capable when connected to VOX enabled two-way radio (Must be verified and tested for compatibility with the two-way radio.)	6-pin Hirose connector. Two-way radio audio through headset without headset battery. Audio revert to radio when headset Hirose disconnected. (Dependent on radio type and compatible SRCK radio cable.)	Bluetooth® 3.0: HFP (8 KHz and 16 KHz), HSP, A2DP. Up to 15 meters (49 ft).

SHORT-RANGE COMMUNICATION	REGION	EIRP (UW)	STANDARDS	FM FREQ. RANGE (MHZ)
Half-duplex communications. Up to 8 programmable FM channels. Up to 45 meters (150 ft). FM Radio enable/disable option: Allows user to listen to commercial FM radio stations.	1	8.02	AS/NZS 4268	88.1 – 107.9
	2	0.048	EN301357-1	88.1 – 107.9
	3	0.012	FCC-15.239 & IC	88.1 – 97.0

IS certification: TIA-4950-A, CSA C22.2 No. 157.92, & UL 913 5th Edition with a hazardous location rating of Class I, II, III, Division 1 & 2, Groups A - G, T4 -20°C to +40°C, T3C -20°C to +50°C

Sensear Inc.
1141 E Main St, Ste. 201
East Dundee, IL 60118
United States

Sensear Pty Ltd
4 Hehir Street
Belmont, WA 6104
Australia

