

Nano POS



VESA Mount Capable*

* VESA pole & bracket are not included.



Aluminium Die-cast Casing



Removable HDD/SSD

SE/MOR



SPECIFICATIONS	Nano POS 6200	Nano POS 6320	Nano POS 6520
PROCESSOR	Intel Celeron J1900 2.0 GHz	Intel Core i3-4330TE 2.4 GHz	Intel Core i5-4570TE 2.7 GHz
SYSTEM MEMORY	4 GB DDR3L RAM (up to 8 GB)	4 GB DDR3 RAM (up to 8 GB)	
STORAGE	2.5" removable SATA HDD/SSD		

DISPLAY

SIZE / RESOLUTION	15" TFT LCD / 1024 x 768 pixels
BRIGHTNESS	350 cd/m ²
TOUCH SCREEN PANEL	Projected capacitive touch (10-point)

I/O INTERFACE

USB PORT	3 x USB 2.0, 1 x USB 3.0	2 x USB 2.0, 2 x USB 3.0
SERIAL PORT	3 x DB9, 1 x RJ50	2 x DB9, 1 x RJ50
VIDEO PORT	1 x VGA	1 x VGA
AUDIO PORT	1 x mic-in, 1 x line-out	1 x mic-in, 1 x line-out
CASH DRAWER PORT	1 x RJ12 (12 V)	1 x RJ12 (12 V)
ETHERNET PORT	1 x RJ45 10/100/1000 Mbps	1 x RJ45 10/100/1000 Mbps

OPERATING SYSTEM

WINDOWS	POSReady 7 / 7 Pro / 10 IoT / 10 Pro
---------	--------------------------------------

ENVIRONMENT & MECHANICAL SPECIFICATIONS

DIMENSIONS & WEIGHT	368 (W) x 329 (H) x 268 (D) mm 7.8 kg	
CHASSIS MATERIAL	Heat-dissipating solid aluminium die-cast casing	
VESA PATTERN	100 x 100 mm	
TEMPERATURE	Operating: 0°C to 35°C Storage: -20°C to 60°C	
HUMIDITY	Operating: 20% to 80% (non-condensing)	
POWER CONSUMPTION	19 V / 4.74 A, external power adaptor, 100-240 V, 50/60 Hz	19 V / 7.89 A, external power adaptor, 100-240 V, 50/60 Hz

MODEL OPTIONS

INTEGRATED CARD READERS	3-track MSR / Fingerprint reader / RFID reader (13.56 MHz, 125 kHz)
CUSTOMER DISPLAY	10"/15" TFT LCD display (1024 x 768 pixels) or 2-line VFD
SCANNER	1D / 2D scanner

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street
Coopers Plains
QLD 4108, Australia

www.senortech.com.au

P: +61 7 3275 5888
F: +61 7 3275 5800
sales@senortech.com.au

SENIOR
TOUCH SCREEN SOLUTIONS

Quality. Safety. Versatility.