



## FED-X S/S Two Door Upright Fridge - XURC600S1V

### Quick Overview

- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy duty evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- 1/2 split door system can lower yearly running cost by up to 30%

### Description

#### FED-X Stainless Steel Two Door Upright Fridge - XURC600S1V

- Net Capacity: 600L
- Cooling System: Fan forced cooling
- Temperature range: -2~+8°C
- Compressor: Cubigel
- Controller: Dixell
- Ambient Temperature: 43°C
- RH: 40%
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy duty evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- 1/2 split door system can lower yearly running cost by up to 30%

**2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration**



## Your Shipping Specifications

---

<b>Net Weight (Kg)</b>	110
<b>Width (mm)</b>	680
<b>Depth (mm)</b>	810
<b>Height (mm)</b>	2000
<b>Packing Width (mm)</b>	765
<b>Packing Depth (mm)</b>	855
<b>Packing Height (mm)</b>	2070
<b>Power</b>	240V; 50V; 10A; 210W