



IPSO®

COMMERCIAL DRYER (REAR CONTROL) FOR OPL LAUNDRY APPLICATIONS

CD9E - CD9G



FEATURES

- **Superior airflow**
 - Advanced blower system produces airflow of 220 cu. Ft. per minute
 - Fast-drying results with advanced airflow pattern
 - Minimum dry time
- **Large capacity**
Large 7.0 ct ft. cylinder
- **Door opening of 2.06 sq. ft. for fast and easy loading and unloading**
- **Time savings**
Large, easy-clean lint filter is located upfront

CONTROL

- **E-Mech control**
The E-Mech Control on IPSO dryers assures reliable performance and helps optimize efficiency. The control panel offers convenient features - including an energy-saving cycle with an electronic timer.
- **Push-to-Start button**
Features simple, push-to-start activation with an 'In Use' LED light



visit laundrysolutions.com.au

OPL CD9 Rear Control Dryer specifications

| | CD9E | CD9G |
|------------------------------|---------------------|---------------------|
| Control Option | E-mech Control | E-mech Control |
| Control Location | Rear | Rear |
| Drum | | |
| Capacity (kg) | 10 | 10 |
| Volume (L) | 198 | 198 |
| Motor | | |
| Power (KW) | 0.25 | 0.25 |
| Cabinet | | |
| Cylinder Finish | Galvanized | Galvanized |
| Colours | White | White |
| Door Type | Solid | Solid |
| Heating | | |
| Heat Source | Electric | Gas |
| Heating Power | 4 kW | 26.37 mJ |
| Connection | | |
| Gas Inlet Connection (mm) | N/A | 9.5 |
| Exhaust Outlet Diameter (mm) | 102 | 102 |
| Exhaust Airflow (L/sec) | 105 | 105 |
| Operation | | |
| Cycles | 4 | 4 |
| Cycle Indicator Lights | No | No |
| Power | | |
| Electrical Requirements | 20 AMP/240/50/1 | 10 AMP/240/50/1 |
| Transport Data | | |
| Gross Weight (KG) | 73 | 73 |
| Net Weight (KG) | 68 | 68 |
| Dimensions (mm) | 1092h x 683w x 711d | 1092h x 683w x 711d |
| Packing Dimensions (mm) | 1156h x 762w x 864d | 1156h x 762w x 864d |

* heights may slightly vary depending on the levelling adjustments

