

V20X LOW-LINER CROSS-RAM BALER

SPECIFICATIONS

- ✓ Bale size: 800mm H (Variable) x 1100mm W x 750mm D
- ✓ Bale Weight: 200-300kg
- ✓ Power: 3 Phase 380/400 volt. 3kW motor
- ✓ Cycle time: 35 seconds
- ✓ Compaction force: Up to 25 tonnes
- ✓ Machine Weight: 980kg
- ✓ Noise Level: 74dB
- ✓ Fill opening: 1100mm W x 625mm H
- ✓ Dimensions: 1880mm H x 1695mm W x 865mm D
- ✓ Integrated bale out unit
- ✓ EN 16500 Compliant
- ✓ IP54 Standards
- ✓ E-Power standards
- ✓ PLC type controller with bale full light and auto cycle
- ✓ Single phase 220 V 50 Hz 2 kW motor available as option.



For more information:

Phone: 08 9248 8681

email: sales@smartwaste.net.au

web: www.smartwaste.net.au

10 Tambrey Way, Malaga, 6090



Low and narrow for use in areas with 2-meter ceilings and 1-meter doorways



Easy installation offers 'plug and play' capability



Cross ram and long-stroke cylinder for optimum compression in a small space



High compaction ratio creates ideal 250kg+ bales



Heavy Duty door clamp



"Bale Full" indicator light helps ensure safe operation at multi-user sites