Dynamic Engineering Australia









FLEXIBLE

operation.

SELF

SUPPORTING
Flexible arm
with Internal/
External support
construction, easy
to clean with precise
manoeuvrability.
Unique spring

High temperature resistant hose combined with a metal hood make the lightweight arm the best choice for professional and heavy duty applications for fume and dust.

controlled lock to hold the arm steady under

Takes care of large areas

This heavy duty extension is specially developed for welding, mixing of chemicals, grinding etc when you need to reach long distances (up to 9m work radius).

Ball-bearing articulated Support Arm and Parallelogram Technology

The horizontal support arm is extremely flexible due to the well tested ball-bearing and disc-brake system. The horizontal arm can carry 60 kg. The extractor hood is incredibly easy to move thanks to modern parallelogram technology.

	Art.Nr	Art.Nr
Product List	160mm Dia.	200mm Dia.
Flexi Extractor Crane 4m (2m + 2m)	P-104	P-105
Flexi Extractor Crane 5m (2m + 3m)	P-034	P-162
Flexi Extractor Crane 6m (2m + 4m)	P-036	P-173
Flexi Extractor Crane 7m (2m + 5m)	P-039	P-175
Flexi Extractor Crane 5m (3m + 2m)	P-035	P-172
Flexi Extractor Crane 6m (3m + 3m)	P-037	P-163
Flexi Extractor Crane 7m (3m + 4m)	P-040	P-164
Flexi Extractor Crane 8m (3m + 5m)	P-042	P-177
Flexi Extractor Crane 6m (4m + 2m)	P-038	P-174
Flexi Extractor Crane 7m (4m + 3m)	P-041	P-176
Flexi Extractor Crane 8m (4m + 4m)	P-043	P-165
Flexi Extractor Crane 9m (4m + 5m)	P-044	P-166

7/52 Kent Street Cannington WA 6107 Ph: (08) 9356 7633 Fax: (08) 9356 7644

Email: sales@dynamiceng.com.au Web: www.dynamiceng.com.au