

ELECTRIC SHOWER TROLLEY

The Aspire Electric Shower Trolley facilitates ergonomic showering for both caregivers and patients. Its soft patient surface and electric positioning enhance comfort and safety. Constructed from stainless steel, it maximises durability and supports a high safe working load, accommodating a wide range of patient needs.





Removable Battery

Easy swap overs allow for spare battery charging and constant uptime



Optional Platform Extension

Add-on accessory to fit a longer padded liner for tall users

CODE: BTS148140

- Hand Control can be mounted on all sides of the trolley in the integrated siderail notches
- Accessible Height Range 460mm low height enables standing transfers while the 900mm maximum height enables ergonomic carer provision
- Adjustable Side Rails offer three different positions, upright for safety, midway for carer washing access and lowered for gap-free transfers
- Middle Access Zones improve carer ergonomics and patient cleaning access
- Electric Adjustable Backrest and Tilt Angle improves patient comfort, visibility, and confidence when being transported and assists with drainage
- **High Visibility Adjustments** points are simple and intuitive to operate
- Stainless Steel Frame is durable and strong design for longevity
- Soft Shower Liner enhances patient comfort during showering or care, contributing to a better patient experience





YEAR WARRANTY
Components, Hand Control, and Cables



Code	Overall Height	Overall Length	Overall Width	Patient Surface Length	Patient Surface Width	Patient Surface Height	Backrest Range		Castor Size	Total Weight
BTS148112	720 -1180	2005 - 2205	820	1855 - 2055	600	460 - 900	15°	3°	125	95kg

 $Range of motion dimensions are accurate to a + /-10mm tolerance \mid All \ measurements are in \ millimetres \ unless \ otherwise \ specified.$



4H400E ELECTRIC SHOWER TROLLEY

- Epoxy powder-coated frame to allow easy access for carers
- Stainless steel and PVC top frame with a padded, vinyl mattress included
- Electric tilt 8°, electric trendelenburg tilt, electric high-low operation of 600mm - 1000mm
- 125mm total-lock castors for manoeuvrability and stability
- · Plug-in rechargeable battery pack
- Ergonomic push handle and wall corner buffer discs







Code	Description	Overall Width	Overall Length	Overall Height	SWL
BTS147100	Standard	730	1890	600 - 1000	150kg
BTS147122	Extra Long	730	2000	600 - 1000	200kg
BTS147124	Short	730	1500	600 - 1000	150kg

Code	Description	Overall Width	Overall Length	Overall Height	SWL
BTS147126	Wide	900	1890	600 - 1000	200kg
BTS147128	Wide Long	900	2000	600 - 1000	200kg

All measurements are in millimetres unless otherwise specified.

ELECTRIC MOBILE CHANGE TABLE

- · Epoxy powder-coated frame
- Stainless steel top frame with padded, heavy-duty vinyl top
- Electric high-low operation of 600mm 1000mm
- · Removable rechargeable battery pack
- $\cdot\,$ Strap rail and wall corner buffer discs
- 125mm total-lock castors for manoeuvrability and stability





2 YEAR WARRANTY Components



Code	Description	Overall Width	Overall Length	Overall Height	Platform Width	Platform Length
BTS147140	Standard	730	1890	600 - 1000	610	1830
BTS147142	Short	730	1560	600 - 1000	610	1500
BTS147144	Wide	900	1890	600 - 1000	710	1830

Code	Description
BTS147150	Side Rail (One Side Only)
BTS147160	Chest Strap
BTS147170	Waist Strap

All measurements are in millimetres unless otherwise specified.