

EXTERMINATOR SERIES **G2**

HIGH TEMPERATURE VERSION

| | | | | |
|-----------------------|------------------------|------------------|--------------------|---------------------------|
| 10 WARRANTY | 65 IP RATING | 70 CRI | 150 LM/W | 65° TEMPERATURE |
|-----------------------|------------------------|------------------|--------------------|---------------------------|



- » Premium, feature-rich highbay solution
- » Low power consumption and very high efficacy up to 190 lm/W
- » Ultra modern, compact design with high heat dissipation
- » Optional Intelligent sensor for additional cost savings
- » IP65 water / dust-resistant
- » Long life endurance of 50,000+ hours (10 Year Warranty)
- » Multiple mounting options - loop hanging, ceiling or wall mount
- » ETV, CE, CB, RoHS, SAA, C-tic



EMERGENCY BATTERY

IDEAL FOR

- | | | |
|-----------------------|-----------|----------------------|
| ■ Warehouse | ■ Library | ■ Wood & Paper Plant |
| ■ Mechanical Workshop | ■ Depot | ■ Indoor Plaza |
| ■ Factory | ■ Ports | ■ Shopping Centre |



| MODEL | ETG-EXTHB100-G2H | ETG-EXTHB150-G2H | ETG-EXTHB200-G2H |
|-----------------------|-------------------------------|-------------------------------|--|
| Power (W) | 100 | 150 | 200 |
| Lumen (lm) | 15,000 | 22,500 | 30,000 |
| Dimension (mm) | Φ360 X 316MM | | Φ360 X 394MM |
| Lamp Efficacy | 150 lm/W | IP Rating | IP65 |
| CCT(K) | 5000K (3000K, 4000K optional) | Anti-Glare Lens | UGR30 |
| LED Chips | SMD 2835 | Driver | Philips Driver |
| Input Voltage | 220-240V AC, 50/60Hz | Power Factor | ≥0.92 |
| Operating Temperature | -30°C ~ +65°C | CRI | >Ra70 (>Ra80 optional) |
| Beam Angle | 60° 90° 120° | Mounting Options | Loop hanging |
| Body Material | Aluminium Alloy and PC | Optional Intelligent Controls | DALI Dimmable / Microwave Motion Sensor / Zigbee Control / Daylight Sensor |
| Colour | Black | Warranty | 10 Years |



IMPROVED HEAT DISSIPATION

OPTIONAL LIGHT DISTRIBUTION

