


COPYRIGHT by MEIKO		
1.0	machine connection: Drain line hose fitted as odour trap in interior of machine	DN 22
1.1	drain (max. 750 mm above of the floor level)	DN 50
2.0	machine connection: fresh water line	G 3/4"
2.1	soft warm water 45 - 60°C	DN 15
	max. 0,54 mmol/l CaCO ₃ / 53,4 ppm/CaCO ₃ (max.3°GH) approx. water flow rate 5 l/min min. flow pressure: 60 kPa / 0,6 bar upstream of the solenoid valve, maximum pressure: 500 kPa / 5 bar stopcock and fine screen ≤ 25 µm	G 3/4 a
3.0	machine connection: electricity connecting cable	5G 6mm ²
3.1	electricity supply cable to the machine	3N PE 400V ~ 50Hz
	nominal current / - capacity	16,3 A 9,8 kW
	⊕ Voltage equalising cable	Fuse protection: 20 A
Electrical equipment suitable for supply voltage: 3N PE 380-415 V 50 Hz / 1N PE 220-240 V 50 Hz		
heat load of the wash room in case of 25 program cycles /h	total	ca. 2.7 kW
	perceptible	ca. 1.8 kW
	latent	ca. 0.9 kW
all cables, pipes etc leaving machine		1,8 m
the position of the connection piping can also be mirror-inverted		
Options available on machine		
(A) Entry height		
(D) Rinse agent pipe and suction lance		
(E) Detergent dosing unit with suction lance		
Power Wash		
Automatic hood opening		
Automatic basket detection		
feeding table on site		
discharge table on site		
	Recommended suction area according to German VDI 2052 or any local regulations have to be observed to determine ventilation of wash areas	

