

F2



|                       |   |   |         |           |           |   |              |      |
|-----------------------|---|---|---------|-----------|-----------|---|--------------|------|
| F007K(D)-W222-□□□/FAQ | 2 | 4 | 4.0/4.8 | 1.6 ~ 4.2 | 0.5 ~ 1.3 | 5 | UYX128GAS#10 | 6000 |
|                       | 3 | 5 | 5.6/6.4 | 1.6 ~ 4.2 | 0.5 ~ 1.3 | 5 | UYX128GAS#10 | 6000 |
| F007K(D)-W222-□□□/FFD | 2 | 4 | 4.0/4.8 | 1.6 ~ 4.2 | 0.5 ~ 1.3 | 5 | UYX128GAS#10 | 6000 |
|                       | 3 | 5 | 5.6/6.4 | 1.6 ~ 4.2 | 0.5 ~ 1.3 | 5 | UYX128GAS#10 | 6000 |
| F007K(D)-W222-□□□/FFP | 2 | 4 | 4.0/4.8 | 1.6 ~ 4.2 | 0.5 ~ 1.3 | 5 | UYX128GAS#10 | 6000 |
|                       | 3 | 5 | 5.6/6.4 | 1.6 ~ 4.2 | 0.5 ~ 1.3 | 5 | UYX128GAS#10 | 6000 |



F007K-W222-356/FAQ/FEC



F007K-W222-356/FFD




F007K-W222-356/FFP



FQ



FQ



FFD/FFP



FFD/FFP



◀ 以上機型可加裝  
**FSC:**  
 電眼型後切刀附直驅馬達  
 Optional device for the above models  
**FSC:**  
 Sensor type rear cutter with direct-drive servo motor

**FQ:上帶滾邊車縫**

适用于T恤、內衣褲之領口、褲管口等上帶滾邊之車縫工程，可加附电动(FEC)或气动式(FAC)长切刀式切布条装置，能将滚边布条切断，节省布条之用料增加车缝效率

**FQ:TAPE BINDING**

For tape binding on openings of leg or neck of underwears, T-shirts, etc... Also can attach electric(FEC) or pneumatic(FAC) tape cutter to save tape and increase sewing efficiency.

**FFD/FFP:上帶滾邊車縫包覆松緊帶**

上送帶裝置控制松鬆帶張力，加上膝動控制松緊帶之左右移動，能有效讓松緊帶前後段與衣身車縫固定，适用于內褲之褲頭、褲腳之滾邊加松緊帶之車縫工程

**FFD:** 齒輪箱型精準張力控制  
**FFP:** 彈簧片型簡易張力控制

**FFD/ FFP:TAPE BINDING WITH ELASTIC BAND**

Top feeding device controls the elastic band's tension. Elastic band right-left position controller (by knee-pushing) sets the materials joining at the beginning and ending of waistband, leg opening of briefs...etc.

**FFD:** Gearbox type for accurate tension control  
**FFP:** Spring type for simple tension control

|                          |
|--------------------------|
| 選購配件 OPTIONAL DEVICE     |
| FA, LF-A, FAC, FEC, LS-A |