

320





EASY AND ACCURATE ALIGNMENTS IN A COMPACT, ROBUST DESIGN.

INSTALLATION MADE EASY

With no moving parts, new alignment software that's easy to learn and use, and a robust, compact design, the geoliner® 320 Wheel Alignment System requires minimal space and none at all in the front of the lift. It's built to work with any alignment lift style and enhance performance in just about any shop.


SERVICE AND MAINTENANCE MADE EASY

Repairable on-site and boasting remote service and automatic software and specification updates, the geoliner 320 means more revenue for your business, with no more calibrating, no more cables and no more worries.

NEXT-GENERATION ALIGNER SOFTWARE

The geoliner 320's next-generation aligner software features a notification system that provides critical information without slowing down the alignment process, with an adaptive user interface that delivers instant access to productivity tools and assistance whenever required.

- Optimized vehicle selection process:
 - Quick access to history right on the home screen
 - Clear and comprehensive make/year/model selection
 - Quick model search
- Quick-select language support for procedures and printouts provides rapid changes between commonly used languages
- All new graphic displays with all screens optimized for maximum visibility and clarity



All new user interface with Compensate, Warn, Alert eliminates problems before they result in a bad alignment.

MEASUREMENT MADE EASY

Rolling run-out compensation means no more hassles: just mount and roll to measure, with no lifting, no head-charging, no head-leveling and no adapters. Place the geoliner 320 on the lift and it's ready to align.



Quick rolling compensation provides critical information via an adaptive user interface, with instant access to productivity tools and assistance.



Three levels of intervention — Compensate, Warn, Alert — with corrective actions clearly identified and more information just one click away.



Attractive toolbox styling, featuring easyrolling casters, storage for all attachments and a fully enclosed printer compartment.



Cast aluminum AC700 wheel clamps fit rims from 11" to 22," with no limitations and 4,9 to 5,2 kg (10.9 to 11.5 lbs.) per clamp.



Pods mount with ease, communicating wirelessly and store quickly and easily when finished.







Mounting hardware adapts to common alignment lifts and is easily removed with Quick Release System.



Small footprint makes the most of any available space, bringing advanced, intuitive alignment services to shops of every size.

ADD ALIGNMENTS TO YOUR BUSINESS THE EASY, ERROR-FREE WAY.

Using advanced XD cameras and sophisticated monitoring algorithms, the 320 Wheel Alignment System detects issues with suspension stress and errors from lift clamps, environment, and more. To save time and ensure accuracy on every alignment, users are notified only when necessary with additional information never more than one click away.

Each rear wheel pod uses two cameras to image a front wheel pod and a reference target mounted at the front of the car, allowing a clear view of all targets through full rotation. The left-side reference pod then uses its camera to create a full 3-D alignment without obstructions from low hanging vehicle components.

Reference pods work easily with either a lift or a pit, allowing for flexibility in installation and placement so they don't interfere with normal work flow. (Typical mounting is at the front edge of the lift surface on the outer edge of the runway.) And since all communication within the 320 happens wirelessly, you never have to worry about beams and cables taking up valuable space in the shop.

FEATURES

- · Fast rolling run-out compensation for accurate vehicle measurements
- · Simple pod design for easy setup and measurement and a compact wireless design
- · Next Generation Battery System, with hot-swappable batteries to eliminate downtime
- · Accurate and reliable XD camera technology, with "compensate, warn, alert" notification

TECHI	IIPNI	CNEC	ובורח	TINNC
IELNI	IILAL	JPEL	ITILMI	בווטוו

Track Width	121,9 cm - 243,8 cm (48" - 96")		
Wheel Base	200,7 cm - 457,2 cm (79" - 180")		
Power Requirements	100 – 230v AC (Must have earth ground). 15 amps circuit, 50/60Hz.		

STANDARD ACCESSORIES

- · Steering Wheel Holder
- · Brake Pedal Depressor
- · Color Inkjet Printer
- · Wheel Chocks
- · Side Mount Lift Kit

OPTIONAL ACCESSORY

· Floor Mount Lift Kit

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)
Phone: +39 0522 733-411 · Fax: +39 0522 733-479 · www.hofmann-equipment.com

Snap-on Equipment Austria GmbH · Hauptstrasse 24/Top 14 · A-2880 St. Corona/Wechsel (RE) Phone: +43 1 865 97 84 · Fax: +43 1 865 97 84 29 · www.hofmann-equipment.com

Snap-on Equipment France · ZA du Vert Galant · 15, rue de la Guivernone BP 97175

Saint-Ouen-l'Aumône · 95056 Cergy-Pontoise CEDEX
Phone: +33 134 48 58-78 · Fax: +33 134 48 58-70 · www.hofmann-equipment.com

Snap-on Equipment GmbH · Konrad-Zuse-Straße 1 · 84579 Unterneukirchen Phone: +49 8634 622-0 · Fax: +49 8634 5501 · www.hofmann-equipment.com

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE) Phone: +39 0522 733-411 · Fax: +39 0522 733-410 · www.hofmann-equipment.com

United Kingdom

Snap-on Equipment Ltd. - Unit 17 Denney Road, King's Lynn - Norfolk PE30 4HG Phone: +44 118 929-6811 - Fax: +44 118 966-4369 - www.hofmann-equipment.c

Part of the machines is illustrated with optional extras which are available at extra cost. $\label{eq:cost} % \begin{subarray}{ll} \end{subarray} % \begin{subarray}{ll} \end{subarra$ Technical and visual modifications reserved

Cod.: 9702 934 · 10/2018

