

PO Box 1468 Auburn St. Wollongong NSW 2500 Fax: +61 2 4226 2208 Email: sales@spacepac.com.au ABN 98 002 454 462



Often imitated but never equaled.

It's no surprise the competition envies our original design.

This agile and versatile personnel carrier has it all: A narrow deck, four wheels for greater stability on rough terrain, powerful motor, rugged automotive differential and larger self-adjusting drum brakes, all-steel unibody construction, bolt-on front bumper and side bar protection, easy-to-access under-seat battery compartment... The list keeps going.

It can also pull up to 6,000 Ibs.* making it a great tow Tractor.









Vehicle shown may have optional accessories and is provided for illustrative purposes only.

M	P	25	0
M	0	de	ls











· /	\ /
4	- V

1

500 lbs.

2,000 lbs.

10 mph

75 "

36V

1

500 lbs.

6,000 lbs.

mph

75 "



PO Box 1468 Auburn St. Wollongong NSW 2500
Phone: 1300 763 444 Fax: +61 2 4226 2208
Email: sales@spacepac.com.au ABN 98 002 454 462







CAB

Safe and comfortable all-steel cabs

Protects operators and everyone around them. Our customizable cabs come with a long list of standard and optional features: lockable/Mika/removable doors, canopy top, ladder/pipe rack, wipers, rear-view mirror, sliding windows with safety glass, heater, air conditioning, cabmounted strobe light, cab sound proofing, rust proofing... the list goes on and on.

BRAKES


Heavy-duty braking power


Provides faster braking and shorter stopping distances, even when towing heavy loads. Stronger, more durable and more efficient design ensures superior braking performance with less maintenance vs. competing brakes. Brake safely and confidently every time.


LIFT-OUT

Time-saving lift-out battery compartment

Makes changing batteries quick and easy. Because the batteries are not attached to the vehicle, maintenance is easier, too. Simply lift out the compartment and replace batteries with fresh ones.









Email: sales@spacepac.com.au ABN 98 002 454 462





	24V	36V		
POWERTRAIN				
Motor	6 hp shunt motor	10 hp shunt motor		
Drive Axle	Helical gear Differential	Helical gear differential		
Transmission	Direct drive	Direct drive		
Controller	SEPEX Electronic speed controller	SEPEX Electronic speed controller		
ENERGY				
Voltage	24V	36V		
Battery	Four 6V-232AH batteries	Six 6V-232AH batteries		
Charger	High-frequency (85-265VAC / 45-65Hz, 1kw), built-in and automatic.	High-Frequency Charger, improves battery performance, prevents current surge, 50/60HZ, 110/220VAC		
CHASSIS				
Body	14-G diamond-plate steel body, tubular frame	14-G diamond-plate steel body, tubular frame		
Suspension	Dual coil springs and shock absorber on rear	Dual coil springs and shock absorber on rear		
Brakes	Dual self-adjusting mechanical drum brakes on rear, hand lever parking brake	Dual self-adjusting mechanical drum brakes on rear, hand lever parking brake		
Wheels	4.8x8 LRB pneumatic tires	4.8x8 LRB pneumatic tires		
Steering	Automotive Steering Wheel	Automotive Steering Wheel		
Seats	Bucket seat on slide adjusters	Bucket seat on slide adjusters		
EQUIPMENT				
Lights	Headlight, Brakes & Tails	Headlight, Brakes & Tails		
Indicators	Battery status indicator	Battery status indicator		
Accessories	Bolt-on bumpers and rear wheel guards, 24V accessories to equalize cells and extend battery life.	Bolt-on bumpers and rear wheel guards, 24V accessories to equalize cells and extend battery life.		
Safety	Reverse alarm, deadman seat switch, horn	Reverse alarm, deadman seat switch, horn		