

Tenso® LST 252

Battery Powered Strapping
Tool 12mm - 16mm

#61812



High Productivity

Saving you time with auto and manual modes

All In One

Eliminates the requirement for numerous tools and accessories

Environmentally Friendly

Welding process eliminates the need for buckles, reducing landfill

High Quality

Innovative German design with the latest technology

The innovative Tenso LST 252 Battery Powered Strapping Tool is faster and easier to use, providing the operator with higher efficiency and productivity.

Introduced into the market in 2016, the Tenso LST Battery Powered Strapping Tools have quickly become the market leader with the highest quality production and manufacturing technique, ensuring tool longevity, and less down time with minimal repairs and servicing for every user.

The tools feature an automatic welding system offering automatic, semi-automatic, manual and soft options through the enhanced tension system.

The perfectly balanced Tenso LST 252 is comfortable and simple to operate in both horizontal and vertical applications, primarily due to the ergonomic and light weight design.

All tensioning and sealing operations are controlled by electronic push buttons. Also featuring a brushless, wear-free, motor system powered by the highest quality Bosch Li-ion battery, providing up to 600 cycles per battery charge.



Features

- Optimal ergonomics for perfect device balance
- Super safe handling with low weight
- Battery protection through smart housing design
- Extremely robust housing for extended life
- Simple troubleshooting with error code display
- Includes high-quality tool case for optimal accessory storage
- Up to 600 strapping cycles per battery charge
- 30 minutes charging time with fast charger
- Special base plate for easy use in adverse environments
- Extreme reliability and durability: 5 devices successfully tested for 300,000 strapping cycles.



Specifications

Dimensions (LxWxH)	375mm x 145mm x 145mm
Package Type	Flat Surface (min. length 120mm)
Strap Type	PP/PET
Strap Width	12mm - 16mm
Strap Thickness	0.65mm - 1.05mm
Max. Tension	2520n/250kgf
Join Type	Friction Weld Seal
Weight	3.6kg (inc. Battery)
Battery	Bosch 18v - 4.0Ah Li-Ion
Battery Charge Time	30 minutes
Battery Usage Cycle	Up to 600 uses on a single charge

