

StrapPack

Semi-Automatic Strapping Machine

Introducing the new iQ-400, StrapPack's new semi-automatic strapping machine with dual tension mode. This allows for a wide variety of applications with just a flick of a switch.

Standard



Covered with Side Panels (Optional)

iQ-400

- The iQ-400 is a durable and heavy-duty strapping machine designed to withstand various harsh environments.
- The iQ-400 is yet amazingly quiet to operate and well suited for office use also.
- The iQ-400 has less moving parts, which makes it easy to maintain and keeps the operation cost low.
- All electric parts are arranged in one side of the machine, enclosed in the cabinet, for easy maintenance and protection of crucial parts.
- The iQ-400 runs strap from 5 millimeters to 15.5 millimeters (5/8 inches) without additional parts.
- The torque tension mode is suitable for stronger tension or to strap compressible packages, while the stroke tension mode is best for soft tension or quick operation.
- Tool-free access to frequently accessed areas for easy maintenance.
- Hinged tables are easy to remove for daily maintenance.
- Optional adjustable legs are available upon request. With this option, table height can be adjusted from 775.5 mm up to 925.5 mm. The machine with this option comes without side panels.

Dimension	Width	780 mm	30-11/16 in.
	Height	777 mm(with work guide)	30-9/16 in.(with work guide)
	Depth	540 mm	22-7/16 in.
	Weight	56 kg.	124 lbs.
Table Height		752 mm	29-5/8 in.
Min. Package Size		W 100 X H 30 mm	W 3-7/8 X H 1-1/8 in.
Joint / Strap/ Coil		heat seal / polypropylene ID 200 or 230 X W 200 mm	heat seal / polypropylene 8 X 8 or 9 X 8 in.
Strap Width / Thickness		5, 6,9,12 (15.5) mm /0.45-0.7mm	1/4,3/8,1/2 (5/8) in./ 0.017-0.027 in.
*Strap Tension		*Max. 500 N (51 kgf) or 150mm stroke	*Max. 112 lbsf. or 6" stroke
Power Supply		100-120, 200-240 V 1 Phase 50 / 60 Hz 0.25 kW	

*The machine shipped with CE specification has a different max strap tension " 392N (40kgf)" due to CE safety standard.
Dimensions and specifications are subject to change without notice.
Modification rights reserved.

© 2017 Strapack Corporation

DISTRIBUTED BY:

ISO 9001 and 14001 Certified



STRAPACK CORPORATION
8-16-6 Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN
Phone: 81-3-6278-1806 Fax: 81-3-6278-1807
(URL) <http://www.strapack.com> (E-mail) info@strapack.com
STRAPACK INC.
33508 Central Avenue, Union City, CA 94587-2097 U.S.A.
Phone :1-510-475-6000 Fax: 1-510-475-6090
STRAPACK, N.V./S.A.
Uilenbaan 200, B-2160 Wommelgem, BELGIUM
Phone: 32-3-355-1520 Fax: 32-3-355-1521