

# LKexv 3910

## MediLine



Gross/net capacity	360/344 litre
Ext. dimensions in mm (w/d/h)	597/615/1840
Int. dimensions in mm (w/d/h)	440/435/1635
Energy consumption in 365 days	316 kWh
Climate rating	7 <sup>1</sup>
Refrigerant	R 600a
Airborne acoustical noise emissions	48 dB(A)
Connection Rating	1.5 A
Voltage	220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	+3°C to +16°C
Gradient *	5.5°C
Max. fluctuation **	5.1°C
Housing material/colour	steel/white
Door/lid material	Steel
Liner Material	moulded polystyrol white
Type of Control	electronic controller
Temperature display	außen digital
Fault: warning signal	visual and audible
Interface	RS 485
volt-free alarm contact	yes
Adjustable Shelving	5
Shelf material	glass
Shelf loading	40 kg
Handle	Ergonomic door handle
Lock	fitted
Self-closing door	yes
Door hinges	right, reversible
Insulation	40 mm
Gross/net weight	74 / 68 kg
EAN-Nr.	9005382197097

1 Climate class / Climate Råting: SN +10°C to +32°C N +16°C to +32°C ST +16°C to +38°C T +16°C to +43°C  
3 +10°C to +25°C 4 +10°C to +30°C 5 +10°C to +40°C 7 +10°C to +35°C

\* Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

\*\* Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.

# LIEBHERR