

EMV+® 731 SERIES

ZOLL®



MILITARY TOUGH  
CLINICALLY PROVEN

## Portable Ventilator

### Full Patient Range

For patients from infant ( $\geq 5$  kg) through adult

### Smart Help™ Display

Guides operator through on-screen commands when responding to alarms

### Versatility with Standard Military Equipment

Functions with deployed oxygen concentrator systems used by the military

### Unprecedented Battery Run-Time

No additional battery back-up needed thanks to 10-hour battery run-time. Battery recharges to 90% in 2 hours.

### AWR Certified

Airworthiness Release certified. Approved for use during all phases of flight aboard both fixed-wing and rotary-wing U.S. Air Force and Army aircraft.

### Silent and Dark Mode

Can be switched to a silent and dark mode, preventing it from interfering with advanced infrared night-vision equipment

### Rugged, All-Weather Device

Designed for the unique needs of the military to handle austere environments. Meets an unprecedented set of military standards.

**ZOLL Medical Corporation**  
**Worldwide Headquarters**  
269 Mill Road  
Chelmsford, MA 01824  
978-421-9655  
800-804-4356

For subsidiary addresses and fax numbers, as well as other global locations, please go to [www.zoll.com/contacts](http://www.zoll.com/contacts).

## EMV+® 731 Series Specifications

### Clinical Specifications

**Operating Modes:** AC, SIMV, CPAP, BL

**Breath Target:** Volume and pressure

**Special Functions:** Plateau Pressure, Manual Breath, Apnea Backup, Oxygen in Use, Inverse Ratio

**Flow Rate:** 0 to 100 LPM @ 40 cm H<sub>2</sub>O

**Breath Rate:** 1 to 80 BPM

**Tidal Volume:** 50 to 2000 ml ATPD  $\pm$  10% of setting

**Inspiratory Time:** 0.3 to 5.0 seconds

**I:E Ratio:** 1:99 to 4.0:1.0

**FiO<sub>2</sub>:** 21 to 100%  $\pm$  3% of full scale  $\pm$  10% of setting

**PEEP:** 0 to 30 cm H<sub>2</sub>O

**Pressure Support:** 0 to 60 cm H<sub>2</sub>O

**Peak Inspiratory Pressure (PIP):** 10 to 80 cm H<sub>2</sub>O

**Trigger Sensitivity:** -0.5 to -6.0 cm H<sub>2</sub>O

**Oxygen Input Pressure:** 55 psig (-25%; +20%) (380 kPa)

### Safety Specifications

**Airway Pressure High Limit:**

20 to 100 cm H<sub>2</sub>O values

**Airway Pressure Low Limit:**

Off, 3 to 35 cm H<sub>2</sub>O

**BPM High Alarm Limit:** Off, 2 to 99

**BPM Low Alarm Limit:** 2 to 40

**LED Status/Alarm Indicator:**

Red, yellow, and green LCD/LED adjustable

### Environmental

**Operating Voltages:** 100 to 240 VAC (50/60 Hz) or 12.5 to 28.0 VDC

**Operating Time:** Internal battery 10 hours

**Temperature Ranges:**

**Operating:** -25° to 49°C (-13° to 120°F) with battery charging, battery discharge and AC power operation

**Battery Charging:** 0° to 45°C (32° to 113°F)

**Long-Term Storage:** -15° to 21°C (5° to 71°F) Optimal storage conditions

**Altitude Compensation:** Automatic -2,000 to 25,000 ft. (-601 to 7,620 meters)

**AWR Certified:** Approved for most U.S. Military aircraft

**Temperature and Humidity Testing:** MIL STD 810F

**Ingress Testing:** MIL STD 810 F

**Shock and Vibration Testing:** MIL STD 810F

**Altitude Testing:** MIL STD 810F

**EMC Testing:** MIL STD 461F

**Military Vehicle Power:** MIL STD 1275 F

### General

**Size:** 8.0" wide x 12.5" high x 4.5" deep (20.3 cm wide x 31.8 cm high x 11.4 cm deep)

**Weight:** 9.7 lbs (4.4 kg)

