

Mini Track Loaders / MT85 Mini Track Loader

Specifications & Options

Standard
 Optional
 N/A Not Applicable

Units Metric

Bobcat MT85

⊖ Engine

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Displacement	900 cm ³
Number of Cylinders	3

⊖ Performance

Rated Operating Capacity (SAE)	386 kg
Tipping Load	1115 kg
Operating Weight	1411 kg
Ground Pressure (Rubber)	0,34 bar
Travel Speed	6,4 km/h
Travel Speed - Reverse	3,9 km/h

⊖ Capacities

Fuel Tank	26,5 l
-----------	--------

⊖ Hydraulic System

Pump Capacity	45,4 l/min
System Relief @ Quick Couplers	199,95 bar
Auxiliary Std Flow	n/a

⊖ Dimension

Length	2697 mm
Width	904 mm
Height	1387 mm
Height to Bucket Hinge Pin	2055 mm
Length of track on ground	1031 mm
Reach @ Maximum Height	472 mm

⊖ Features

Lift-Arm Support	■
Auxiliary Hydraulics	■
Spark Arrestor Muffler	■
Bob-Tach Attachment System	☑
Reverse Travel Stop Panel	N/A
Wide Track	☑
Neutral Start Interlocks	■
Lift Arm Lockout With Manual Bypass	■
Tilt Lockout	■
Built-In Tie Down & Crane/Lift Locations	■
Ride-on Platform	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.