

MANUFACTURING INTELLIGENT COMPRESSED AIR® PRODUCTS SINCE 1983





COOL



CONSERVE





CONVEY

CATALOG

6

NEW

HollowStream™ Liquid Atomizing Cone Nozzles...... pg. 103

TurboBlast® Safety Air Guns....pg. 115

Intellistat® Ion Air Nozzle......pg. 143



YOU REQUESTED THIS CATALOG AND PRICE LIST.
PLEASE SEE MAILING LABEL ON BACK COVER.



THANKS FOR CHOOSING...

...EXAIR as the source for your problem solving products. This catalog includes new products, technical data, photos and drawings to help you with your application. Please take a few extra minutes to review the different sections of this catalog. Chances are, you'll find the answers to some of your industrial/production problems.

EXAIR products are designed to improve the overall efficiency of your operations. Our Ultrasonic Leak Detector, the EFC™ Electronic Flow Control for compressed air and Digital Flowmeter are money-saving and energy-conserving tools that can save your company tens of thousands of dollars. The Digital Sound Level Meter can help you increase safety and eliminate costly fines resulting from high noise.

The <u>Best Practices for Compressed Air Systems</u> manual published by the Compressed Air Challenge® recommends Intelligent Compressed Air® products like the Super Air Knife™, Super Air Amplifier™, and the family of Super Air Nozzles™ for energy conservation. Our Intelligent Compressed Air® products are identified with this graphic.

The people at EXAIR do their best to earn your business. When you contact EXAIR, you can expect quality products along with exceptional value and service since the products we manufacture are sold direct to you.

Here are a few ways we make that happen:

Free Expert Technical Help! Our full staff of qualified Application Engineers is here to help you with your application. When you call our toll free number, live chat, tweet, fax or e-mail us, you'll get help right away from someone who understands the product and your application.

Great support! Would you like to read our blog posts regarding new applications, to use energy cost calculators to see how much your company can save, or to receive Twitter alerts for up to the minute information? Do you need a CAD drawing of an EXAIR product, a copy of a lost installation sheet or want to place an order after hours? Our secure web site lets you do all that and more!

Special Products Just For You! Do you have an application for a product that isn't shown in our catalog? Need an EXAIR product in another size, an odd length or different material? We manufacture many specials as shown throughout this catalog. Just let us know what you have in mind.

Fast Delivery! The products shown in this catalog are in stock and in most cases, will ship the same day you order.

For 25 years running, 99.9% of our orders shipped on time!

We will continue to do everything possible to see that you are satisfied with EXAIR. We appreciate your interest in our products and look forward to working with you.

Sincerely,

Bryan Peters, President

P.S. There's no risk to try our products. In addition to our five year warranty, we extend the following Unconditional Guarantee to all our U.S. and Canadian customers:



EXAIR unconditionally guarantees its cataloged products for 30 days.

If you are not satisfied for any reason within that time, you may return the product for full credit with no restocking charge.



Compressed Air Challenge is a registered trademark of Compressed Air Challenge, Inc.

EXAIR is the leader in standards compliance











Stay up to date by visiting our website and take advantage of the information and services we didn't have room to display in this catalog.







Where you can

- · Chat live with our problem solving, technical expert Application Engineers
- Watch product videos to learn more about the features and benefits of our engineered products
- Quickly order online with a purchase order or credit card (US & Canada)
- Access product presentation slides you can use to educate others
- Find International Distributors all across the world



Access our Knowledge Base to

- Download 3D models and CAD drawings in multiple formats to place into your drawings
- Calculate air savings and ROI to see how quickly EXAIR products will pay off
- Search our Case Study Library & Applications database and become familiar with how our products solve problems
- Use our product FAQ's for quick access to our most common questions
- Learn about our free Efficiency Lab service and use it to determine air and money savings you can achieve when installing EXAIR engineered solutions
- Collect compressed air data and pipe sizing recommendations
- . Find Flow, Force and Heat conversions



Visit our PDF library and download

- · Electronic files of the entire catalog or individual sections
- Installation and Maintenance Guides on every EXAIR product
- Our current price list to have all product prices in one convenient location
- EXAIR's Air Nozzle Blowoff Guide to see the details on our enormous selection of sizes, materials and performance options



Follow our blog for 5 new entries a week and learn

- · Details and installations of widely varied applications
- The methodology and results of critical mathematical formulas which help determine money savings, air savings, performance benefits and more
- · New product releases before they reach our catalog or website
- More about EXAIR, our team and community involvement
- Go to blog.exair.com







Make social connections

- Watch over 90 videos on EXAIR's YouTube Channel and see product features and benefits, applications, Tips & Tricks, How-to, our team members, or be entertained by Professor Penurious!
- Follow our Company on Twitter @EXAIR or our Application Engineers and learn more about promotions, updates on manufacturing, engineering and international industry perspective.

















• Connect with us on Facebook at facebook.com/exair or follow us on Instagram.



EXAIR Optimization

Minimize compressed air use and detect wasteful leaks

6 Steps to Optimization
Electronic Flow Control
Digital Flowmeter
Digital Flowmeter with wireless capability 1
Digital Sound Level Meter
Ultrasonic Leak Detector1



Air Knives

Blowoff, clean, dry and cool with less noise and air consumption

id air consumption	
Super Air Knife	0
Compare Blowoffs	3
Explanation of Materials	6
Universal Air Knife Mounting System	9
Plumbing Kits	9
Standard Air Knife	3
Full-Flow Air Knife	



Air Wipes

Blowoff, dry, clean and cool pipe, cable, extruded shapes and hose

Super Air Wipes	 	 38
Standard Air Wines	 	 42

44

Vent, exhaust, cool, dry and clean - with no moving parts

Super Air Amplifiers				 				.46
Adjustable Air Amplifiers		 		 		 		.50

52

Air Nozzles and Jets

Reduce noise levels and air costs on blowoff operations

AIT NOZZIES52
Air Nozzle Comparison Chart
Super Air Nozzles55
Flat Super Air Nozzles57
Super Air Scraper57
Back Blow Air Nozzles
Safety Air Nozzles60
Air Jets
High Force Air Nozzles
High Force Air Nozzle Comparison Chart63
High Force Flat Super Air Nozzles63
High Force Super Air Nozzles64
Super Air Nozzle Clusters67
Stay Set Hoses
Swivel Fittings
Blowoff Systems

70

Air Atomizing Nozzles

All stainless steel construction for durability and corrosion resistance

ia corrosioni resistance	
1/8 NPT Atomizing Nozzles	.71
Internal Mix Narrow Angle Round	. 71
Internal Mix Wide Angle Round	. 72
Internal Mix Flat Fan	.73
External Mix Narrow Angle Flat Fan	. 74
Siphon Fed Round	.75
Siphon Fed Flat Fan	.76
1/4 NPT Atomizing Nozzles	.77
Internal Mix Narrow Angle Round	. 77
Internal Mix Wide Angle Round	. 78
Internal Mix Flat Fan	79
Internal Mix Deflected Flat Fan	. 80
Internal Mix 360° Hollow Circular	. 80
External Mix Round	. 81
External Mix Narrow Angle Flat Fan	. 82
External Mix Wide Angle Flat Fan	. 83
Siphon Fed Round	.84
Siphon Fed Flat Fan	.85
1/2 NPT Atomizing Nozzles	.86
Internal Mix Narrow Angle Round	
	1/8 NPT Atomizing Nozzles Internal Mix Narrow Angle Round. Internal Mix Hat Fan External Mix Plat Fan External Mix Narrow Angle Flat Fan Siphon Fed Round. Siphon Fed Round. Siphon Fed Round. Siphon Fed Rat Fan 1/4 NPT Atomizing Nozzles Internal Mix Narrow Angle Round. Internal Mix Wide Angle Round. Internal Mix Plat Fan Internal Mix Plat Fan Internal Mix God' Hollow Circular External Mix Bround External Mix Narrow Angle Flat Fan Siphon Fed Round.



No Drip Air Atomizing Nozzles

Eliminate drips to conserve valuable liquids and improve product finishes.

na improve product iinisnes.
1/8 NPT No Drip Atomizing Nozzles
No Drip Internal Mix Narrow Angle Round93
No Drip Internal Mix Wide Angle Round 93
No Drip Internal Mix Flat Fan
No Drip External Mix Narrow Angle Flat Fan 95
No Drip Siphon Fed Round96
No Drip Siphon Fed Flat Fan96
1/4 NPT No Drip Atomizing Nozzles
No Drip Internal Mix Narrow Angle Round93
No Drip Internal Mix Wide Angle Round 93
No Drip Internal Mix Flat Fan
No Drip Internal Mix Deflected Flat Fan 94
No Drip Internal Mix 360° Hollow Circular 94
No Drip External Mix Round95
No Drip External Mix Narrow Angle Flat Fan 95
No Drip External Mix Wide Angle Flat Fan 95
No Drip Siphon Fed Round96
No Drip Siphon Fed Flat Fan
1/2 NPT No Drip Atomizing Nozzles
No Drip Internal Mix Narrow Angle Round 93
No Drip Internal Mix Wide Angle Round93
No Drip Internal Mix Flat Fan
No Drip Internal Mix 360° Hollow Circular94
No Drip External Mix Narrow Angle Flat Fan 95
No Drip Siphon Fed Round
Droplet Size/Spray Angle Information



Liquid Atomizing Spray Nozzles Stainless-steel nozzles to atomize pressured

liquids. No air required.	
FullStream Cone Nozzles	99
HollowStream Cone Nozzles	102





Safety	/ Air Guns	

Safety air guns use engineered air nozzles for high performance

Chip	Shields	105
VariB	Blast® Precision Safety Air Guns	106
VariB	Blast® Compact Safety Air Guns	107
Soft	Grip Safety Air Guns	109
Soft	Grip Super Air Scraper	112
Heav	y Duty Safety Air Guns	113
Back	Blow Safety Air Guns	114
Turbo	oBlast® Safety Air Guns	115
Supe	r Blast Safety Air Guns	117



Gen4® Static Eliminators

Eliminate static electricity, dust and

SHOCKHAZAIU	
Gen4® Super Ion Air Knife121	
Static Meter123	
Gen4® Standard Ion Air Knife127	
Gen4® Ionizing Bars129	
Gen4® Super Ion Air Wipes	
Gen4® Ion Air Cannon	
Gen4® Ion Air Gun	
Gen4® Ion Air Jet/Gen4 Stay Set Ion Air Jet 137	
Gen4® Ionizing Point	
Gen4® Power Supplies	
Intellistat® Ion Air Gun141	
Intellistat® Ion Air Nozzle	



E-Vac® Vacuum Generators Vacuums for lifting, clamping, mounting and placement

How to Build an E-Vac System
In-Line
Adjustable150
Vacuum Cups

	K	N	
			5
		Line Va	
			9
		Myse	

Air Operated Conveyors Convey parts, materials and waste -

with no moving parts

Line Vac	156
Threaded Line Vac	162
Heavy Duty Line Vac	165
Sanitary Flange Line Vac	167
Light Duty Line Vac	169



Industrial Housekeeping Reliable vacuums for chip removal, liquid

u	mister and eleaning
	EasySwitch® Wet-Dry Vac17
	Reversible Drum Vac17
	High Lift Reversible Drum Vac
	Chip Trapper
	High Lift Chip Trapper
	Chip Vac
	Heavy Duty Dry Vac18
	Heavy Duty HEPA Vac18
	Vac-u-Gun

Vortex Tubes & Spot Cooling Cold air for industrial spot cooling problems

Vortex Tubes		 	 	 	 189	
Adjustable Spot Coole	r.	 	 	 	 197	
Mini Cooler					200	



Cold Gun Aircoolant Systems

Cool machining operations with clean, cold air



Cabinet Cooler® Systems Cool and purge NEMA 12, 4 and 4X electrical

trol panels
How it Works
Selecting the Right Model
Special Cabinet Coolers
Calculating Heat Load
Cabinet Cooler Sizing Guide
NEMA 12 Models212
NEMA 4 Models213
NEMA 4X Models214
Cabinet Cooler System Accessories215
Hazardous Location Cabinet Coolers

Mufflers, filters, regulators, valves, swivel fittings and more

Filters218
Regulators
Silencing Mufflers 220
Valves, Swivels, Thermostats
Magnetic Bases, Stay Sets, Hoses 223
Air Hoses
Fittings224
Receiver Tank



Catalog item orders received before 2 pm EDT/EST are generally shipped from Cincinnati, Ohio on the same day. You can expect delivery within 1-4 days depending on your location.

Terms and Conditions (U.S. and Canada Only)

Terms: Net 30 days upon credit approval, Visa, MasterCard, Discover and American Express.











ICC (International Chamber of Commerce) **INCOTERM 2010:**

Delivery

EX WORKS (EXAIR Corporation, 11510 Goldcoast Dr., Cincinnati, Ohio 45249, USA.)

All cataloged products are shipped from stock, via U.P.S. within 24 hours after receipt of order. Priority shipment is available upon request.

E-mail: orders@exair.com

Call 1-800-903-9247 or +1-513-671-3322 Fax toll free 1-866-329-3924 or

Worldwide 7:00 a.m. to 4:00 p.m. ET (Mon. - Fri.)

Worldwide +1-513-671-336 Secure website: www.exair.com

Remit to address (payments only):

EXAIR Corporation Location 00766, Cincinnati, Ohio 45264-0766

Sales and use tax, where applicable, are not included.

Technical Assistance: Please call our Application Engineering Department,

1-800-90-EXAIR (1-800-903-9247) e-mail at techelp@exair.com.

Built to Last WARRANTY Year Warranty applies to compressed air products only.

powered products.

Warranty:

5 Year "Built To Last" Warranty against defects in workmanship and materials on all compressed air products*. Defective products must be returned freight prepaid for repair or replacement at our option. This warranty applies under conditions of normal use, but does not apply to defects that result from

intentional damage, negligence, unreasonable use, wear or exposure.

FXAIR's Unconditional Guarantee:

A 1 Year Warranty applies to all accessories and electrically

Extends to all U.S. and Canadian customers and includes invoiced U.P.S. Ground Service shipping charges. Products returned after the 30 day guarantee period are subject to a 15% restocking charge. Products must be returned freight prepaid.



EXAIR unconditionally guarantees its cataloged products for 30 days. If you are not satisfied for any reason within that ne, you may return the product for full credit with no restocking charge.

Copyright Restrictions:

The content of the EXAIR Catalog, including all photos, graphics, drawings and arrangements are proprietary to EXAIR Corporation and are protected by the United States and international copyright and trademark laws. You are authorized to use the contents of

the EXAIR Catalog for personal use or as it relates to your role as a current or prospective customer of EXAIR. The contents of this catalog may not be copied or modified for any type of publication or distribution without the prior written consent of EXAIR Corporation. The content of the EXAIR Catalog is the intellectual property solely of the EXAIR Corporation with no rights transferred to other parties. No part of this catalog may be reproduced for any commercial purposes without the express authorization in writing by the EXAIR Corporation.

Trademarks:

"EXAIR.com", "EXAIR", "Cabinet Cooler", "E-Vac", "Intelligent Compressed Air", "VariBlast", "Gen4", "Intellistat", "EasySwitch", "TurboBlast" and "Compressed Air Intelligence" are registered trademarks of the EXAIR Corporation. The EXAIR logo, product names, designs and descriptive phrases are trademarked by EXAIR Corporation. These trademarks may not be used without prior written permission of the EXAIR Corporation.

EXAIRLogger, EFC, Digital Flowmeter, Digital Sound Level Meter, High Power Cold Gun, Super Air Knife, Standard Air Knife, Full-Flow Air Knife, Air Cannon, Super Air Amplifier, Adjustable Air Amplifier, Super Air Nozzle, Micro Air Nozzle, High Power Safety Air Nozzle, Stay Set Hose, Soft Grip Super Air Scraper, Super Air Scraper, Super Blast Safety Air Gun, Super Air Wipe, Heavy Duty Line Vac, Light Duty Line Vac, Sanitary Flange Line Vac, Threaded Line Vac, FullStream, FloodStream, HollowStream, Standard Air Wipe, Super Ion Air Knife, Standard Ion Air Knife, Super Ion Air Wipe, Ion Air Cannon, Ion Air Gun, Ion Air Jet, Ionizing Point, Stay Set Ion Air Jet, Line Vac, Chip Vac, Heavy Duty Dry Vac, Heavy Duty HEPA Vac, Reversible Drum Vac, High Lift Reversible Drum Vac, Chip Trapper, High Lift Chip Trapper, Vac-u-Gun, Deep Hole Vac-u-Gun, Air Disk, Air Stik, Mini Cooler, Cold Gun Aircoolant System, and ETC are trademarks of EXAIR Corporation.

Cincinnati, Ohio 45249-1621 Phone Number: (513) 671-3322 Fax Number: (513) 671-3363 E-mail: techelp@exair.com Web Site: www.exair.com

11510 Goldcoast Dr.



Corporation

Intelligent Compressed Air® products are identified throughout this catalog that can help your plant save tens of thousands of dollars over the course of a single year. The Best Practices for Compressed Air Systems manual published by the Compressed

Air Challenge* recommends products like the Super Air Knife™, Super Air Amplifier™, and the family of Super Air Nozzles™ for energy conservation. Many of the products shown offer unique ways to solve common industrial problems using compressed air. Compressed Air Challenge is a registered trademark of Compressed Air Challenge, Inc.



EXAIR has partnered with Energy Star, a voluntary program of the U.S. Department of Energy and the Environmental Protection Agency. Energy Star offers energy efficient solutions to help save money while protecting the environment for future generations. EXAIR has implemented improved energy management practices and technologies throughout our facility, including energy efficient lighting, HVAC systems, and electronic thermostats. EXAIR's participation in this program underscores our commitment to conserving energy.

EXAIR products are subject to ongoing development. Specifications are subject to change without notice.

Some products in this catalog are covered by U.S. Patent #5402938, #8153001, #8268179, #D903,817 and #9156045, and others may be U.S. Patent Pending. EU Regd, Des. No.00770318-0001 D Mexico No.60723; Canada No.194141

Copyright @2022 EXAIR Corporation. All Rights Reserved.













EXAIR's Intelligent Compressed Air® products vs Your current installation

How does the Efficiency Lab work?

Our Efficiency Lab service begins with receiving a sample of the product(s) you currently use for your application. One of our qualified Application Engineers will use calibrated testing equipment to compare the performance of your existing product(s) to an EXAIR engineered solution. These tests will determine air consumption, noise levels and force. The test results will then be published in a comprehensive report, which includes a cost savings analysis, and be provided to you. For most applications, EXAIR products can help you improve application efficiency AND typically pay for themselves in a matter of weeks.

How can I get a product tested for free?

To participate in our FREE Efficiency Lab please contact one of our Application Engineers and get the details about sending us your product(s).

You may reach an Application Engineer by phone at (800) 903-9247 or (513) 671-3322. You can send an email to lab@exair.com or visit our website and take advantage of our live help at www.exair.com.

EXAIR's FREE Efficiency Lab service determines how much air and dollar savings you will achieve by installing one of our Intelligent Compressed Air products.

Unable to send your product to EXAIR's Efficiency Lab?

If it is not possible to send us your product, we have a one page Product Efficiency Survey on our website (exair.com/labdoc) where you can provide us the details about a current inefficient compressed air application. Fill in the information and click submit. You will hear from one of our Application Engineers within three business days.

Okay, so what is the fine print?

This service is available to all customers in the U.S. and Canada only. Some restrictions may apply.

What about confidentiality?

Yes, EXAIR will keep the results of our Efficiency Lab test and report confidential unless given permission to share that information with others.

Products must be shipped to EXAIR freight prepaid EXAIR will pay the return shipping via UPS ground.







EasySwitch Wet-Dry Vac



Built to Las

WARRANT

EasySwitch® Wet-Dry Vac

Make the seamless transition from a dry material vacuum to liquids with ease!

What is the EasySwitch Vacuum?

EXAIR's patent-pending EasySwitch vacuum simplifies the filter change process when switching from vacuuming a dry material to a liquid or vice versa. Utilizing minimal compressed air, the EasySwitch is a powerful pneumatic vacuum that is ideal for any application - wet, dry, light and heavy.

The EasySwitch is designed to handle the toughest of industrial cleanup jobs with ease. EXAIR's EasySwitch vacuum uses a standard or HEPA certified filter when vacuuming dry material. The fast and simple conversion to vacuuming liquids is done by releasing one latch and simply removing the filter element. Using only

compressed air, the EasySwitch vacuum creates a powerful vacuum without the need for electricity. Because the vacuum generator has no moving parts and uses no electricity, there is little concern for failed parts, motor failure or personnel safety associated with using electric vacuums for liquids.



Why the EasySwitch Vacuum?

The EasySwitch vacuum is an all-purpose pneumatic vacuum with the capability

of handling any job-dry or wet. Switching between vacuuming liquids or solids is as easy as removing the pleated filter when vacuuming liquids, and reinstalling directly into the open filter hatch when working with dry material. Like most of EXAIR's Intelligent Compressed Air* products, this compressed air-driven vacuum functions at a quiet 79 decibels without purchasing additional noise muffling accessories. This quiet operation feature protects operator hearing. In addition, the EasySwitch vacuum generally uses less compressed air to produce better or similar performance than other pneumatic competition. The EasySwitch vacuum also features accessory options of both a standard and anti-static vacuum hose, drum dolly for convenient movement, premium metal attachments and tool holder. Providing customers with an effective and adaptable method of cleanup, the EasySwitch vacuum is your allencompassing solution to industrial housekeeping.

Applications

- Coolant
- Chips
- Floor Cleanup
- Drains
- Shavings
- Sawdust
- Absorbent
- Mold and allergen removal

Advantages

- · Easy to switch from liquid to dry material
- · High performance with minimal air requirements
- · Low sound level
- · Maintenance free
- · Safe no electricity
- · Spill free auto safety shutoff
- No motors to clog or wear out
- Continuous duty



Do Not Use With Combustible Dust

vvarnin

Warnina:

Do Not Use With Any Material With A Low Flash Point Or With Flammable Liquids Such As Fuel Oil, Alcohol, Mineral Spirits, Gasoline Or Kerosene.



How The EasySwitch Wet-Dry Vac Works

The EasySwitch vacuum utilizes a filter hatch, secured by one simple latch, for easy installation and replacement of filters. It does not require any additional springs, clips or closures. A rubber handle (1) is connected to the filter latch (2). Unlatching the handle from the drum lid will allow the hatch to be raised. When the hatch is raised, the filter (3) can be installed or uninstalled easily. The filter simply lifts out of the filter hatch hole, and be can reinstalled by placing the filter on top of edge gasket (4) on the filter hatch hole. For operation, close the hatch and secure the rubber handle (1). When the filter is installed, the vacuum will work with dry media and, when it is uninstalled, it will work with liquids. When the drum is filled with liquid, the vacuum is automatically turned off by a float shutoff.



The Model 6101 EasySwitch Vac System includes a standard filter, 10' (3m) hose, 20' (6.1m) compressed air hose, plastic tools, shutoff valve and gauge. HEPA version also available.



I PM

2,548

2,605

2.661



Premium EasySwitch Vac Systems add a 55 gallon drum.

The Model 6201 Deluxe EasySwitch Vac System comes complete with standard filter, 10' (3m) static resistant hose, 20' (6.1m) compressed air hose, shutoff valve, gauge, heavy duty tools, tool holder and drum dolly. HEPA version also available.

65 Conveying Rate Comparison for EasySwitch Wet-Dry Vac

1,840

Pressure Supply		Wa	ter		umbling dia	Steel Shot		
PSIG	BAR	GPM	LPM	Lbs/ min	kg/ min	Lbs/ min	kg/ min	
80	5.5	36	136	68	31	54	24	

-210 -392

Model #	Description
6101	55 Gallon EasySwitch Wet-Dry Vac System includes the EasySwitch Vac unit, EasySwitch drum lid, standard filter, pre-filter, 1/2" compressed
	air hose assembly, pressure gauge, 10' of 1.5" vacuum hose, crevice tool, 19" straight wand, skimmer tool and dust brush. (drum not included)
6201	55 Gallon Deluxe EasySwitch Wet-Dry Vac System - same as Model 6101 and adds a drum dolly, an upgrade to 10 feet of 1.5" antistatic hose,
6201	spill recovery kit, extension wand, round dust brush, 24" and 11" crevice tools, 12" wide floor tool and tool holder. (drum not included)
6301	55 Gallon Premium EasySwitch Wet-Dry Vac System - same as Model 6201 and adds a 55 gallon drum.
	55 Gallon HEPA EasySwitch Wet-Dry Vac System includes the EasySwitch Vac unit, EasySwitch drum lid, HEPA filter and pre-filter,
6103	1/2" compressed air hose assembly, pressure gauge, 10' of 1.5" vacuum hose, crevice tool, 19" straight wand, skimmer tool and dust
	brush. (drum not included)
6203	55 Gallon Deluxe HEPA EasySwitch Wet-Dry Vac System - same as Model 6103 and adds a drum dolly, an upgrade to 10 feet of 1.5" antistatic
	hose, spill recovery kit, extension wand, round dust brush, 24" and 11" crevice tools, 12" wide floor tool and tool holder. (drum not included)
6303	55 Gallon Premium HEPA EasySwitch Wet-Dry Vac System - same as Model 6203 and adds a 55 gallon drum.

	Accessories							
Model #	Description	Model#	Description					
902100	Standard Filter for EasySwitch Vac	902032	Replacement EasySwitch Vacuum Unit Gasket					
902200	HEPA Filter	902184	Replacement Filter Port Gasket					
902146	Pre-Filter for EasySwitch Vac	901176	Magnetic Tool Holder					
902176	Replacement Muffler Material	902187	Latch Repair Kit					
902031	Replacement Drum Lid Gasket	902190	Replacement E-Clip for Hinge					

90 6.2 59 1,670 -190 -355

100 6.9















Product

Reversible Drum Vac™

Pump 55 gallons in 90 seconds! Two-way pumping action!

What Is The Reversible Drum Vac?

A safe, maintenance free way to recover:

- Coolant Sludge and chips
- Hvdraulic oils Tramp oil · Liquid spills · Waste water

Why The Reversible Drum Vac?



EXAIR's compressed air operated Reversible Drum Vac System attaches quickly to any closed head 30, 55 or 110 gallon drum. Its high powered vacuum fills a 55 gallon drum in less than two minutes. With the simple turn of a knob, the same stainless steel pump quickly empties the drum. www.exair.com/dvvideo.htm Coolant sumps can be easily refilled, floor spills

vacuumed, or contaminated liquids transferred to filtration tanks in minutes. The flow rate in and out of the drum can be controlled with the knob, making it ideal for dispensing liquids.

EXAIR's Mini Reversible Drum Vac System delivers the same two-way action for small jobs. It comes complete with a 5 gallon drum and all the tools.

Electrically operated "all purpose" vacuums aren't designed for use in industrial environments. As a result, motors wear out quickly and impellers clog. The Reversible Drum Vac does not use electricity and has no moving parts, assuring maintenance free operation. An automatic safety shutoff valve prevents spills or overfilling.



Applications Coolant sumps

- Food processing
- Lathes
- Floor cleanup
- EDM machines
- Pits
- Screw machines
- Machining centers
- Tanks

Advantages

- No moving parts
- · Maintenance free
- Stainless steel construction
- Safe no electricity
- Built-in pressure/vacuum relief
- · Compact and portable
- · Installs quickly
- · Spill free auto safety shutoff
- · Fits standard closed head drums



EXAIR's Mini Reversible Drum Vac

up of small messes.

Model 6901 Spill Recovery Kit used with the Mini Reversible Drum Vac provides fast cleanup of messy spills.



Reversible Drum Vacs are designed to fit the 3/4 NPT bung of any closed top drum. This model 6196-30 30 gallon system empties the coolant sump of a CNC.






Pressure Supply 80 PSIG (5.5 BAR)	Air Consumption		Li		Water S Flow Rate		
DESCRIPTION	SCFM	SLPM	"H ₂ O	mm Hg	GPM	LPM	
REVERSIBLE DRUM VAC	19	538	96	179	30	114	dBA



The Model 6196, Model 6196-30 and Model 6196-110 Reversible Drum Vac Systems include a vacuum hose and an aluminum wand.





The flex hose (1) is attached to the barbed connection (2) on the Reversible Drum Vac system. The knob (3) on the Reversible Drum Vac pump is set to the "fill" position. The air supply valve (4) is opened to permit compressed air at 80-100 PSIG (5.5 - 6.9 BAR) to flow through the Reversible Drum Vac pump which pulls liquid through the flex hose and into the drum. When all liquid is in the drum, the air supply is turned off. If liquid exceeds the drum capacity, the safety shut-off valve (5) will prevent overfilling. The liquid can then be pumped back out of the flex hose (1) by setting the knob (3) on the Reversible Drum Vac pump to the "empty" position and opening the air supply valve.







Reversible Drum Vac System includes a 5 gallon drum w/lid, ABS spill recovery kit, vacuum hose and all tools.

Model 6196-5 Mini

Model 6296 and Model 6296-30 Deluxe Reversible Drum Vac Systems include a drum dolly, ABS spill recovery kit, vacuum hose, tool holder and all tools.



Premium Reversible Drum Vac Systems include the drum, drum dolly, an upgrade to heavy duty aluminum tools, ABS spill recovery kit, tool holder and air hose.

Reversible Drum Vac Systems

1	Model#	Description							
	6196	55 Gallon Reversible Drum Vac System includes two-way pump assembly (1/4 NPT), shutoff valve, 10' (3m) flexible							
	0190	vacuum hose (1-1/2"/38mm I.D.) with 90° quick release elbow connection, (1) aluminum wand (drum not included).							
	30 Gallon Reversible Drum Vac System - same as Model 6196 except fits a 30 gallon drum (drum not included).								
6196-110 110 Gallon Reversible Drum Vac System - same as Model 6196 except fits a 110 gallon drum (drum not									
	6196-5	5 Gallon Mini Reversible Drum Vac System includes two-way pump assembly (1/4 NPT), shutoff valve, 5 gallon container with lid and lock ring, 10' (3m) flexible vacuum hose (1-1/2"/38mm I.D.) with 90° quick release elbow connection, aluminum wand, ABS spill recovery kit, (2) extension wands, crevice tool and skimmer tool.							
6296 55 Gallon Deluxe Reversible Drum Vac System - same as Model 6196 and adds drum dolly, ABS spill rec (2) extension wands, crevice tool, skimmer tool and tool holder (drum not included).									
•	6296-30	30 Gallon Deluxe Reversible Drum Vac System - same as Model 6296 except fits 30 gallon drum (drum not included).							
	6296-5	5 Gallon Deluxe Mini Reversible Drum Vac System - same as Model 6196-5 and adds drum dolly.							
	6396	55 Gallon Premium Reversible Drum Vac System - same as Model 6196 and adds the 55 gallon drum with lock ring and lid, drum dolly, ABS spill recovery kit, 11" (279mm) and 24" (610mm) aluminum crevice tools, skimmer tool, tool holder and 20' (6.1m) air hose.							
	6396-30	30 Gallon Premium Reversible Drum Vac System - same as Model 6396 except includes a 30 gallon drum.							
6	5396-110	110 Gallon Premium Reversible Drum Vac System - same as Model 6396 except includes a 110 gallon drum.							
	6091	Reversible Drum Vac Only - included in all systems listed above.							
		Assessming							



Model #	Model # Description		Description
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)	901071	Heavy Duty Aluminum Tools plus Tool Holder
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)	9041-5	5 Gallon Drum Dolly
901067-5			30 Gallon Drum Dolly
901067-30			55 Gallon Drum Dolly
901067			110 Gallon Drum Dolly
901067-110 110 Gallon Drum with lock ring and lid		6901	Spill Recovery Kit includes a one-piece 54" (1372mm)
901007-110	110 Gallott Drutti with lock filig and lid	0901	ABS wand and 14" (356mm) double blade squeegee tool.
6569-20 20' (6.1 m) Flexible Vacuum Hose (1-1/2"/38mm I.D.)		901176	Magnetic Tool Holder









High Lift Reversible Drum Vac COMPRESS

Drum Vac



Drum Vac

High Lift Reversible Drum Vac™

Two-way pump provides maximum lift (up to 15 feet)!

Move thick liquids (up to 1400 cP) through 20' of hose!

What Is The High Lift Reversible Drum Vac?

A safe, powerful, and maintenance free way to recover:

- Coolant
- · Sludge and chips
- Hydraulic oils
- Tramp oil
- Liquid spills
- Waste water

Why The High Lift Reversible Drum Vac?

EXAIR's compressed air operated High Lift Reversible Drum Vac System attaches quickly to any closed head 30, 55 or 110 gallon drum. Its high powered vacuum is able to lift liquids up to 15 feet and fill a 55 gallon drum in less than 85 seconds. With the simple turn of a knob, the same stainless steel pump quickly empties the drum. The High Lift Reversible Drum Vac has the extra power you need to move liquids from below grade work areas, sumps or tanks up to 15 feet deep!

Like all of EXAIR's industrial vacuums, the High Lift Reversible Drum Vacuses no electricity and has no moving parts which assures maintenance free operation. It is designed for continuous and heavy duty applications where electric vacuums fail due to motor wear or clogged impellers. This vacuum efficiently and safely uses the compressed air in your facility. An automatic safety shutoff valve prevents overfilling.

Applications

- · Below grade coolant sumps
- · Deep wells
- · Underground storage tanks
- Pits
- Drains
- · Deep hole broaching
- · Bulk storage tanks
- Cisterns

Advantages

- · No moving parts
- · Maintenance free
- · Stainless steel construction
- · Safe no electricity
- · Built-in pressure/vacuum relief
- Compact and portable
- · Installs quickly
- · Spill free auto safety shutoff
- · Fits standard closed head drums

Pump Farther Pump Higher Pump Thicker Liquids

from

15 Feet

If you need assistance choosing the right High Lift Reversible Drum Vac System, please contact an Application Engineer to discuss your application.

High Lift Reversible Drum Vac System Specifications

Pressure Supply 80 PSIG (5.5 BAR)		ir nption	Li	ft			Sound Level
DESCRIPTION	SCFM	SLPM	"H ₂ O	mm Hg	GPM	LPM	83
HIGH LIFT REVERSIBLE DRUM VAC	43	1,218	180	336	30	114	dBA



The flex hose (1) is attached to the barbed connection (2) on the Reversible Drum Vac system. The knob (3) on the High Lift Reversible Drum Vac pump is set to the "fill" position. The air supply valve (4) is opened to permit compressed air at 80-100 PSIG (5.5 - 6.9 BAR) to flow through the High Lift Reversible Drum Vac pump which pulls liquid through the flex hose and into the drum. When all liquid is in the drum, the air supply is turned off. If liquid exceeds the drum capacity, the safety shut-off valve (5) will prevent overfilling. The liquid can then be pumped back out of the flex hose (1) by setting the knob (3) on the High Lift Reversible Drum Vac pump to the "empty" position and opening the air supply valve.

Warning: Do not use with any material with a low flash point or with flammable liquids such as fuel oil, alcohol, mineral spirits, gasoline or kerosene.

Description



Model 6195, Model 6195-30 and Model 6195-110 **High Lift Reversible Drum Vac Systems** include a vacuum hose and an aluminum wand.



Model 6295 and Model 6295-30 Deluxe High Lift Reversible Drum Vac Systems include a drum dolly, ABS spill recovery kit, vacuum hose, tool holder and all tools.



Premium High Lift Reversible Drum Vac Systems include the drum, drum dolly, an upgrade to heavy duty aluminum tools, ABS spill recovery kit, tool holder and air hose.







Deluxe and Premium High Lift Drum Vac Systems include a drum dolly.

rible vacuum hose
).
, (2) extension
ded).
ng and lid, drum m) air hose.

		Accessor

Model #	Model # Description 9001 Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM) 9006 Oil Removal Filter, 3/4 NPT, 50-150 SCFM (1,416-4,248 SLPM) 901067-30 30 Gallon Drum with lock ring and lid 901067 55 Gallon Drum with lock ring and lid 901067-110 110 Gallon Drum with lock ring and lid 901067-110 110 Gallon Drum with lock ring and lid 901067-110		Description
9001			Heavy Duty Aluminum Tools plus Tool Holder
9006			30 Gallon Drum Dolly
901067-30			55 Gallon Drum Dolly
901067			110 Gallon Drum Dolly
901067-110			Spill Recovery Kit includes a one-piece 54" (1372mm) ABS wand and 14" (356mm) double blade squeegee tool.
6569-20 20' (6.1m) Flexible Vacuum Hose (1-1/2"/38mm I.D.)		901176	Magnetic Tool Holder









Model #

CE







Chip Trapper



Chip Trapper[™]

Filter the chips out of your used coolant and cutting oils!

Vacuums in the liquid with solids, pumps out only the liquid!

What Is The Chip Trapper?

The patented* Chip Trapper offers a fast, easy way to clean chips, swarf and shavings out of used coolants and other liquids. The Chip Trapper vacuums the coolant or liquid that is filled with debris and traps all the solids in a reusable filter bag. Only the liquid pumps back out. It is ideal for use on machines with



sumps, parts washers, tanks and storage containers of contaminated liquids.

The Chip Trapper uses EXAIR's compressed air powered Reversible Drum Vac (included) that can fill or empty a 55 gallon drum in less than two minutes. Simply set the Reversible Drum Vac pump and directional flow control valve on top of the drum to "fill" for it to quickly

vacuum the liquid with solids. Once the sump, pit or tank is empty, set the pump and directional valve to "empty" for it to pump out clean coolant/liquid. All the chips and other solids are trapped inside the reusable filter bag of the Chip Trapper.

Why The Chip Trapper?

A sudden lack of coolant flow in a machining operation will likely damage the part and expensive tooling. Machine tools commonly discharge some chips and shavings into the coolant sump. As the chips accumulate and mound up, the coolant flow used to flood the part and tooling becomes restricted. Some high pressure coolant systems sound an audible alarm and abruptly shut down the machine when low coolant flow occurs. This results in downtime to fix the problem and clear the alarm. That isn't the case with standard machines where immediate damage can occur if the operator fails to spot the lack of coolant. Regular cleaning of the coolant sump with the Chip Trapper can quickly eliminate this very costly problem.

Applications

- CNC's
- Lathes
- Saws
- Mills
 Drills
- Parts washers
- Pits
- Tanks
- Containers
- Grinders

*Patent #8153001 and #8268179

- ations Advantages
 Removes unwa
 - Removes unwanted solids from liquid
 - · Recycles coolants
 - No moving parts
 - · No motors to clog or wear out
 - Self priming stainless steel pump
 - · Safe no electricity
 - · Built-in pressure/vacuum relief
 - · Drum is included
 - Spill free auto safety shutoff
 - Quiet



Chips can accumulate in the sump, restricting coolant flow.

Chip Trappel



The Chip Trapper pumps the coolant back into the sump – free of chips and debris.



Chip Trapper filters out solids from parts washer fluids.





How The Chip Trapper Works

The vacuum hose (1) is attached to the barbed connection of the Chip Trapper (2). The directional flow control valve on top of the drum (3) and knob on the pump (4) are set to the "fill" position. The air supply valve is opened to permit compressed air at 80-100 PSIG (5.5 - 6.9 BAR) to flow through the pump which pulls the liquid through the hose, then into the reusable filter bag (5). When all liquid is in the drum, the air supply is turned off. The filtered liquid can then be pumped out by setting the directional flow control valve on top of the drum and the knob on the pump to the "empty" position. Once the air supply valve is opened, the air pushes the liquid back through the hose while all solids remain in the reusable filter bag.

Warning: Do not use with any material with a low flash point or with flammable liquids such as fuel oil, alcohol, mineral spirits, gasoline or kerosene.

Chip Trapper System Specifications

Pressure Supply 80 PSIG (5.5 BAR)	Air Consumption		Water Flow Rate		Sound Level	
DESCRIPTION	SCFM SLPM		GPM	LPM	86	
CHIP TRAPPER	19	538	30	114	dBA	

The filter bag included with the system provides 5 micron filtration.

Built To Last

The stainless steel pump has no motors or impellers to clog or wear out and there is no electricity or shock hazard! Safe operation is assured with a built-in pressure/vacuum relief and an automatic safety shutoff valve that prevents spills or overfilling.



The Chip Trapper includes the pump assembly with directional flow valve, a 30, 55 or 110 gallon drum, 10' (3m) chemical resistant hose, 20' (6.1m) compressed air hose, aluminum chip wand, (2) reusable 5 micron filter bags and drum dolly.



	Chip Trapper Systems							
Model #	Model # Description							
6198	55 Gallon Chip Trapper System includes the Reversible Drum Vac pump assembly, directional flow valve, 55 gallon drum, lever lock drum lid, shutoff valve, 10' (3m) flexible vacuum hose (1-1/2"/38mm I.D.), 20' (6.1m) compressed air hose, chip wand, (2) filter bags and drum dolly.							
6198-30	6198-30 30 Gallon Chip Trapper System - same as Model 6198 except includes a 30 gallon drum							
6198-110	6198-110 110 Gallon Chip Trapper - same as Model 6198 except includes a 110 gallon drum.							
6091	6091 Reversible Drum Vac Only - included in all systems listed above.							

		Acces	sories
Model #	Description	Model #	Description
901060-1	Replacement Filter Bag, 1 micron	901060-200	Replacement Filter Bag, 200 micron
901060	Replacement Filter Bag, 5 micron	901060-SP	Filter Bag Sample Pack- Includes one each 1, 25, 50, 100 & 200 micron bags
901060-25	Replacement Filter Bag, 25 micron	6901	Spill Recovery Kit includes a one-piece 54" (1372mm) ABS wand and
901060-50	Replacement Filter Bag, 50 micron	0901	14" (356mm) double blade squeegee tool
901060-100	Replacement Filter Bag, 100 micron	9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)













High Lift Chip Trapper



High Lift Chip Trapper™

Filter chips and solids out of used coolant and liquids from below grade sumps or elevated tanks!

Vacuum in liquid with solids and pump out only the liquid, with 15 feet of lift!

What Is The High Lift Chip Trapper?

The patented* High Lift Chip Trapper offers a fast, easy way to clean chips, swarf and shavings out of used coolants and other liquids. The High Lift Chip Trapper vacuums the coolant or liquid that is filled with debris and traps all the solids in a reusable filter bag. Only the liquid pumps back out. It is ideal for use on pits, wells, below grade sumps, tanks and storage containers of contaminated liquids.



EXAIR's compressed air operated High Lift Chip Trapper System attaches quickly to the included 30, 55 or 110 gallon drum lid. Its high powered vacuum is able to lift liquids up to 15 feet or pump liquids from as far as 20 feet and fill a 55 gallon drum in less than 85 seconds. With the simple turn of a knob, the same stainless steel pump quickly empties the drum. The High Lift Chip Trapper has the extra power you need to move liquids from below grade work areas, sumps or tanks.

Wells, pits, below grade or elevated tanks can accumulate debris. This debris can cause problems when the liquid is transferred into a machine or process. Waste oil for heating or recycled lubricants which are suitable for dirtier jobs can be used without worry of solids damaging equipment. The heavy duty power of the High Lift Chip Trapper is capable of moving high viscosity liquids up to 1400 centipoise.

Applications

- · Below grade coolant sumps
- Deep wells
- · Underground storage tanks
- Pits
- · Deep hole broaching
- Bulk storage tanks
- Cisterns

*Patent #8153001 and #8268179


Advantages

- · Removes unwanted solids from liquid
- Recycles coolants
- · No moving parts
- · No motors to clog or wear out
- · Self priming stainless steel pump
- · Safe no electricity
- Built-in pressure/vacuum relief
- · Spill free auto safety shutoff
- Ouiet



15 Feet

If you need assistance choosing the right High Lift Chip Trapper System, please contact an Application Engineer to discuss your application.







How The High Lift Chip Trapper Works

The vacuum hose (1) is attached to the barbed connection of the High Lift Chip Trapper (2). The directional flow control valve on top of the drum (3) and knob on the pump (4) are set to the "fill" position. The air supply valve is opened to permit compressed air at 80-100 PSIG (5.5 – 6.9 BAR) to flow through the pump which pulls the liquid through the hose, then into the reusable filter bag (5). When all liquid is in the drum, the air supply is turned off. The filtered liquid can then be pumped out by setting the directional flow control valve on top of the drum and the knob on the pump to the "empty" position. Once the air supply valve is opened, the air pushes the liquid back through the hose while all solids remain in the reusable filter bag.

Warning: Do not use with any material with a low flash point or with flammable liquids such as fuel oil, alcohol, mineral spirits, gasoline or kerosene.

High Lift Chip Trapper System Specifications

Pressure Supply 80 PSIG (5.5 BAR)		ir nption	Li				Sound Level
DESCRIPTION	SCFM	SLPM	"H ₂ O	mm Hg	GPM	LPM	83
HIGH LIFT CHIP TRAPPER	43	1,218	180	336	30	114	dBA

Built To Last

The stainless steel pump has no motors or impellers to clog or wear out and there is no electricity or shock hazard! Safe operation is assured with a built-in pressure/vacuum relief and an automatic safety shutoff valve that prevents spills or overfilling.





The High Lift Chip Trapper includes the pump assembly with directional flow valve, a 30, 55 or 110 gallon drum, 20' (6.1m) chemical resistant hose, 20' (6.1m) compressed air hose, aluminum chip wand, (2) reusable 5 micron filter bags and drum dolly.



The 5 micron filter bag traps all the chips so no solids get pumped back out of the drum.

П	High Lift Chip Trapper Systems							
Г	Model # Description							
55 Gallon High Lift Chip Trapper System includes the High Lift Reversible Drum Vac pump assembly, directional flow valve, 55 gallo drum, lever lock drum lid, shutoff valve, 20' (6.1m) flexible vacuum hose (1-1/2'/38mm I.D.), 20' (6.1m) compressed air hose, chip wa (2) filter bags and drum dollv.								
	6190-30 30 Gallon High Lift Chip Trapper System - same as Model 6190 except includes a 30 gallon drum. 6190-110 110 Gallon High Lift Chip Trapper - same as Model 6190 except includes a 110 gallon drum.							
	6095 High Lift Reversible Drum Vac Only- Included in all systems listed above.							

Accessories					
Model # Description Model #			Description		
901060-1	Replacement Filter Bag, 1 micron	901060-200	Replacement Filter Bag, 200 micron		
901060	Replacement Filter Bag, 5 micron	901060-SP	Filter Bag Sample Pack- Includes one each 1, 25, 50, 100 & 200 micron bags		
901060-25	Replacement Filter Bag, 25 micron	6901	Spill Recovery Kit includes a one-piece 54" (1372mm) ABS wand and		
901060-50	Replacement Filter Bag, 50 micron	6901	14" (356mm) double blade squeegee tool		
901060-100	Replacement Filter Bag, 100 micron	9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)		







Corporation









Chip Vac™

Vacuums chips directly into an open-top drum with no moving parts!

What Is The Chip Vac?

EXAIR's Chip Vac picks up dry or wet chips and delivers them directly to an ordinary open-top drum. The Chip Vac is used to clean chips from fixtures, floors and work surfaces of machining centers, lathes, saws, mills and other industrial equipment. The powerful suction is ideal for fast and efficient cleaning.

EXAIR's Mini Chip Vac System delivers the same cleaning power for small jobs. It comes complete with a 5 gallon drum and all the tools.



Why The Chip Vac?

The compressed air operated Chip Vac is an industrial duty vacuum designed specifically for vacuuming chips. It creates a powerful direct flow action that vacuums metal, wood or plastic chips into an ordinary drum. Designed for occasional use with dusty materials, the included filter bag keeps the surrounding air clean.

Electrically operated "all purpose" vacuums aren't designed for use in industrial environments. As a result, motors wear out quickly and impellers clog. The Chip Vac has no moving parts to wear out or break which ensures long life. Sound level is half that of electric vacs.

The Chip Vac Systems include a drum lid with a locking ring that fits an open top drum. In less than a minute, the Chip Vac can be removed and easily placed onto another drum to keep different materials separate for recycling. Constant heavy lifting and dumping of the vacuum cleaner tanks is eliminated since all chips are vacuumed directly into the drum.

Applications

- CNC's
- Lathes
- Saws
- Mills Drills
- Grinders
- Routers
- Molding machines
- Absorbent pick-up

Advantages

- No moving parts
- Low cost
- · No motors to clog or wear out
- · No electricity
- · Chips go directly into a drum
- Powerful direct flow action
- · Includes accessories
- · 50% guieter than electric vacs





The Chip Vac removes abrasive stainless steel chips from a CNC.



110 Gallon Chip Vac offers maximum capacity cleanup on a large machining operation.



The Mini Chip Vac allows for easy clean up of small messes.



How The Chip Vac Works



Compressed air, normally 80-100 PSIG (5.5 - 6.9 BAR), flows through the inlet (1) into an annular plenum chamber (2). It is then injected into the throat through directed nozzles (3). These jets of air create a vacuum at the intake (4) which draws material in, accelerates it through the unit (5), and directs it to the bottom of the drum. The airflow exhausts through the port in the drum lid. Airborne particles are trapped by the filter bag (6).

The Chip Vac System can be used with an open head steel, fiber or plastic drum that is in good condition (ANSI Standard #MH2-2004). To prevent material contamination, a poly drum liner can be inserted into the drum.

Warning: Do not use with combustible dust.










Deluxe and Premium Chip Vac Systems include a drum dolly.

Chip Vac System Specifications

Size	Pressure	Supply	Air Cons	umption	INLET	Sound	
3126		BAR	SCFM	SLPM	IIVEEI	Level	
110, 55 & 30 Gallon	80	5.5	40	1,132	3/8 NPT	77 -10 4	
5 Gallon	80	5.5	33	934	3/8 NPT	77 dBA	

Air consumption has been minimized by using the appropriate amount of air required for vacuuming chips.







The Model 6193-5 Mini Chip Vac System includes a vacuum hose, 5 gallon drum, chip wand and plastic tools.



Premium Chip Vac Systems include the drum, drum dolly, an upgrade to static resistant hose, heavy duty aluminum tools, tool holder, air hose and guick connects fittings. (Model 6393 shown.)

Chip Vac Systems

Model #	Description		
6193	55 Gallon Chip Vac System includes the Chip Vac, lever lock drum lid, shutoff valve, filter bag, 10' (3m) flexible vacuum hose (1-1/2"/38mm I.D.),		
0193	chip wand, (2) extension wands, crevice tool, brush, skimmer tool (drum not included).		
6193-30	30 Gallon Chip Vac System - same as Model 6193 except fits a 30 gallon drum (drum not included).		
6193-5	5 Gallon Mini Chip Vac System - includes the Chip Vac (3/8 NPT), shutoff valve, filter bag, 5 gallon container with lid and lock ring, 10' (3m)		
0193-3	flexible vacuum hose (1-1/2"/38mm I.D.), aluminum chip wand, (2) extension wands, crevice tool, brush, skimmer tool.		
6293 55 Gallon Deluxe Chip Vac System - same as Model 6193 and adds drum dolly and tool holder (drum not included).			
6293-30 30 Gallon Deluxe Chip Vac System - same as Model 6293 except fits 30 gallon drum (drum not included).			
6293-5	5 Gallon Deluxe Chip Vac System - same as Model 6193-5 and adds drum dolly.		
6393	55 Gallon Premium Chip Vac System - same as Model 6193 and adds a 55 gallon drum, drum dolly, an upgrade to static resistant hose,		
0393	an upgrade to heavy duty aluminum tools, 20' (6.1m) air hose, tool holder and quick connects fittings.		
6393-30	30 Gallon Premium Chip Vac System - same as Model 6393 except includes 30 gallon drum.		
6393-110 110 Gallon Premium Chip Vac System - same as Model 6393 except includes a 110 gallon drum.			
6093	Chip Vac Only - included in all 30 gallon through 110 gallon systems listed above.		
6093-5	Mini Chip Vac Only - included with 6193-5 and 6293-5 5 gallon systems.		

Model #	Description	Model #	Description
6804	Replacement Filter Bag	9041-5	5 Gallon Drum Dolly
901176	Magnetic Tool Holder	9041-30	30 Gallon Drum Dolly
901071	Heavy Duty Aluminum Tools plus Tool Holder	9041	55 Gallon Drum Dolly
6569-20	20' (6.1m) Flexible Vacuum Hose (1-1/2" / 38mm I.D.)	9041-110	110 Gallon Drum Dolly







CE







Heavy Duty Dry Vac



Heavy Duty Dry Vac™

Vacuum more material in less time! Industrial duty vacuum has a rugged construction to resist wear!

What Is The Heavy Duty Dry Vac?

EXAIR's Heavy Duty Dry Vac attaches to an ordinary 30, 55 or 110 gallon open-top drum to turn it into a powerful, industrial duty vacuum cleaner. The Heavy Duty Dry Vac has been engineered to vacuum more dry materials in less time with less wear.

Designed for tough industrial environments, the hardened alloy construction resists premature wear while the increased power handles difficult jobs and harsh conditions. The quiet operation makes it suitable for a wide variety of applications including the clean up of abrasive materials like steel shot, garnet, metal chips and sand while also useful for general purpose applications like vacuuming floors, machines, work stations, industrial machinery and equipment.

Why The Heavy Duty Dry Vac?

Electrically operated vacuums have motors and impellers that clog and wear out quickly. There's also a potential shock hazard when electric vacs are used in standing liquids. The Heavy Duty Dry Vac is compressed air powered which eliminates the shock hazard. It has no moving parts to wear out or break, to assure long life. It is quiet with a sound level that is half that of electric vacs. A static resistant hose prevents painful shocks when vacuuming dry materials.

	Vacuuming Rate Comparison					
	1/4 NPT Pipe Plugs bulk density is 250 lb/ft³ (4005 kg/m³)		Steel Shot (blasting media) bulk density is 317.7 lb/ft³ (5089 kg/m³)			
Standard Chip Vac	11.1 lbs/min (5 kg/min)	27.4 lbs/min (12.4 kg/min)	13 lbs/min (5.9 kg/min)			
HD Dry Vac	26.9 lbs/min (12.2 kg/min)	51.6 lbs/min (23.4 kg/min)	32 lbs/min (14.5 kg/min)			
% Increase	142%	88%	146%			



- Moves more material in less time
 - · Hardened construction resists wear
 - No moving parts maintenance free
 - No motors to clog or wear out
 - No electricity
 - · Continuous duty with high capacity
 - Static resistant hose
 - Quiet
 - · Powerful direct flow action
 - · Heavy duty accessories



The Heavy Duty Dry Vac cleans up a spill of tumbling media.



110 Gallon Heavy Duty Dry Vac provides maximum capacity cleanup for a large, dusty walnut shell blasting application.



Sand that covers the floor around a sand blaster is quickly vacuumed into the drum using the rugged floor tool.



Applications

· Abrasive tumbling media

Industrial machinery

Work surfaces

- Punch presses
- Absorbent pick-up
- Absorberre piek up
- Building maintenance/remodeling
- Saws
- Gravel





Compressed air, normally 80-100 PSIG (5.5 - 6.9 BAR), flows through the inlet (1) into an annular plenum chamber (2). It is then injected into the throat through directed nozzles (3). These jets of air create a vacuum at the intake (4) which draws material in, accelerates it through the unit (5), and directs it to the bottom of the drum. The airflow exhausts through the port in the drum lid. Airborne particles are trapped by the filter bag (6). The Heavy Duty Dry Vac unit (5) and vacuum tools (7) are built to withstand rugged use.

The Heavy Duty Dry Vac's lever lock drum lid fits any open top drum. Moving it from one drum to another can be done quickly, making it easy to keep different materials separate for recycling. All materials are vacuumed directly into the drum, eliminating the heavy lifting that is common with electrically powered vacuums. The Heavy Duty Dry Vac can be used with an open head steel, fiber or plastic drum that is in good condition (ANSI Standard #MH2-2004). To prevent material contamination, a poly drum liner can be inserted into the drum.

Warning: Do not use with combustible dust.

Heavy Duty Dry Vac System Specifications

Model			Air Cons	INLET	Sound Level
ALL	80	5.5	68	3/8 NPT	82 dBA



The Model 6197 Heavy Duty Dry Vac System includes 10' (3m) static resistant hose, 20' (6.1m) compressed air hose, filter bag, aluminum chip wand, shutoff valve and gauge.



The Model 6297 Deluxe Heavy Duty Dry Vac System comes complete with a 10' (3m) static resistant hose, 20' (6.1m) compressed air hose, filter bag, shutoff valve, gauge, heavy duty tools, tool holder and drum dolly.

Premium Heavy Duty Dry Vac Systems are the same as Model 6297 and add either a 30, 55 or 110 gallon drum.

Heavy Duty Dry Vac System

	Model #	Description
	6197	55 Gallon Heavy Duty Dry Vac System includes the Heavy Duty Dry Vac, lever lock drum lid, shutoff valve, filter bag, 10' (3m) polyethylene static resistant hose (1-1/2")38mm I.D.), hose hanger, 1/2 NPT quick connect couplings, 20' (6.1m) air hose with swivel fitting, pressure gauge, and aluminum chip wand (drum not included).
	6197-30	30 Gallon Heavy Duty Dry Vac System - same as the Model 6197 except fits a 30 gallon drum (drum not included).
6297 clude 2 piece doub		55 Gallon Deluxe Heavy Duty Dry Vac System- same as Model 6197 plus drum dolly and heavy duty aluminium tools. Additional tools include 2 piece double bend wand, 12" (305mm) floor tool, 11" (279mm) crevice tool, 24" (610mm) crevice tool, simmer tool with detachable brush, tool holder, and a 3-1/2" (89mm) diameter dust brush with conductive bristles (drum not included).
	6297-30	30 Gallon Deluxe Heavy Duty Dry Vac System - same as the Model 6297 except fits a 30 gallon drum (drum not included).
	6397	55 Gallon Premium Heavy Duty Dry Vac System - same as the Model 6297 and adds a 55 gallon drum.
	6397-30	30 Gallon Premium Heavy Duty Dry Vac System - same as the Model 6397 except includes a 30 gallon drum.
	6397-110	110 Gallon Premium Heavy Duty Dry Vac System - same as the Model 6397 except includes a 110 gallon drum.
	6097	Heavy Duty Dry Vac only - included in all systems listed above.

Acce			iε
------	--	--	----

Model #	Description	Model #	Description
6804	Replacement Filter Bag	9041-30	30 Gallon Drum Dolly
901176	Magnetic Tool Holder	9041-110	110 Gallon Drum Dolly
901071	Heavy Duty Aluminum Tools plus Tool Holder	901069	55 Gallon Drum Only
6580-20	20' (6.1m) Static Resistant Vacuum Hose	901069-30	30 Gallon Drum Only
9041	55 Gallon Drum Dolly	901069-110	110 Gallon Drum Only















Heavy Duty HEPA Vac™

A rugged HEPA quality vacuum! High capacity cleaning for dusty environments!

What Is The Heavy Duty HEPA Vac?

EXAIR's compressed air operated Heavy Duty HEPA Vac attaches to an ordinary 30, 55, or 110 gallon open top drum to turn it into a powerful, HEPA (High Efficiency Particulate Air) quality, industrial vacuum cleaner. Like the Heavy Duty Dry Vac, it's powerfully designed to move more material with less wear. In addition, the Heavy Duty HEPA Vac has been engineered to filter contaminants to HEPA requirements in dusty environments requiring frequent cleaning.

Why The Heavy Duty HEPA Vac?

Engineered for dusty environments that require regular cleaning, the HEPA filter is designed with high capacity in mind. Ordinary vacuums can clog up quickly in environments with an abundance of dust or particulates. An economical, easily maintained pre-filter stops larger particles of debris while the HEPA filter handles smaller matter. All of EXAIR's filters are 100% tested in strict accordance to IEST-RP-CC-007 for minimum 99.97% filtration at the 0.3 micron level to meet HEPA standards. An optional filter protector is available to extend the life of the HEPA filter.

The Heavy Duty HEPA Vac does not use electricity and has no moving parts, assuring maintenance free operation. This eliminates the risk of electric shock often associated with electric shop vacs. Static resistant hose prevents painful shocks when vacuuming dry, dusty materials.





A clogged filtering system for a buffing booth is quickly cleaned and put back into service using the Heavy Duty HEPA Vac.

Applications

- Critical dust removal
- · Clean up around grit and dust producing equipment
- Abrasive media
- Shop floors
- Drywall refinishing
- Industrial contaminants
- Mold and allergen removal
- Trapping dust and airborne irritants
- Eliminate exhaust debris

Advantages

- For frequent use in dusty environments
- Hardened construction resists wear
- · No moving parts maintenance free
- No electricity
- Static resistant hose
- Dust free operation
- Reduces exposure to airborne particulates
- Includes accessories
- Ouiet



A technician uses a Heavy Duty HEPA Vac to perform scheduled maintenance on a pulverizer.





How The Heavy Duty HEPA Vac Works



Compressed air, normally 80-100 PSIG (5.5 - 6.9 BAR), flows through the inlet (1) into an annular plenum chamber (2). It is then injected into the throat through directed nozzles (3). These jets of air create a vacuum at the intake (4) which draws material in, accelerates it through the unit (5), and directs it to the bottom of the drum. The airflow passes first through the pre-filter and then through the 0.3 micron HEPA filter, trapping airborne particles. It then exhausts through the vent in the drum lid (6). The Heavy Duty Dry Vac unit (5) and vacuum tools (7) are built to resist wear.

The Heavy Duty HEPA Vac's lever lock drum lid fits any open top 30, 55 or 110 gallon drum. Moving it from one drum to another can be done quickly, making it easy to keep different materials separate for recycling. All materials are vacuumed directly into the drum, eliminating the heavy lifting that is common with electrically powered vacuums. The Heavy Duty HEPA Vac can be used with an open head steel, fiber or plastic drum that is in good condition (ANSI Standard #MH2-2004). To prevent material contamination, a poly drum liner can be inserted into the drum.

Heavy Duty HEPA Vac System Specifications

Model	Pressure Supply		Air Consumption		INLET	Sound
Model	PSIG	BAR	SCFM	SLPM	INLEI	
ALL	80	5.5	68	1,924	3/8 NPT	82 dBA



The Model 6199 Heavy Duty HEPA Vac System includes HEPA filter, pre-filter, 10' (3m) static resistant hose, 20' (6.1m) compressed air hose, aluminum chip wand, shutoff valve and gauge.



The Model 6299 Deluxe Heavy Duty HEPA Vac System comes complete with HEPA filter, pre-filter, 10' (3m) static resistant hose, 20' (6.1m) compressed air hose, shutoff valve, gauge, heavy duty tools, tool holder and drum dolly. Premium Heavy Duty HEPA Vac Systems are the same

as Model 6299 and add either a 30, 55 or 110 gallon drum.

Warning: Do not use with combustible dust.

Heavy	Duty HE	PA Vac S	ystem:

Model #	Description			
6199	55 Gallon Heavy Duty HEPA Vac System includes Heavy Duty Dry Vac, lever lock drum lid, shutoff valve, pre-filter, HEPA filter, 10' (3m) polyethylene static resistant hose (1-1/2"/38mm I.D.), hose hanger, 1/2 NPT quick connects coupling, 20' (6.1m) air hose with swivel fitting, pressure gauge, and aluminum chip wand (drum not included)			
6199-30	30 Gallon Heavy Duty HEPA Vac System – same as Model 6199 except fits a 30 gallon drum (drum not included).			
6299	55 Gallon Deluxe Heavy Duty HEPA Vac System-same as Model 6199 plus drum dolly and heavy duty aluminium tools. Additional tools include 2 piece double bend wand, 12" (305mm) floor tool, 11" (279mm) crevice tool, 24" (610mm) crevice tool, skimmer tool with detachable brush, tool holder, and a 3-1/2" (89mm) diameter dust brush with conductive bristles (drum not included).			
6299-30	30 Gallon Deluxe Heavy Duty HEPA Vac System – same as Model 6299 except fits a 30 gallon drum (drum not included).			
6399	55 Gallon Premium Heavy Duty HEPA Vac System - same as the Model 6299 and adds a 55 gallon drum.			
6399-30	-30 30 Gallon Premium Heavy Duty HEPA Vac System – same as Model 6399 except includes a 30 gallon drum.			
6399-110	110 Gallon Premium Heavy Duty HEPA Vac System - same as Model 6399 except includes a 110 gallon drum.			
6097	Heavy Duty Dry Vac only - included in all systems listed above.			

Accessories						
Model #	Description	Model #	Description			
901356	Replacement Pre-filter	9041	55 Gallon Drum Dolly			
901357	Replacement HEPA Filter	9041-30	30 Gallon Drum Dolly			
901373	Optional Filter Protector	901176	Magnetic Tool Holder			
901071	Heavy Duty Aluminum Tools plus Tool Holder	901069	55 Gallon Drum Only			
6580-20	20' (6.1m) Static Resistant Vacuum Hose	901069-30	30 Gallon Drum Only			







WARRANT







Vac-u-Gun™

Vacuum, blow and transfer with no moving parts!

Rugged die cast construction for industrial use!



What Is The Vac-u-Gun?

A low cost solution to a wide variety of industrial housekeeping problems. The Vac-u-Gun is a vacuum gun, a blow gun and a transfer tool all in one. Lightweight and easy to use, the Vac-u-Gun has durable die cast construction with no moving parts to wear out.



Why The Vac-u-Gun?

The Vac-u-Gun uses less compressed air than an ordinary blow gun. It injects a small amount of compressed air through directed nozzles to produce a vacuum on one end and a high output flow on the other The amplified output flow is 12 times the air consumption rate.

The Vac-u-Gun offers a more efficient way to blowoff, cool, dry and clean. In vacuum mode, work surfaces can be easily cleaned by vacuuming the debris away instead of blowing it off the surface only to sweep it up later. In blow mode, the Vac-u-Gun has a large 1-1/4" (32mm) diameter that allows it to cover more surface area in less time compared to ordinary air guns. Transferring materials over long distance is also possible using the smooth bore vacuum hose. Three Vac-u-Gun Systems with tools are available.



Model 6192 Vac-u-Gun Collection System with bag vacuums absorbent and chips.

Applications

- Vacuum shavings
- Vacuum absorbent
- Vacuum sawdust
- Vacuum spills
- · Transfer small parts
- Transfer pellets
- Transfer trim
- Blow chips
- Blow water
- · Blow coolant
- Blow scrap

Advantages

- Low cost
- No moving parts maintenance free
- Durable die cast construction
- Switch from vacuum to blow mode in seconds
- · Safe no electricity
- · Meets OSHA pressure requirements
- Vacuum or blowoff
- · Lightweight and portable
- Versatile
- Ouiet




Model 6292 Vac-u-Gun Transfer System carries dust away from sensitive electronic controls.



Model 6392 Vac-u-Gun All Purpose System removes plastic shavings from a saw.








Vac-u-Gun Specifications

Pressure Supply			ir mption	Vac		Fo	orce		Sound Level
PSIG	BAR	SCFM	SLPM	"H ₂ O	kPa	Ozs	Grams	Inlet	84
80	5.5	13	368	-29.5	-7	9	255	1/4 NPT	dBA*

^{*} Tested in "vacuum" mode with bag attached.



Reverse the direction of the nozzle insert to change from vacuum to blowoff.

Versatile

In seconds, the Vac-u-Gun can be transformed from a powerful vacuum gun into an efficient blow gun or into a transfer tool for lightweight materials. Each Vac-u-Gun System comes complete with a set of attachments to suit numerous industrial applications.

Warning: Do not use with combustible dust.



In blow mode, the Vac-u-Gun consumes less air than ordinary blow guns.

Vac-u-Gun Systems



Model 6192 Collection System includes Vac-u-Gun, reusable bag, brush, crevice tool, skimmer tool and (2) extension wands.

Corporation



Model 6292 Transfer System includes Vac-u-Gun, 10' (3m) vacuum hose, brush, crevice tool, skimmer tool and (2) extension wands.



Model 6392 All Purpose System includes Vac-u-Gun, reusable bag, 10' (3m) vacuum hose, brush, crevice tool, skimmer tool and (2) extension wands.

Accessories					
Model #	Description				
9001	Auto Drain Filter Separator, 3/8 NPT, 65 SCFM (1,841 SLPM)				
9005	Oil Removal Filter, 3/8 NPT, 15-37 SCFM (425-1,048 SLPM)				
6092	Vac-u-Gun Only - included with all systems shown above.				









