Fiber polisher



Mr. A.A

Home | Company | LEED | News | Terms | Learning | Career | Contact

Select Language

Powered by Google Translate

V

PRODUCTS Fiber Rotary Joints Electrical Slip Rings Fiber Components Fiber Polishers

SERVICES Fiber Termination Outdoor Fiber Patchcords Laser Pigtailing Training

> SOLUTIONS Sliprings RF Rotary Joints Fluid Rotary Unions Multiplexers Media Converters





ShareThis

FP180e polisher CLICK for larger view

et al. 100.588.8801 🛛 😂 🛤 609.895.9552

Search

FIBER POLISHER: FP180e

Unlike the FP180 series hand polisher, Princetel's FP180e series fiber connector polisher relies on a build-in DC motor to power the turn table. The machine is ideal for small-scale production and laboratory applications. It is also a convenient tool for technicians who terminate fibers in the field.

The motor-driven turn table provides quiet and stable operation. However, when wall power is not available one can power the machine from a car cigarette lighter outlet or an external 6-12 V battery (not included). Adjustable force ensures consistent finish for a wide variety of connector types and the number of connectors in the fixture.

FEATURES

12-V DC motor powered off wall apdater or car cigarette lighter outlet Polish up to three connectors or ferrules simultaneously Quick release for convenient removal of polish fixture Adjustable force for consistent surface finish and different ferrule sizes Low center of gravity for high stability Small footprint for multiple-machine operation Universal fixture fits all connectors with the same ferrule diameter Precise setting of ferrule protrusion for uniform polish results and higher yield

SPECIFICATIONS

PARAMETERS Turntable speed Time control Planetary/spin speed ratio Eccentric distance Force adjustment Fixture capacity Working temperature Storage temperature Motor speed Motor torque Wall power requirement Motor power requirement Adapter output connector Housing material Weight (polisher) Dimensions (lxwxh) VALUES 160 rpm Manual 1:50 5 mm 0-1.2 kg Up to 2 connectors/ferrules (3 optional) -20 to 65 C -40 to 85 C 160 rpm 3 Nm 90-240 VAC, 50-60 Hz, 6 W 12 VDC, 400 mA 5.5-2.1 mm female plug ABS plastic ~2.5 kg 110x80x200 mm

Copyright Princetel, Inc. All rights reserved.