

WL948K

LOVOL

ALFA
SERIES



The LOVOL WL948K ALFA series wheel loader has a 17 tonne operating weight, and 4.8 tonne safe lift capacity with a 3.3m³ bucket. This is a high class machine for serious business operations. Tier 3 Cummins engine - no Adblue, DPF or EGR, with renowned Linde hydraulics HST (hydrostatic) drive system, making for smoother operation, more comfort, less fatigue, and enhanced performance with up to 25% fuel saving, and tyre life, with 80% brake life savings. Compact counter weight makes this the most agile machine in its weight class. L5 radial tyres, hydraulic reversible fan, hydraulic wet brake axles, diff lock, F/R thumb action multi-function joysticks, air suspension seat with rearview camera, A/C, dust-proof luxury cab.

The LOVOL WL948K ALFA series is a machine that rivals the best - and all at a reasonable price!

Features

- Cummins engine - QSB7 6.7L Tier 3
- No Adblue | DPF | EGR
- Linde hydraulic system
- Linde HST drive
- Wet brake axles
- Full hydraulic brakes
- Multi-function Rexroth joysticks
- Hydraulics reversible fan
- Signal banked radiators (no blockage)
- ROP's & FOP's certified cab
- F/R function on joystick
- A/C & heater, sealed cab
- Air suspension seat
- Rearview camera
- Adjustable/sliding arm rest
- Adjustable steering column
- Full LED lighting package
- Reverse alarm
- Battery isolator
- 3m³ GP bucket
- Cutting edge - bolt on/reversible
- Bucket teeth
- Quick hitch

Options

- Auto greaser
- Soft ride - loaded and unloaded
- ISO (Volvo L70 - 120) Quick hitch
- Windscreen glass protection
- 3rd service function/auxiliary hydraulics
- Bulk bucket 4m³ - 5m³
- Pallet forks/hay forks
- Weight scales
- Hydrogen (+10 fuel saving/+30 emissions reduction)
- Mine safety package
- Anti-drop/burst protection (crane) valves



1300 Equip U (378 478)
www.equipmentspecialists.com.au

WL948K

LOVOL



RADIATOR REAR DOOR
Fully raised opening rear door.

SIDE ENGINE COVER
One piece fully opening engine covers creates huge access. No bolted covers to remove.

CAB
Fully lined and sealed low noise, less vibration cab.

ENGINE
Cummins QSB7. Tier 3. No AdBlue DPF, EGR. Limited electronics.

CENTRE PIVOT
Patented composite reinforced pivot structure and bushings.

BUCKET
Choice of buckets. GP, Rock, Coal, Grain, Bulk.

DRIVE LINE
Linde hydrostatic driveline.

RELIABILITY
Strong guard shielded air conditioning system.

BRAKING
Full hydraulic multi disc wet brakes.

LINDE HYDROSTATIC SYSTEM

LINDE HYDRAULIC PUMPS

5 SECONDS 4.8T LIFT

WL948K Specifications		
Item	Units	Value
Operational Weight	kg	16400
Rated load	kg	4800 (4.8 tonnes)
Engine Brand	/	Cummins QSB7
Engine Power	kw/hp	146/195
Transmission	/	Linde hydrostatic drive
Axles	/	Wet brakes with diff lock
Boom lifting time	Sec	5.0
Fuel tank capacity	litre	250
Brakes	/	Full hydraulic wet multi disc
Hydraulic pressure	/	22Mpa (3200psi)
Tyre size	/	20.5R25 L5
Dimensions	mm	7810 long, 2700 wide, 3320 high
Bucket capacity	m ³	3.0
Bucket lift height	mm	4100
Travel speed	km/h	38

Attachments/Dimensions

Rock bucket 2.8m³ Bulk bucket 5.0m³



1300 Equip U (378 478)
www.equipmentspecialists.com.au