



TECHNICAL DATA				
width	840 mm			
depth	885 mm			
height	2140 mm			
WEIGHT(basic version)	218 kg			
VOLTAGE	400V 3N 50Hz			
POWER REQUIRED	12500 W			
WATER HARDNESS	< 8 °F			
WATER CONDUCTIVITY	> 200 µS/cm			
INLET WATER PRESSURE	200-400 kPa			
size allowed	655 mm			
RACK DIMENSIONS	700x700 mm			
RACK EQUIPMENT	1XC86/A - 1XC97/A - 1X91100			
WASHING CYCLES (min)	1 (4)	2 (7)	3 (10)	4 (13)
racks/h(*) ⁽¹⁾	15	8	6	4
WATER CONSUMPTION / CYCLE	4,3 L			
BOILER CAPACITY	15 L			
BOILER HEATING ELEMENT	9000 W			
RINSING TEMPERATURE (SET)	85°C			
TANK CAPACITY	82 L			
TANK HEATING ELEMENT	6000 W			
TANK TEMPERATURE (SET)	55°C			
WASHING PUMP POWER	1750 W (800 l/min ^{***}) x 2			
RINSING PUMP POWER	250 W (150 l/min ^{***})			
DRAIN PUMP (optional)	190 W (120 l/min ^{***})			
ACOUSTIC PRESSURE	69,9 dB(A)			

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.