

TECHNICAL INFORMATION

Cutting capacity at 0°	Round: 350mm Quadrato: 330mm Rectangular: 500x310mm
Cutting capacity ata 45° (sx)	Round: 300mm Quadrato: 300mm Rectangular: 300x300m
Cutting capacity ata 45° (dx)	Round: 300mm Quadrato: 300mm Rectangular: 300x300mm
Cutting csapacity ata 60° (sx)	Round: 150mm Quadrato: 150mm Rectangular: 150x320mm
Cutting capacity ata 60° (dx)	Round: 150mm Quadrato: 150mm Rectangular: 150x320mm
Cutting capacity bundle / scrap-end	Max: 500x250mm Min: 130x20mm Scrap-end: 255mm
Cutting capacity at 0° solids (C45)	250mm
Minimum cutting diameter	10mm
Minimum cutting length	25mm
Minimum scrap-end	240mm (single cut at 0°)
Blade size	4250x34x1.1mm
Blade speed	From 0 to 100 m/min
Blade motor	2.2KW
Blade tension	1900kg/cm2
Feeder length	2000mm with automatic repetition (available also 3000mm option)
Feeder motor power	Brushless BMH 2.5 N-m
Hydraulic unit power	0,55Kw
Sawframe rotation power	0,55Kw
Size - Working plate height	3700x2300x2180mm / h 845mm
Weight	2250kg