

Automan AB (2-10 hp)

Professional Piston Compressors



A solid, robust and reliable compressor for trouble-free operation



1. Pressure reducing valve with quick coupling

The manually adjustable pressure reducer is equipped with quick coupling so it only takes seconds to add a new application to the compressor.

2. Start/stop/auto switch

The built-in, adjustable pressure differential switch allows the compressor to run automatically and maintain a minimum set pressure in the air receiver, giving peace of mind to the operator.

3. Dual purpose belt guard

This solid belt guard not only offers protection for the belt, but also directs cool air over the complete block. This means superior cooling in high ambient conditions.

4. Block

High quality slow running pump equipped with aftercooler. The combination of aluminium and cast iron ensuring a long lifetime.

Tank

The Automan's tank is powder coated, giving it the best protection against damage and corrosion.

6. Handle

Full handle with rubber grip. Designed for the best ergonomy.

7. wheels

High resistance wheels and movable front wheel with break.

Technical specifications

Model	Installed power		Max pressure	Displ.	FAD	Motor Speed	Receiver	Weight
	hp	kW	Bar	L/min	l/min	Rpm	L	kg
AB21-50	2	1.5	10	255	102	1075	50	49
AB21-90	2	1.5	10	255	126	1075	90	56
AB31-90	3	2.2	10	393	228	1050	90	72
AB31-150	3	2.2	10	393	228	1050	150	87
AB31-200	3	2.2	10	393	228	1050	200	91
AB31-270	3	2.2	10	393	228	1050	270	125
AB40-270	4	3	11	553	372	1300	270	120
AB55-150	5.5	4	10	568	415	1400	150	84
AB55-200	5.5	4	10	568	415	1400	200	112
AB55-270	5.5	4	11	568	415	1400	270	154
AB55-500	5.5	4	11	568	415	1400	500	194
AB75-150	7.5	5.5	10	756	586	1400	150	112
AB75-200	7.5	5.5	10	756	586	1400	200	113
AB75-270	7.5	5.5	11	756	586	1400	270	164
AB75-500	7.5	5.5	11	756	586	1400	500	230
AB100-200	10	7.5	10	1233	958	1300	200	143
AB100-270	10	7.5	11	1233	958	1300	270	180
AB100-500	10	7.5	11	1233	958	1300	500	244



