

BLANKET WARMERS

NULINE
REFRIGERATION

FEATURES

- Fan Forced System
- Overheating Alarm
- Safety Cutoff at 70°C
- Double Glazed Doors
- Stainless int./ext. with Chrome Plated Shelves
- Microprocessor Control
- Digital Display with High Alarm
- ARTG Number 257613



	Ambient +5°C to 60°C
	80 L 247 L 611 L 1000 L
	500 x 600 x 625 700 x 700 x 972 750 x 700 x 1880 1200 x 700 x 1935



SURGICAL AND MEDICAL SUPPLIES PTY LTD
16 Kensington Road Rose Park SA 5067
Telephone: (08) 8332 1666 Fax: (08) 8332 5132
Email: sales@surmed.com.au
Website: www.surmed.com.au



BLANKET WARMERS



Model	BW100	BW260	BW650	BW1100
Gross Capacity	80 L	247 L	611 L	1000 L
Blanket Capacity	5 - 6	10 - 12	30 - 35	47 - 52
External Dimensions in mm (w/d/h including castors)	500 x 600 x 625	700 x 700 x 972	750 x 700 x 1880	1200 x 700 x 1935
Internal Dimensions in mm (w/d/h)	390 x 480 x 370	590 x 685 x 600	630 x 610 x 1590	1100 x 550 x 1555
Packed Dimensions in mm (w/d/h including pallet)	575 x 670 x 765	800 x 800 x 1070	850 x 800 x 2030	1300 x 800 x 2085
Gross Weight - kg (packed weight)	63	109	180	260
Net Weight - kg	48	89	160	220
Voltage	240V			
Temperature Range	Ambient +5°C to 60°C			
Exterior Cabinet Finish	Stainless Steel			
Inner Liner Material	Stainless Steel			
Door	Glass			
Door Hinge		RH		LH / RH
Door Handle	Full Length			
Type of Controller	Microprocessor			
Temperature Display	Digital			
BMS Connectivity				
(BMS Connectivity for Remote Alarms only)	Optional			
(BMS Connectivity for 4-20mA Transmitter)	Optional			
Port Entry	Optional			
Power Requirement	10amp GPO			
Castors	Fixed Legs		Yes	
Adjustable Shelves	2	3	5	6
Usable Shelf Area in mm (w/d)	370 x 440	500 x 540	550 x 580	1000 x 510



Nuline Refrigeration reserves the right to alter the specifications without prior notice.