



SCIG



SITRAK

T5G 8x4 Mixer Cab Chasis



(Reference Photo)

EXTERNAL DIMENSIONS

Length(mm)	8250
Width(mm)	2488
Height(mm)(empty)	3155
Wheel base(mm)	1800+2625+1400
Wheel track(mm)	Front 2065 Rear 1850
Approach angle(°)	13
Departure angle(°)	33
Front overhang(mm)	1450

FEATURES

- Reliable MC07 engine with 350Hp and High Torque.
- Allison 4430P transmission with Chelsea PTO
- Comfortable cab for operator comfort.
- Air Suspension Leading safety features include EBS/ESC
- Differential locks and cross locks for when the going gets tough.
- Alloy rim/air tank to reduce tare weight.
- ZF steering pump / Voss connector and other high advanced parts.
- The new G5S offers you flexibility configurations to meet your transportation requirements.



SCIG



SITRAK

Kerb Weight(kg)	8150
Max load of two axles (kg)	Front 6500*2 Rear 18000
GVM (kg)	31000

CAPABILITY

Max speed(km/h)	100
Min turning diameter (m)	23
Max climb gradient (%)	≥25
Fuel tank (L)	220L

CABIN

Model	G5S-M
Sits	2
Turning radius (mm)	2410

ENGINE

Model	MC07H.35-61
Displacement (L)	7.36L
Power rating kW/(r/min)	254/2200
Max torque Nm/(r/min)	1400/1200-1600

CLUTCH

Model	Allison Torque Converter
Mode	Electronic control fluid

TRANSMISSION

Model	Allison4430
Forward gear ratio	4.70,2.21,1.53,1.00,0.76,0.67
Reverse gear	5.55

FRAME

Model	ladder framework
Main beam cross-section (mm)	280×80×8
Width of frame Assembly(mm)	Front 940 Rear 850

DRIVING AXLE

Model	MCY11BES
Main drive Ratio	5.29
Differential lock	Equipped

FRONT AXLE

Model	VPD71DS
-------	---------

SUSPENSION

Front	Model	Non-independence
	Number	3 leaf parabolic
Rear	Model	Non-independence
	Number	Hendrickson 4 airbag

STEERING GEAR

Model	Recirculating ball
Ratio	22.2 ~ 26.2:1
Max pressure of pump (kPa)	20000
Steering way	Recirculating ball hydraulic power

BRAKING SYSTEM

Working pressure (kPa)	1000
Drive braking type	Dual circuit
Brake power adjust type	EBS ESC
Parking brake type	Spring stored energy air cut brake
Assistant brake type	Exhaust brake

ELECTRICS

Circuit type	double, control positive pole
Voltage (V)	24
Generator power (kW)	2.0
Accumulator voltage / capacity(V/Ah)	2x12/180

EXTRAS

Sun visor, side skirts	Included
------------------------	----------