



**<54.7 km**  
Range per Charge



**158.8 kg**  
Weight Capacity



**176 cm**  
Turning Radius



# **PATHRIDER®** **—ENDURANCE—**

## **Built to Handle Adventures!**

Engineered for excitement and built to endure, the Pathrider Endurance paves the way for thrilling adventures ahead. With a swift cruising speed of 9.7 km/h and a single-charge range of up to 54.7 km, its pneumatic tyres are ready to conquer any terrain, whether it's a paved road or a rugged trail. It invites you to expand your horizons and chase after what brings you joy. Loaded with premium features, this ride turns the impossible into possible.



# PATHRIDER® ENDURANCE



Front & Rear Suspension



Right and Left Hand Mirrors



Full Lighting Package

RANGE PER CHARGE (MAX) <sup>1,3</sup>	Up to 54.7 km
MAXIMUM WEIGHT CAPACITY	158.8 kg
TURNING RADIUS <sup>2</sup>	176 cm
MAXIMUM SPEED <sup>1</sup>	9.7 km/h
LENGTH & WIDTH <sup>2,5</sup>	L: 146 cm W: 75.3 cm
SEAT TYPE WIDTH & DEPTH (STANDARD)	High Back Seat W: 55.9 cm (53") D: 50.8 cm (45.7")
SEAT-TO-DECK HEIGHT <sup>2</sup>	45.5 cm - 53 cm
SEAT-TO-GROUND HEIGHT <sup>2</sup>	55.6 cm - 63 cm
GROUND CLEARANCE <sup>2,7</sup>	9.6 cm at transaxle

OVERALL WEIGHT (NOT INC BATTERY) <sup>2,6</sup>	100 kg
WEIGHT OF HEAVIEST PIECE <sup>2</sup>	34 kg (rear section)
SUSPENSION	Front & Rear
3W/4W OPTION	4W
FRONT TYRES	3.5" x 13" pneumatic
REAR TYRES	3.5" x 13" pneumatic
BATTERY REQUIREMENTS	(2) 50AH (Lithium Ion)
BATTERY CHARGER	Off-board, 8A (Lithium Ion)
BATTERY WEIGHT <sup>4</sup>	10.8 kg
COLOUR OPTIONS	■ Black ■ Orange

1. Varies with user weight, terrain type, battery amp hour (AH), battery charge, battery condition and tyre condition. This specification can be subject to a variance of 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of 3%.
3. Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from the theoretical calculations based on battery specification and drive system performance. Test conducted at maximum weight capacity. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3 %.
4. Battery weight may vary based on manufacturer.
5. Width of base (not including seat).
6. Includes standard seat weight.
7. Does not account for anti-tip clearance.

**NOTE:** All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%. Special order seats or non-standard dimensions will not fold-flat and depth-adjustable.