

## SECTIONAL DOORS

# P7 Industrial

The B&D P7™ Industrial door is an innovative, sectional overhead panel door that can be purposely designed to suit its application. The lightweight aluminium frame of the P7 Industrial holds different styles of panel inserts from a range of long lasting, durable materials including acrylic and aluminium. P7 Industrial can be installed with an aluminium finish or with a choice of over 100 powder coat colours – enough to complement any commercial building's décor.



## STANDARD FEATURES

- Large range of sizes from 1370mm (h) x 1800mm (w) to 4500mm (h) x 7620mm (w)
- Range of insert options available to suit your application
- Custom panel sizes and evenly spaced insert openings ensure your door looks symmetrical and aesthetically pleasing
- Soft pliable weatherseal helps stop leaves and rain entering under the door
- Frame manufactured from industrial strength anodised aluminium and available in an extensive powder coating colour selection, to compliment your colour scheme

## P7

### 12 INSERT STYLES TO CHOOSE FROM.

### RUNNING IN 1.5MM GALVABOND® Z250 GUIDES.

Constructed from 1.5mm box shaped aluminium extruded frame, screwed together with a range of insert options to choose from.

### BEST FOR

carparks, private parking, kiosks, shopping centres, shopfronts

### OPENINGS

Range from 1370mm to 4500mm (High) and up to 7620mm (Wide)

### OPERATION

We recommend you automate your P7 Industrial Door. Ask us for the best option for added operational convenience

High cycles spring option available

### RECOMMENDED OPENER

Axess Pro 1505

## DIMENSIONS

SIZE	MINIMUM DOOR SIZE	MAXIMUM DOOR SIZE
Height	1370mm	4500mm
Width	1800mm	7620mm

## INSTALLATION REQUIREMENTS

INSTALLATION CLEARANCES – STANDARD HEADROOM							
HEADROOM (mm)							SIDEROOM (mm)
RECOMMENDED			WITH OPENER*			RECOMMENDED EACH SIDE	
From - To (inc.) Height	Up to 4710W	4710 - 5285W	Over 5285W	Up to 4710W	4710 - 5285W	Over 5285W	
1370 - 2440	340	340	390	440	440	490	120
2445 - 3050	340	340	390	440	440	490	120
3055 - 3660	340	390	390	440	490	490	120
3665 - 4500	390	390	390	490	490	490	120

INSTALLATION CLEARANCES – LOW HEADROOM								
HEADROOM (mm)							SIDEROOM (mm)	
RECOMMENDED			WITH OPENER*			RECOMMENDED EACH SIDE		
From - To (inc.) Height	Up to 4710W	4710 - 5285W	Over 5285W	Up to 4710W	4710 - 5285W	Over 5285W	Up to 15m2	Over 15m2
1370 - 2440	190	190	190	290	290	290	155	195
2445 - 3050	190	190	200	290	290	300	155	195
3055 - 3660	190	200	200	290	300	300	155	195
3665 - 4500	200	200	200	300	300	300	155	195

\*Clearance calculated using Industrial Opener specifications.

## INSERT OPTIONS

