

TECHNICAL INFORMATION

Cutting capacity at 90°	Round: 510mm Square: 480mm Rectangular: 650x450mm
Cutting capacity at 45° (left)	Round: 440mm Square: 430mm Rectangular: 430x430mm
Cutting capacity at 45° (right)	Round: 440mm Square: 440mm Rectangular: 440x440mm
Cutting capacity at 60° (left)	Round: 250mm Square: 250mm Rectangular: 250x450mm
Cutting capacity at 60° (right)	Round: 250mm Square: 250mm Rectangular: 250x450mm
Cutting capacity at 0° bundle - scrapend	Max: 650x450mm Min: 130x20mm Scrap-end: 280mm
Cutting capacity at 0° solids (C45)	280mm (350mm with blade 41mm)
Minimum cutting diameter	10mm
Minimum cutting length	25mm
Minimum scrap-end	265mm (single cut at 90°)
Blade size	5320x34x1.1mm
Blade speed	Da 18 a 100 m/min
Blade power	3KW (4KW motor reducer available with blade 41mm)
Blade tension	1900kg/cm ²
Feeder length	2000mm with automatic repetition (available 3000mm length option)
Feeder motor power	Brushless BMH 2.5 N-m
Hydraulic unit motor power	0.55Kw
Sawframe rotation motor power	0.55Kw
Working table height	845mm
Weight	4000kg
Size	31930x2870x2300mm