Paxum® S300

Paxum Inline Fully Automatic Pallet Wrapping Machine

#62208



Programmable Control

Customizable Options

SIEMENS Control System Remote Control Operation





This cutting-edge machine, equipped with a Motor Drive Conveyor, is tailored to seamlessly integrate into your automatic production line. Partnered with high-quality Paxum Machine Stretch Film, it ensures unparalleled load containment and stability during transportation and storage.

Features

- Customizable Wrapping Cycles
- Automatic Height Testing
- Stainless-Steel Conveyor
- 300% Pre-stretch Ratio
- Programmable Control
- SIEMENS PLC Controls
- Soft Start and Stop
- Ideal for Production Lines
- Maximum Load Capacity: 3000KG
- Efficient and Automatic
- Pallet Grip system
- Slewing Bearing Turntable
- Durable Conveyor
- Remote Control Operation





		•	•				
SI	oe	ci	ПС	O	т	o i	าร
		911			311	Э4	10

Specifications							
Maximum wrap-	30-40 loads/hour	Weighing Scale	Optional				
ping speed							
Load Size Diagonal	1753mm	Machine Weight	980KG				
Maximum Wrap- ping Height	2400mm	Machine Weight	400KG				
Turntable Speed	0-15RPM(Adjustable)	Machine Size	L:2000mm W:1800mm H:3700mm				
Turntable Size	2000mm	Turntable technology	Slewing Ring				
Turntable Drive	1.5PH	Voltage	380V/220V/50HZ 1phase				
Cut And Clamp Film	Automatic (Heat type)	Inverter	X-Line				
Max load weight	3000KG	Position sensor	SICK(Germany)				
Standard Film Width	500mm	PLC	SIEMENS(Hongkong)				
Constant Film Deliv- ery Force	Standard	Travel Switch	OMRON(Japan)				
Standard Pre-Stretch	300% pre-stretch	Motor	GPG				
Roller Materials	Stainless Steel 201	Relay	OMRON(Japan)				
	diameter:89mm						
Film Capacity	250mm Diameter	Touch screen	SIEMENS 7inch				
Film Delivery System	Power Roller -Stretch Plus	Switch	Schneider				
Film Rope System	Standard						