



# Concrete Mixers

## QUALITY JAPANESE MIXERS

- 45 Years in making Mixers!
- Drum & Internals NAW490
- High Tensile COR-TEN steel
- VERY low center of gravity
- 1 Year frame warranty on cracking
- 1 Year warranty on Mixer
- Unique A-frame design with U Bolts
- ZFCML10 Eco-Mix (PMP for 3.6 Mixer)
- All other parts made in Australia - water tank, ladders, steps, extra chutes etc.
- We only use the best quality parts, materials, brass fittings, stainless, nuts & bolts.
- Rear steps, extra chutes etc all powder-coated.
- Intellimix OR Woodtech remotes available
- Kyokuto mixers have been in the Australian market for 4 Years.
- We support servicing & parts with support Agents in other states.

Brought to you by:

**KYOKUTO AUSTRALIA**





## Kyokuto Australian Specifications:

|                         | EA066-30  | EA106-30                      | EA122-30                      | EA148-30                      | EA158-30                                  | EA166-30                                  |                       |
|-------------------------|---|-------------------------------|-------------------------------|-------------------------------|---|---|-----------------------|
| Drum Capacity           | 6.6m <sup>3</sup>   | 10.6m <sup>3</sup>            | 12.2m <sup>3</sup>            | 14.8m <sup>3</sup>            | 15.8m <sup>3</sup>                        | 18.6m <sup>3</sup>                        |                       |
| Max. agitating capacity | 4m <sup>3</sup>   | 7m <sup>3</sup>               | 8m <sup>3</sup>               | 9m <sup>3</sup>               | 10m <sup>3</sup>                          | 12m <sup>3</sup>                          |                       |
| Max. mixing capacity    | 3.6m <sup>3</sup>   | 6.5m <sup>3</sup>             | 7.6m <sup>3</sup>             | 8.5m <sup>3</sup>             | 9.5m <sup>3</sup>                         | 11.5m <sup>3</sup>                        |                       |
| Drum revolution speed   | 0-13rpm   | 0-15rpm                       | 0-15rpm                       | 0-15rpm                       | 0-15rpm                                   | 0-15rpm                                   |                       |
| Dimension               | Unit overall length (Approx.)                                 | 4105mm                        | 5500mm                        | 5650mm                        | 6400mm                                    | 6650mm                                    | 7450mm                |
|                         | Unit overall height (Approx.)                                 | 2300mm                        | 2350mm                        | 2400mm                        | 2750mm                                    | 2800mm                                    | 2900mm                |
|                         | Drum inside length  |                               | 4085mm                        | 4285mm                        | 4890mm                                    | 5095mm                                    | 5855mm                |
|                         | Drum inside diameter  |                               | 2100mm                        | 2300mm                        | 2300mm                                    | 2300mm                                    | 2300mm                |
|                         | Manhole diameter  |                               | 600mm                         | 650mm                         | 650mm                                     | 650mm                                     | 650mm                 |
|                         | Hopper (Width x Length)                                       |                               | 1000mm x 930mm                | 1000mm x 930mm                | 1000mm x 930mm                            | 1000mm x 930mm                            | 1000mm x 930mm        |
|                         | Chute length (Main + Sub)                                     |                               | 1800mm x 680mm                | 1800mm x 680mm                | 1800mm x 680mm                            | 1800mm x 680mm                            | 1800mm x 680mm        |
| Drum & Blade material   | Weather proof & high tensile steel (4.0mm, NAW490 - B480GNQR) |                               |                               |                               |   |   |                       |
| Drum inclination angle  | 18 °  | 16 °                          | 16 °                          | 13 °                          | 13 °                                      | 11 °                                      |                       |
| Discharging speed       | Slump value = 5cm   | 3m <sup>3</sup> /5min         | 3m <sup>3</sup> /5min         | 3m <sup>3</sup> /5min         | 3m <sup>3</sup> /5min                     | 3m <sup>3</sup> /5min                     | 3m <sup>3</sup> /5min |
|                         | Slump value = 20cm  | 3m <sup>3</sup> /1min         | 3m <sup>3</sup> /1min         | 3m <sup>3</sup> /1min         | 3m <sup>3</sup> /1min                     | 3m <sup>3</sup> /1min                     | 3m <sup>3</sup> /1min |
| Reduction gear          | PMP Hydro Motor   | ZF CML10 ECO-MIX              | ZF CML10 ECO-MIX              | ZF CML12 ECO-MIX              | ZF CML12 ECO-MIX                          | ZF CML14 ECO-MIX                          |                       |
| Hydraulic pump          | PMP   | Rexroth                       | Rexroth                       | Rexroth                       | Rexroth                                   | Rexroth                                   |                       |
| Hydraulic motor         | PMP Hydro Motor   | ZF CML10 ECO-MIX              | ZF CML10 ECO-MIX              | ZF CML12 ECO-MIX              | ZF CML12 ECO-MIX                          | ZF CML14 ECO-MIX                          |                       |
| Oil cooler              | YS-12L  | YS-18L                        | YS-18L                        | YS-26L                        | YS-26L                                    | YS-26L                                    |                       |
| Water tank capacity     | Alloy 200L<br>(300L optional)                                 | Alloy 200L<br>(300L optional) | Alloy 200L<br>(300L optional) | Alloy 200L<br>(300L optional) | (STD) 300ltr<br>(500ltr, 600ltr optional) | (STD) 300ltr<br>(500ltr, 600ltr optional) |                       |



**Contact Dave today!**

**PHONE**  
0405 743 170



**EMAIL**  
dave@kyokutoaustralia.com.au  
**WEB**  
kyokutoaustralia.com.au



11 ENTERPRISE STREET,  
CALOUNDRA WEST 4551  
SUNSHINE COAST QLD