

KR 2700 CE EAC



Semi-automatic Car Tire Changer

Cylindrical vertical tower, for rims up to 24"



IT type: Bead Seater (Tubeless Inflator)

Technical Specification:

Outer Clamping Size	Inner Clamping Size	Max. Wheel Dia.	Max. Wheel Width	Beadbreaking Force	Operating Pressure	Power Supply	Motor Power
12"-24"	10"-22"	1040MM	3"-15"	2700 KG	8-10 BARR	220V/50HZ/1PH 380V/50HZ/3PH	1.1KW 0.75KW

Technical Features

- ✗ Swing horizontal arm with Ø41mm hexagon shaft.
- ✗ Cylindrical vertical tower featuring high torsional rigidity.
- ✗ Mechanical locking and vertical adjustment of mounting arm.
- ✗ Tools head with interchangeable plastic inserts for rim protection.
- ✗ Self-centering four-jaws with double pneumatic cylinder for secure clamping of all rim types.
- ✗ Powerful clamping cylinders provide uniform clamping pressure.
- ✗ Clockwise and anticlockwise rotation of the turntable through electric motor.
- ✗ The pedal assembly can be removed allowing easy servicing.
- ✗ Tire inflation unit mounted on column with inflation tube, pressure gauge and pressure release button
- ✗ Protection kit for bead breaker shoe, demounting head and clamping jaw comes standard.
- ✗ Complete with lubrication filter and pressure regulator.



Technical Details



Stainless tool head with interchangeable plastic inserts to protect rims.



Tire inflation unit mounted on column with inflation tube, pressure gauge and pressure release button




Premium quality pressure regulator with water filter and lubricator.



Powerful bead breaker with 2700kg capacity.



Extractable pedal assembly for easy maintenance



Self-centering four-jaws with double pneumatic cylinder for secure clamping of all rim types.



Hexagon shaft locking handle



Swing horizontal arm with Ø41mm hexagon shaft.



Tyre Paste Container



Paste Brush



Tool Head Protection



Bead Breaker Protection



Claw Protection



Tyre Lever

Standard Accessories