



CUSHMAN®

## HAULER® 800X



### MAKE TOUGH JOBS A WALK IN THE PARK.

Every part of the Cushman® Hauler® 800X utility vehicle is designed to take on tough jobs. From an 8.4-cubic-foot cargo bed, to bench seating, to a lifted suspension and trail tires, it can navigate off the beaten path without breaking a sweat. With the option of a fuel-efficient 13.5 hp Kawasaki® gas-powered engine, or a quiet, zero-emissions 48V AC electric drivetrain, the power to boost performance is in your hands. It's time to see what utility really means. Take the Hauler 800X for a drive.

**13.5 HP**  
KAWASAKI®  
GAS ENGINE

**8.4 CU FT**  
CARGO BED

**16.5 MPH**  
MAX SPEED

**48V AC**  
ELECTRIC  
DRIVETRAIN





## CUSHMAN® HAULER® 800X



### OPTIONS & ACCESSORIES

- Improved Surface Tires\*
- Brake Lights\*
- Taillights\*
- Fuel/Oil Gauge (gas vehicle only)\*
- On-board Charger (electric vehicle only)\*
- Premium Steering Wheel\*
- 2" Rear Receiver Hitch\*
- LED Headlights with High/Low Beam
- ROPS-Certified Cab
- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- Weather Enclosure
- USB Outlet
- 12-Volt Outlet
- Canopy Storage Net
- Rearview Mirror

\*Included in Commercial Package



**COVERED WITH THE 2-YEAR CUSHMAN CARE TOTAL PROTECTION WARRANTY**

	ELECTRIC MODEL	GAS MODEL
<b>BODY &amp; CHASSIS</b>		
<b>FRAME</b>	Welded Steel w/ E-Shield e-coat plus DuraShield™ Powder Coat	
<b>BODY &amp; FINISH</b>	Injection Molded TPO (Front) / Injection Molded PP (Rear)	
<b>STANDARD COLOR</b>	Patriot Blue	
<b>DIMENSIONS</b>		
<b>OVERALL LENGTH</b>	110 in (279.4 cm)	
<b>OVERALL WIDTH</b>	49 in (125 cm)	
<b>OVERALL HEIGHT</b>	51 in (129.5 cm) (w/o Roof) / 74 in (188 cm) (w/ Canopy)	
<b>WHEEL BASE</b>	65.5 in (166.4 cm)	
<b>WHEEL TRACK</b>	37 in (94.0 cm) Front / 38 in (96.5 cm) Rear	
<b>GROUND CLEARANCE</b>	5.5 in (14.0 cm)	
<b>CARGO DECK CAPACITY</b>	8.4 cu ft (0.24 m³)	
<b>CARGO DECK DIMENSIONS</b>	44.5 in x 28.5 in x 12 in (113 cm x 72 cm x 30.5 cm)	
<b>CARGO DECK MATERIAL</b>	Roto-Molded Polyethylene	
<b>POWER</b>		
<b>POWERTRAIN</b>	48V AC	4-Cycle, 24.5 ci (401cc) Cylinder
<b>VALVE TRAIN</b>	N/A	Single Cylinder OHV
<b>HORSEPOWER (KW)</b>	4.4 hp (3.3 kW) Continuous	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
<b>ELECTRICAL SYSTEM</b>	48V	Starter/Generator. Solid State Reg.
<b>BATTERY (QTY/TYPER)</b>	Six, 8V Deep Cycle	One, 12V Maintenance Free
<b>BATTERY CHARGER</b>	48V DC PowerWise QE, 120V AC, UL/CSA	N/A
<b>KEY OR PEDAL START</b>	Pedal	
<b>AIR CLEANER</b>	N/A	Replaceable Dry Cartridge
<b>LUBRICATION</b>	N/A	Pressurized Oil System
<b>OIL FILTER</b>	N/A	Spin-On
<b>COOLING SYSTEM</b>	N/A	Air Cooled
<b>FUEL CAPACITY</b>	N/A	5.6 Gallon (21.2 L) Tank
<b>SPEED CONTROLLER</b>	235 Amp AC Controller	N/A
<b>DRIVE TRAIN</b>	Motor Shaft Direct Drive	Continuously Variable Transmission
<b>TRANSAXLE</b>	Differential w/ Helical Gears	
<b>GEAR SELECTION</b>	Dash-Mounted Forward-Neutral-Reverse	Forward - Reverse
<b>REAR AXLE RATIO</b>	16.99: 1	11.47: 1 (Forward) 14.53: 1 (Reverse)
<b>PERFORMANCE</b>		
<b>SEATING CAPACITY</b>	2-Person (Bench)	
<b>WEIGHT W/O BATTERIES</b>	756 lb (342.9 kg)	800 lb (362.9 kg)
<b>CURB WEIGHT</b>	1122 lb (508.9 kg)	850 lb (385.6 kg)
<b>VEHICLE LOAD CAPACITY</b>	725 lb (328.9 kg)	
<b>BED LOAD CAPACITY</b>	325 lb (147.4 kg)	
<b>TOWING CAPACITY</b>	500 lb (226.8 kg)	
<b>OUTSIDE CLEARANCE CIRCLE</b>	18.9 ft (5.8 m)	
<b>SPEED</b>	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	
<b>STEERING &amp; SUSPENSION</b>		
<b>STEERING</b>	Self-Compensating Rack & Pinion	
<b>SUSPENSION</b>	Leaf Springs w/ Hydraulic Shock Absorbers	
<b>SERVICE BRAKE</b>	Rear Wheel Mechanical, Self-Adjusting Drum	
<b>PARKING BRAKE</b>	Self-Compensating, Single-Point Engagement	
<b>TIRES (FRONT &amp; REAR)</b>	K500 20 x 8-10 (6 Ply Rated)	

©2018 Textron Specialized Vehicles Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82291-G5 (Rev. 11/2017)